

Vacuum Cylinder

Vacuum pad equipped with Cylinder and Vacuum generator



⚠ Safety instructions for this product

Safety instructions, Common safety instructions for each product category and Detailed safety instructions for each product are in the end of this catalog and our website.

Model Designation (Example)

VSPE (1)	40 (2)	- 10 (3)	L (4)	N (5)	-ER (6)	- 6J (7)
					Optional	

(1) Vacuum Cylinder

(2) Pad size, (4) Pad type (○: Available)

Type	Standard		Skidproof	Bellows	Multi-bellows	Metal detectable	Flat	Flat, Large Suction Flow	Mark-free	Sponge	Soft	Soft bellows	Type	Oval
	General	Deep											Code	E
Code	R	A	K	B	W	BE,BD	F	FH	Q	S	L	LB	Code	E
4													2x4	
6													3.5x7	
8													4x10	
10		M4											5x10	
15													6x10	
20													4x20	
25													4x30	
30													5x30	
35													6x30	
40													8x20	
50													8x30	
		M6												

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

4x10

5x10

6x10

4x20

4x30

5x30

6x30

8x20

8x30

Pad dia. (mm)

2x4

3.5x7

(3) Stroke

Code	5	10	20	30
Stroke (mm)	5	10	20	30

(5) Pad material (○: Available)

Code	N	S	U	F	SE	NE	G	HN	EP	FS	NH	YS2	YS4
Rubber material	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	Food Sanit. Act-compliant NBR	HNBR	EPDM	Fluoro silicone	Oilproof NBR	Extra soft silicone Hardness 20°	Hardness 40°
Standard	R	○	○	○	○	○	○	○	○	○	○	○	○
Deep	A	○	○	○	○	○	○	○	○	○	○	○	○
Soft	L	○	○	○	○	○	○	○	○	○	○	○	○
Soft Bellows	LB	○	○	○	○	○	○	○	○	○	○	○	○
Skidproof	K	○	○	○	○	○	○	○	○	○	○	○	○
Bellows	B	○	○	○	○	○	○	○	○	○	○	○	○
Multi-bellows	W	○	○	○	○	○	○	○	○	○	○	○	○
Flat	F	○	○	○	○	○	○	○	○	○	○	○	○
Flat, Large Suction Flow	FH	○	○	○	○	○	○	○	○	○	○	○	○
Oval	E	○	○	○	○	○	○	○	○	○	○	○	○

*Some rubber materials are not available depending on pad sizes. Please check the page of each pad type for details.

● Metal detectable type (Pad type code: BE, BD)

Code	MSF3	MSF5	MSS3	MSS5
Rubber material	Iron powder type Hardness 30°	SUS powder type Hardness 50°	SUS powder type Hardness 30°	SUS powder type Hardness 50°

● Mark-free type (Pad type code: Q)

Code	K	M	KE
Resin material	PEEK	POM	Conductive PEEK

● Sponge type (Pad type code: S)

Code	S	C
Rubber material	Silicone	Chloroprene

(6) Pad Surface treatment for Suction Mark-free

Optional (○: Available)

Code	No code	-NF	-SF	-DL	-ER	-FG
Surface treatment	No surface treatment	Fiber surface type Nylon fiber	Fiber surface type Silk fiber	DLC. coating	Reformed surface	Fluoro coating
Applicable rubber material	—	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F) Conductive silicone (SE)	Nitrile (N) Conductive NBR (NE)	Silicone (S) Conductive silicone (SE) Extra soft silicone (YS2, YS4)
Standard	R	○	○	○	○	○
Deep	A	○	○	○	○	○
Soft	L	○	○	○	○	○
Soft Bellows	LB	○	○	○	○	○
Bellows	B	○	○	○	○	○
Multi-bellows	W	○	○	○	○	○
Flat	F	○	○	○	○	○
Flat, Large Suction Flow	FH	○	○	○	○	○
Oval	E	○	○	○	○	○

*Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free. Some surface treatments are not available depending on pad sizes. Please check the page of each pad type for details.

(7) Port size and joint type

Code	4J	6J
Fitting type	Push-in fitting	Push-in fitting
Size (O.D. × I.D.)	4×2.5 mm	6×4 mm

Model designation of Holder only (Example)

VSPE (1)	- T15 (2)	- 30 (3)	- 6J (4)
--------------------	---------------------	--------------------	--------------------

(1) Vacuum Cylinder

(2) Connection configuration code

Code	T15	T40	M4	M6
Type	Mount type	Mount type	Screw type	Screw type

*Please select a connection configuration code, referring to the table of (2) Pad size and (4) Pad type under Model Designation (Example) of Vacuum Cylinder.

(3) Stroke

Code	5	10	20	30
Stroke (mm)	5	10	20	30

(4) Port size and joint type

Code	4J	6J
Fitting type	Push-in fitting	Push-in fitting
Size (O.D. × I.D.)	4×2.5 mm	6×4 mm

Characteristics

By just applying compressed air, a work-piece gets sucked and lifted.

The vacuum cylinder is incorporated with a vacuum pad and a vacuum generator.

"M4" and "M6" connection holders are also available.

Various pad types such as Standard and Bellows can be mounted.

Pad Surface treatment for Suction Mark-free (Optional)

NEW Fluoro coating type is a new addition to the surface treatment for Suction Mark-free.

·Fiber surface type ... Raised fiber (nylon or silk) on vacuum pad surface prevents rubber from directly contacting workpieces, and suction marks are minimized.

·DLC. Coating type ... Special chemical coating on vacuum pad achieves minimal friction. It prevents thin/light work-pieces from sticking to the surface of vacuum pad.

·Reformed surface ... Surface of vacuum pad is reformed at molecular level by chemical immersion to reduce suction mark.


·Fluoro coating type ... Surface treatment by fluorine gas prevents a vacuum pad from sticking to a work-piece and prevents below convolutions from sticking to each other. It also improves durability and abrasion resistance.

Vacuum characteristics

Supply pressure (MPa)	Nozzle dia. (mm)	Final vacuum (-kPa)	Suction flow (l/min [ANR])	Air consumption (l/min [ANR])
0.5	0.5	90.7	7	11.5

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Model code	Connection configuration code
Vacuum Cylinder (Soft pad) VSPE	ø4	5	VSPE4-5L[5][6]-[7]	T15
		10	VSPE4-10L[5][6]-[7]	
		20	VSPE4-20L[5][6]-[7]	
		30	VSPE4-30L[5][6]-[7]	
	ø6	5	VSPE6-5L[5][6]-[7]	
		10	VSPE6-10L[5][6]-[7]	
		20	VSPE6-20L[5][6]-[7]	
		30	VSPE6-30L[5][6]-[7]	
	ø8	5	VSPE8-5L[5][6]-[7]	
		10	VSPE8-10L[5][6]-[7]	
		20	VSPE8-20L[5][6]-[7]	
		30	VSPE8-30L[5][6]-[7]	
	ø10	5	VSPE10-5L[5][6]-[7]	T40
		10	VSPE10-10L[5][6]-[7]	
		20	VSPE10-20L[5][6]-[7]	
		30	VSPE10-30L[5][6]-[7]	
	ø15	5	VSPE15-5L[5][6]-[7]	
		10	VSPE15-10L[5][6]-[7]	
		20	VSPE15-20L[5][6]-[7]	
		30	VSPE15-30L[5][6]-[7]	
	ø20	5	VSPE20-5L[5][6]-[7]	
		10	VSPE20-10L[5][6]-[7]	
		20	VSPE20-20L[5][6]-[7]	
		30	VSPE20-30L[5][6]-[7]	
	ø30	5	VSPE30-5L[5][6]-[7]	T40
		10	VSPE30-10L[5][6]-[7]	
		20	VSPE30-20L[5][6]-[7]	
		30	VSPE30-30L[5][6]-[7]	
	ø40	5	VSPE40-5L[5][6]-[7]	T40
		10	VSPE40-10L[5][6]-[7]	
		20	VSPE40-20L[5][6]-[7]	
		30	VSPE40-30L[5][6]-[7]	



Cylinder thrust force

Supply pressure (MPa)	Cylinder thrust force (N)	Condition
0.5	5	Vacuum level inside cylinder tube of the product should be -85 kPa or more.

<Notes>

·The cylinder thrust force (spec. value) above is calculated under the condition of no leakage between a vacuum pad and a work-piece with supply pressure 0.5 MPa. The cylinder thrust force of this product depends on the vacuum level inside the cylinder tube. Calculate a cylinder thrust force by the formula below, using an actual measured vacuum level, if supply pressure 0.5 MPa cannot be secured, or there is leakage between a vacuum pad and a work-piece, etc.

$$\text{Formula: Cylinder thrust force} = 5 \times \frac{\text{(Actual vacuum level [-kPa])}}{85} \text{ [N]}$$

(Example) Actual measured vacuum level: -60 kPa

$$\text{Cylinder thrust force} = 5 \times \frac{60}{85} \approx 3.5 \text{ [N]}$$


Selectable pad size and material of Pad Surface Treatment for Suction Mark-free

Pad dia. (mm)	[6] Surface treatment code				
	-NF	-SF	-DL	-ER	-FG
	Fiber surface type Nylon fiber Silk fiber	DLC. coating	Reformed surface	Fluoro coating	
ø4	—	—	○	○	○
ø6	—	—	○	○	○
ø8	—	—	○	○	○
ø10	○	○	○	○	○
ø15	○	○	○	○	○
ø20	○	○	○	○	○
ø30	○	○	○	○	○
ø40	○	○	○	○	○
Applicable material	S	S, SE	N, NE	S, SE	


(○ : Available)



Notes
*Please select a rubber material code for [5] in model code and port size and joint type code for [7], referring to the model designation (example) of Vacuum Cylinder on page 731.



CAD data is available at PISCO website.



Packaging specifications
1 pc./bag




Options
Please select a Pad rubber surface treatment code for [6].

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Model code	Connection configuration code
Vacuum Cylinder (Soft bellows pad) VSPE	ø6	5	VSPE6-5LB[5][6]-[7]	T15
		10	VSPE6-10LB[5][6]-[7]	
		20	VSPE6-20LB[5][6]-[7]	
		30	VSPE6-30LB[5][6]-[7]	
	ø8	5	VSPE8-5LB[5][6]-[7]	
		10	VSPE8-10LB[5][6]-[7]	
		20	VSPE8-20LB[5][6]-[7]	
		30	VSPE8-30LB[5][6]-[7]	
	ø10	5	VSPE10-5LB[5][6]-[7]	
		10	VSPE10-10LB[5][6]-[7]	
		20	VSPE10-20LB[5][6]-[7]	
		30	VSPE10-30LB[5][6]-[7]	
	ø15	5	VSPE15-5LB[5][6]-[7]	T40
		10	VSPE15-10LB[5][6]-[7]	
		20	VSPE15-20LB[5][6]-[7]	
		30	VSPE15-30LB[5][6]-[7]	
	ø20	5	VSPE20-5LB[5][6]-[7]	
		10	VSPE20-10LB[5][6]-[7]	
		20	VSPE20-20LB[5][6]-[7]	
		30	VSPE20-30LB[5][6]-[7]	



Notes
*Please select a rubber material code for [5] in model code and port size and joint type code for [7], referring to the model designation (example) of Vacuum Cylinder on page 731.



Packaging specifications
1 pc./bag



Options
Please select a Pad rubber surface treatment code for [6].

Selectable pad size and material of Pad Surface Treatment for Suction Mark-free

Pad dia. (mm)	[6] Surface treatment				
	-NF	-SF	-DL	-ER	-FG
	Fiber surface type Nylon fiber Silk fiber	DLC. coating	Reformed surface	Fluoro coating	
ø6	—	—	○	○	○
ø8	—	—	○	○	○
ø10	○	○	○	○	○
ø15	○	○	○	○	○
ø20	○	○	○	○	○
Applicable material	S	S, SE	N, NE	S, SE	

(○ : Available)

Vacuum cylinder with the connection configuration code "M4" and "M6":

Although the connection configuration codes "M4" and "M6" are not found in the Vacuum Cylinder tables, "M4" and "M6" are selectable. For "M4"/"M6" vacuum cylinders, select one with the matching connection configuration code from the following "Cylinder Holder Only" and from the "Pad & screw set" (on page 374 to 383).

Cylinder Holder Only

Holder type	Model code	Connection configuration code
Vacuum Cylinder (Soft pad) VSPE	VSPE-T15-5-[4]	T15
	VSPE-T15-10-[4]	
	VSPE-T15-20-[4]	
	VSPE-T15-30-[4]	
	VSPE-T40-5-[4]	T40
	VSPE-T40-10-[4]	
	VSPE-T40-20-[4]	
	VSPE-T40-30-[4]	
	VSPE-M4-5-[4]	M4
	VSPE-M4-10-[4]	
	VSPE-M4-20-[4]	
	VSPE-M4-30-[4]	
	VSPE-M6-5-[4]	M6
	VSPE-M6-10-[4]	
	VSPE-M6-20-[4]	
	VSPE-M6-30-[4]	


Applicable vacuum pad list

Holder type	Connection configuration code	Pad type/size (mm)	
		Soft	Bellows
VSPE-T15-[3]-[4]	T15	ø4 to ø15	ø6 to ø15
VSPE-T40-[3]-[4]	T40	ø20 to ø40	ø20

Holder type	Connection configuration code	Pad type/size (mm)									
		Standard	Skidproof	Bellows	Multi-bellows	Metal detectable	Flat, Large Suction Flow	Mark-free	Sponge	Oval	
VSPE-M4-[3]-[4]	M4	ø10, ø15	ø15	ø10	ø10, ø15	ø10	ø10, ø15	ø10	—	—	
VSPE-M6-[3]-[4]	M6	ø20 to ø50	ø20 to ø50	ø20 to ø50	ø20 to ø50	ø20	ø20 to ø30	ø20, ø30	ø10 to ø50	All sizes	




Notes
*1. Please select a code from Port size and joint type (4J or 6J) for [4], referring to the model designation (example) on page 731.
*2. For a vacuum pad to be connected to a cylinder holder only with "M4" or "M6" connection configuration code, select a code from "Pad & screw set".



Packaging specifications
1 pc./bag

1. PISCO's Vacuum pad series consists of the combination of vacuum pads and holders.




2. Vacuum pad and pad holder have a specific connection type depending on the size and shape.

Pad connection type	Insert type (Direct connection)		Mount type (Direct connection)		Screw type (Connection with screw)	
Connection configuration code	H3		T4 T8 T15 T40 (Exclusive to soft type & soft bellows type vacuum pads) PB8 PB15 (Exclusive to Vacuum pad for packaging bag) E10 E20 (Exclusive to Oval type vacuum pad)	M4 M6 M10 M20 G1 G2 G3 G4		

*As shown in above drawings, Vacuum pad and pad holder are connected with a screw or a rim.

3. Any Vacuum pad and pad holder can be connected, as long as their connection configuration codes are same.



If you have purchased a pad and holder set but want to install a different pad or replace the holder with a different one...
→Please check the connection configuration code of your pad or pad holder and select the one that matches the configuration code.

4. Please refer to the below chart for the "Connection Configuration Code". *Configuration codes are also listed on the page of model code list for each product.

Connection configuration code list (Holder)

Common holder

	Fixed type		Mini	Slim	Spring type		No cover	Low dust emission
	Mini	Standard			Standard			
Code	VPMA	VPA	VMC	VPSC	VPC	VPOC	VPLFC	
Type								
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	H3 T8	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPMB	VPB	VPMD	—	VPD	VPOD	VPLFD	
Type				—				
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	—	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPME	VPE	—	—	VPF	*Holders with configuration code: G1 to G4 can be connected to VPE holders.		
Type			—	—		Holder with configuration code: G1, G2, G3 and G4 VPE holder (Male thread: G1, G2, G3, and G4) Vacuum Pad		
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 T15 T40	—	—	H3 T8 M4 M6			

Common holder (Lightweight/Low profile)

	Top port		Side port		Dual side port	
	Code	VPHC	Code	VPHD	Code	VPHDW
Type						
Configuration code	T15 T40 M4 M6	T15 T40 M4 M6 T8	T15 T40 M4 M6			
Code	—	VPHE	VPHEW			
Type	—					
Configuration code	—	T15 T40 M4 M6	T15 T40 M4 M6			

Special holder *Pads of other shapes cannot be installed.

	Top port		Side port	
	Code	VPA	Code	VPB
Type				
Configuration code	E10 E20	E10 E20		
Code	VPA	VPE		
Type				
Configuration code	PB8 PB15	PB8 PB15		

Connection configuration code list (Pad) (○: Available)

Pad type or application	Standard															Pad type or application
	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Pat Large suction flow type	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	For oval application	
Code	R	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	E	
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

Some combinations are possible by using a conversion screw adapter.

H3, T4 and T8 can be converted to M4 or M6. M4 to M6 conversion is also available. For details, please see "Rearrangement parts" of each pad type.

Model Designation (Example)



(1) Vacuum Pad

(2) Pad size (3) Pad type (6) Connection configuration code *Required for Pad & screw set only. (○: Available)

Pad type or application	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Flat (Large suction flow type)	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	Pad type or application
Code	RM	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	Code
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	2x4
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	3.5x7
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x10
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x10
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x10
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x20
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x30
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x30
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x30
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x20
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x30
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

(4) Pad material (○: Available)

Code	N	S	U	F	SE	NE	G	HN	EP	FS	NH	YS2	YS4	MSF3	MSF5	MSS3	MSS5
Rubber material	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	Food Sanit. Act compliant NBR	HNBR	EPDM	Fluoro-silicone	Oil proof NBR	Extra soft silicone	Iron powder type	SUS powder type	Metal detectable silicone		
Pad color	Black	Clear white	Dark blue	Gray	Black	Black	Light gray	Black	Black	Dark orange	Black	Pink	Blue	Reddish brown	Dark green	Brown	Green
Material code marking ¹⁾	None	None	None	None	SE	NE	None	HN	EP	None	None	None	None	SF	SF	SS	SS
Standard	General	Deep	Small	RM	○	○	○	○	○	○	○	○	○	○	○	○	○
Soft	L	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Soft bellows	LB	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Skidproof	K	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Bellows	B	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Multi-bellows	W	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
For packaging bag	PB	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Metal Detectable	BE	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Ribs	BD	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Ultrathin	P	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Flat	F	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Flat large suction flow	FH	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Oval	E	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

● Mark-free type (Pad type code: Q)

Code	K	M	KE
Resin material	PEEK	POM	Conductive PEEK
Pad color	Beige	White	Black

● Sponge type (Pad type code: S)

Code	S	C
Rubber material	Silicone	Chloroprene
Pad color	Dark orange	Black

*1. For vacuum pads in black color (SE: Conductive silicone, NE: Conductive NBR (low resistance), HN: HNBR and EP: EPDM) and Vacuum pad Metal Detectable type, the pad material code is marked on the top or the side of the vacuum pad for material identification. (The marking on black vacuum pads has started since Oct. 2023 gradually.)



(5) Surface treatment (Optional) (○: Available)

Code			No code	-NF	-SF	-DL	-ER	-FG	
Surface treatment			None	Fiber surface		DLC. coating	Reformed surface	Fluoro-coating	
				Nylon fiber	Silk fiber				
			—						
Applicable pad material			—	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F) Conductive silicone (SE)	Nitrile (N) Conductive NBR (NE)	Silicone (S) Conductive silicone (SE) Extra soft silicone (YS2, YS4)	
Pad type	Standard	General	R	—	○	○	○	○	
		Deep	A	—	○	○	○	○	
		Small	RM	—	—	—	○	○	
	Soft		L	—	○	○	○	○	
		Soft bellows	LB	—	○	○	○	○	○
		Skidproof	K	—	—	—	—	—	—
	Bellows		B	—	○	○	○	○	○
		Multi-bellows	W	—	—	—	○	○	○
		For packaging bag	PB	—	—	—	—	—	○
	Metal Detectable	BE, BD	—	—	—	—	—	—	
	Ultrathin		P	—	—	—	○	○	○
		Flat	F	—	—	—	○	○	○
		Flat large suction flow	FH	—	—	—	○	○	○
	Mark-free	Q	—	—	—	—	—	—	
	Sponge	S	—	—	—	—	—	—	
	Oval	E	—	—	—	○	○	○	

*Some surface treatments are not available depending on pad size.

Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free.


(6) Connection configuration code (Required for Pad & screw set only.) Please refer to the Pad size and type list on the 374 page.

Code	No code	-M4	-M6	-M10	-M20	-M5(*)
Connection config. code	—	M4	M6	M10	M20	—
Thread size	Pad rubber only	M4×0.7	M6×1	M10×1.5	M20×2	M5×0.8

*M5 thread is used for mounting on non-PISCO holders. Contact us for the price of screw set.

(7) Mark-free resin attachment material (Bellows type only) (Optional)

Code	No code	-QK	-QM	-QKE
Resin material	—	PEEK	POM	Conductive PEEK (Volume resistance: 10 ¹² to 10 ¹⁵ Ω·cm)
	—			



*1. Selectable for Bellows type pad dia. 10 to 30 mm.

*2. Resin attachment cannot be installed when selecting surface treatment.

*3. Resin attachment cannot be installed when selecting Extra soft silicone for pad material.

(8) -S3 spec. (Required for Pad & screw set only) (Optional)

Code	No code	-S3
Metal material	Standard	No copper-based metallic materials used in flow paths

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code (M4 , M6 etc.)" can be connected. For connectable holders, please see the page of Pad holder only (page 384-).



Bellows series,

Pad rubber alone



P526

Model code	○: Available as standard item										Connection config. code
	④ Pad rubber material										
	N	S	YS2	YS4	U	F	SE	NE	HN	EP	
	Nitrile	Silicone	Extra soft silicone ⁽²⁾ Hardness 20 [*]	Hardness 40 [*]	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM	
VP2B④	○	○	—	—	—	—	—	—	—	—	H3
VP4B④	○	○	—	—	—	—	○	—	—	—	
VP6B④⑤	○	○	—	—	○	○	○	○	○	○	T8
VP8B④⑤	○	○	—	—	○	○	○	○	○	○	
VP10B④⑤	○	○	(*)	(*)	○	○	○	○	○	○	M4③
VP15B④⑤	○	○	(*)	○	○	○	○	○	○	○	
VP20B④⑤	○	○	○	○	○	○	○	○	○	○	M6③
VP25B④⑤	○	○	○	○	○	○	○	○	○	○	
VP30B④⑤	○	○	○	○	○	○	○	○	○	○	
VP40B④⑤	○	○	○	○	○	○	○	○	○	○	
VP50B④⑤	○	○	○	○	○	○	○	○	○	○	
VP60B④⑤	○	○	—	—	○	○	○	○	○	○	
VP80B④⑤	○	○	—	—	○	○	○	○	○	○	M10③
VP100B④⑤	○	○	—	—	○	○	○	○	○	○	



Bellows series,
Pad & screw set

P526

Model code	○: Available as standard item										Connection config. code	
	④ Pad rubber material											⑧
	N	S	YS2	YS4	U	F	SE	NE	HN	EP		-S3
	Nitrile	Silicone	Extra soft silicone ⁽²⁾ Hardness 20*	Hardness 40*	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM		-S3 spec.
VP10B④⑤-M4⑧	○	○	(*)	(*)	○	○	○	○	○	○	○	M4
VP15B④⑤-M4⑧	○	○	(*)	○	○	○	○	○	○	○	○	
VP20B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	M6
VP25B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP30B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP40B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP50B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP60B④⑤-M10	○	○	—	—	○	○	○	○	○	○	(*)	M10
VP80B④⑤-M10⑧	○	○	—	—	○	○	○	○	○	○	○	
VP100B④⑤-M10⑧	○	○	—	—	○	○	○	○	○	○	○	

■ Available pad size and material for surface treatment (Bellows series)

Pad dia. (mm)	⑤ Surface treatment code					Model code	YS2	YS4	⑧	-S3	Connection config. code
	-NF	-SF	-DL	-ER	-FG						
	Fiber surface Nylon	Silk coating	DLC coating	Reformed surface	Fluoro-coating (S, SE) (YS2, YS4)						
φ6	—	—	○	○	—				—	—	—
φ8	—	—	○	○	—						
φ10	—	—	○	○	—						
φ15	○	○	○	○	○						
φ20	○	○	○	○	○						
φ25	○	○	○	○	○						
φ30	○	○	○	○	○						
φ40	○	○	○	○	○						
φ50	○	○	○	○	○						
φ60	○	○	—	○	—						
φ80	○	○	—	—	○						
φ100	—	—	—	—	○						
Material	S, F	S, F, SE	N, NE	S, SE, YS2, YS4		Pad & screw set					
						VP10B④-FG	○	○	—		
						VP15B④-FG	○	—	—	M4③	
						Pad & screw set					
						VP10B④-FG-M4⑧	○	○	○		
						VP15B④-FG-M4⑧	○	—	○	M4	

*4. Fluoro-coating of Extra soft silicone (YS2, YS4)
For Extra soft silicone pads, dia. 10 mm or 15 mm of 20° hardness type (YS2) and dia. 10 mm of 40° hardness type (YS4) can be selected only when Fluoro-coating treatment is selected.

Notes
 *1. For Pad & screw set of Bellows series 60 mm pad dia., the standard spec. is equivalent to "-S3" spec.
 *2. Extra soft silicone is compliant with Food Sanitation Act and FDA.
 *3. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.

CAD data is available at PISCO website.
 Packaging specifications 1 pc./bag
 Options
 ⑤ : Surface treatment
 ⑧ : -S3 ⇒ -S3 spec.

Holders with the same "connection configuration code (M4 , M6 etc.)" can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Bellows series, with Resin attachment

P526

Picture of mark-free resin attachment with pad

By attaching a resin attachment, bellows pad (pad dia.: 10 to 30 mm) can be used as Mark-free pad.

Model code	○: Available as standard item								Connection config. code	
	④ Pad rubber material									
	N	S	U	F	SE	NE	HN	EP		
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM		
VP10B④-QK	○	○	○	○	○	○	○	○	M4③	
VP10B④-QM	○	○	○	○	○	○	○	○		
VP10B④-QKE	○	○	○	○	○	○	○	○		
VP15B④-QK	○	○	○	○	○	○	○	○		
VP15B④-QM	○	○	○	○	○	○	○	○		
VP15B④-QKE	○	○	○	○	○	○	○	○		
VP20B④-QK	○	○	○	○	○	○	○	○	M6③	
VP20B④-QM	○	○	○	○	○	○	○	○		
VP20B④-QKE	○	○	○	○	○	○	○	○		
VP25B④-QK	○	○	○	○	○	○	○	○		
VP25B④-QM	○	○	○	○	○	○	○	○		
VP25B④-QKE	○	○	○	○	○	○	○	○		
VP30B④-QK	○	○	○	○	○	○	○	○	M10③	
VP30B④-QM	○	○	○	○	○	○	○	○		
VP30B④-QKE	○	○	○	○	○	○	○	○		


● How to attach

- (1) Fix a bellows pad and a pad holder with a pad screw.
- (2) Attach a resin attachment to the bellows pad.

①
Bellows
pad

②
Pad screw
Resin
attachment

Picture of mark-free resin attachment with pad
 By attaching a resin attachment, bellows pad (pad dia.: 10 to 30 mm) can be used as Mark-free pad.





Bellows series,
Pad & screw set + Resin attachment

P526



Mark-free resin attachment for
Bellows series

P526

Model code	○: Available as standard item									Connection config. code	
	④ Pad rubber material										
	N	S	U	F	SE	NE	HN	EP	-S3		
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM	-S3 spec.		
VP10B④-M4-QK⑧	○	○	○	○	○	○	○	○	○	M4	
VP10B④-M4-QM⑧	○	○	○	○	○	○	○	○	○		
VP10B④-M4-QKE⑧	○	○	○	○	○	○	○	○	○		
VP15B④-M4-QK⑧	○	○	○	○	○	○	○	○	○		
VP15B④-M4-QM⑧	○	○	○	○	○	○	○	○	○		
VP15B④-M4-QKE⑧	○	○	○	○	○	○	○	○	○		
VP20B④-M6-QK⑧	○	○	○	○	○	○	○	○	○	M6	
VP20B④-M6-QM⑧	○	○	○	○	○	○	○	○	○		
VP20B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○		
VP25B④-M6-QK⑧	○	○	○	○	○	○	○	○	○		
VP25B④-M6-QM⑧	○	○	○	○	○	○	○	○	○		
VP25B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○		
VP30B④-M6-QK⑧	○	○	○	○	○	○	○	○	○	M10	
VP30B④-M6-QM⑧	○	○	○	○	○	○	○	○	○		
VP30B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○		

Model code	○: Available as standard item		
	④ Resin attachment material		
	K	M	KE
	PEEK	POM	Conductive PEEK
VP10BQ④-AT	○	○	○
VP15BQ④-AT	○	○	○
VP20BQ④-AT	○	○	○
VP25BQ④-AT	○	○	○
VP30BQ④-AT	○	○	○

Mark-free resin attachment for Bellows series

Connection code	Model code	○: Available as standard item		
		④ Resin attachment material		
		K	M	KE
		PEEK	POM	Conductive PEEK
4	VP10BQ④-AT	○	○	○
	VP15BQ④-AT	○	○	○
	VP20BQ④-AT	○	○	○
	VP25BQ④-AT	○	○	○
	VP30BQ④-AT	○	○	○

Notes
 *1. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
 *2. Resin attachment must be used with a vacuum pad for work conveyance.

CAD data is available at PISCO website.
 Packaging specifications 1 pc./bag
 Options
 ⑧ : -S3 ⇒ -S3 spec.

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code" (M4, M6, etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Flat series, Pad rubber alone										Flat series, Pad & screw set									
○: Available as standard item										○: Available as standard item									
Model code	④ Pad rubber material						Connection config. code	Model code	④ Pad rubber material						Connection config. code				
	N	S	U	F	SE	NE			N	S	U	F	SE	NE		-S3			
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.			
VP10F④⑤	○	○	○	○	○	○	M4⑧⑨	VP10F④⑤-M4⑧	○	○	○	○	○	○	○	M4			
VP15F④⑤	○	○	○	○	○	○		VP15F④⑤-M4⑧	○	○	○	○	○	○	○				
VP20F④⑤	○	○	○	○	○	○	M6⑧⑨	VP20F④⑤-M6⑧	○	○	○	○	○	○	○	M6			
VP25F④⑤	○	○	○	○	○	○		VP25F④⑤-M6⑧	○	○	○	○	○	○	○				
VP30F④⑤	○	○	○	○	○	○		VP30F④⑤-M6⑧	○	○	○	○	○	○	○				

 Flat large suction flow series, Pad rubber alone							 Flat large suction flow series, Pad & screw set							
○: Available as standard item							○: Available as standard item							
Model code	④ Pad rubber material					Connection config. code	Model code	④ Pad rubber material					Connection config. code	
	N	S	F	SE	NE			N	S	F	SE	NE		⑤
	Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.
VP10FH④⑤	○	○	○	○	○	M4⑧	VP10FH④⑤-M4⑧	○	○	○	○	○	○	M4
VP15FH④⑤	○	○	○	○	○		VP15FH④⑤-M4⑧	○	○	○	○	○	○	
VP20FH④⑤	○	○	○	○	○	M6⑧	VP20FH④⑤-M6⑧	○	○	○	○	○	○	M6
VP25FH④⑤	○	○	○	○	○		VP25FH④⑤-M6⑧	○	○	○	○	○	○	
VP30FH④⑤	○	○	○	○	○		VP30FH④⑤-M6⑧	○	○	○	○	○	○	

									
Mark-free series, Resin pad alone				Mark-free series, with Flexible Swing Joint					
Model code	○: Available as standard item			Connection config. code	Model code	○: Available as standard item			Connection config. code
	④ Pad rubber material					④ Pad rubber material			
	K	M	KE			K	M	KE	
	PEEK	POM	Conductive PEEK			PEEK	POM	Conductive PEEK	-S3 spec.
VP10Q④	○	○	○	M4①	VP10Q④-M4⑧	○	○	○	M4
VP20Q④	○	○	○	M6①	VP20Q④-M6⑧	○	○	○	M6
VP30Q④	○	○	○		VP30Q④-M6⑧	○	○	○	



Sponge series,
Pad rubber alone


P656



Sponge series,
Pad & screw set


P656

Model code	○: Available as standard item		Connection config. code	Model code	○: Available as standard item			Connection config. code
	④ Pad rubber material				④ Pad rubber material			
	C	S			C	S	-S3	
	Chloroprene	Silicone			Chloroprene	Silicone	-S3 spec.	
VP10S④	○	○	M8④①	VP10S④-M6⑧	○	○	○	M6
VP15S④	○	○		VP15S④-M6⑧	○	○	○	
VP20S④	○	○		VP20S④-M6⑧	○	○	○	
VP25S④	○	○		VP25S④-M6⑧	○	○	○	
VP30S④	○	○		VP30S④-M6⑧	○	○	○	
VP35S④	○	○	M10④①	VP35S④-M6⑧	○	○	○	M10
VP50S④	○	○		VP50S④-M6⑧	○	○	○	
VP70S④	○	○		VP70S④-M10	○	○	(*)	
VP100S④	○	○		VP100S④-M10	○	○	(*)	

- Notes**
- *1. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- *2. A Flexible Swing Joint is required to mount on the holder. If you do not have a Flexible Swing Joint, please select from the Mark-free series, with Flexible Swing Joint set.
- *3. For Pad & screw set of Sponge series 70 mm and 100 mm pad dia., the standard spec. is equivalent to "-S3" spec.

CAD data is available at PISCO website.

Packaging specifications 1 pc./bag

Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Holders with the same "connection configuration code" (E10, E20, etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Oval series, Pad rubber alone												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP				
VP2×4E④⑤	○	○	○	○	○	○	○	○				
VP3.5×7E④⑤	○	○	○	○	○	○	○	○				
VP4×10E④⑤	○	○	○	○	○	○	○	○				
VP4×20E④⑤	○	○	○	○	○	○	○	○				
VP4×30E④⑤	○	○	○	○	○	○	○	○				
VP5×10E④⑤	○	○	○	○	○	○	○	○				
VP5×20E④⑤	○	○	○	○	○	○	○	○				
VP5×30E④⑤	○	○	○	○	○	○	○	○				
VP6×10E④⑤	○	○	○	○	○	○	○	○				
VP6×20E④⑤	○	○	○	○	○	○	○	○				
VP6×30E④⑤	○	○	○	○	○	○	○	○				
VP8×20E④⑤	○	○	○	○	○	○	○	○				
VP8×30E④⑤	○	○	○	○	○	○	○	○				

Oval series, Pad & screw set												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP	-S3			
VP2×4E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP3.5×7E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			


- Notes**
- *A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- CAD data is available at PISCO website.
- Packaging specifications 1 pc./bag
- Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Available pad size and material for surface treatment (Oval series)


Pad dia. (mm)	⑤ Surface treatment code		
	-DL	-ER	-FG
2×4	○	○	○
3.5×7	○	○	○
4×10	○	○	○
4×20	○	○	○
4×30	○	○	○
5×10	○	○	○
5×20	○	○	○
5×30	○	○	○
6×10	○	○	○
6×20	○	○	○
6×30	○	○	○
8×20	○	○	○
8×30	○	○	○
Material	S, F, SE	N, NE	S, SE

Vacuum Pad Configuration


Pad dia. : $\phi 0.7, \phi 1, \phi 1.5, \phi 2, \phi 3, \phi 4$ mm





Pad dia. : $\phi 1, \phi 2, \phi 3, \phi 4$ mm



Pad dia. : $\phi 6, \phi 8, \phi 10, \phi 15, \phi 20$ mm






Pad dia. : $\phi 4, \phi 6, \phi 8, \phi 10, \phi 15$ mm





Vacuum Pad Configuration



Pad dia. : $\varnothing 10$, $\varnothing 15$, $\varnothing 20$, $\varnothing 25$, $\varnothing 30$, $\varnothing 35$, $\varnothing 40$, $\varnothing 50$ mm



Pad dia. : $\varnothing 60$, $\varnothing 70$, $\varnothing 80$, $\varnothing 100$ mm



Pad dia. : $\varnothing 150$, $\varnothing 200$ mm



Vacuum Pad Configuration

Pad dia. : ø4, ø6, ø8, ø10, ø15 mm (Exclusive to Soft and Soft Bellows type)

VPHC

VPHD

VPHDW

VPHE

VPHEW

Push-in fitting

Push-in fitting

Push-in fitting

Push-in fitting

Push-in fitting

Barb fitting

Barb fitting

Barb fitting

Barb fitting

Barb fitting

Metric female thread

Metric female thread

Metric female thread

Metric female thread

Metric female thread

Metric male thread

Parallel pipe male thread

Taper pipe male thread

NPT male thread

Metric female thread

Soft pad

Soft Bellows pad

Soft pad dia. : ø4, ø6, ø8, ø10, ø15 mm

Soft-bellows pad dia. : ø6, ø8, ø10, ø15 mm

Connection config. code

T15

Connection type

Mount type

(Direct connection)

Pad dia. : ø20, ø30, ø40 mm (Exclusive to Soft and Soft Bellows type)

VPHC

VPHD

VPHDW

VPHE

VPHEW

Push-in fitting

Push-in fitting

Push-in fitting

Push-in fitting

Push-in fitting

Barb fitting

Barb fitting

Barb fitting

Barb fitting

Barb fitting

Metric female thread

Metric female thread

Metric female thread

Metric female thread

Metric female thread

Metric male thread

Parallel pipe male thread

Taper pipe male thread

NPT male thread

Metric female thread

Soft pad

Soft Bellows pad

Soft pad dia. : ø20, ø30, ø40 mm

Soft-bellows pad dia. : ø20 mm

Connection config. code

T40

Connection type

Mount type

(Direct connection)

Pad dia. : ø20, ø25 mm (Exclusive to Vacuum pad for packaging bag)

VPA

VPE

Push-in fitting

Metric male thread

Parallel pipe male thread

Packaging bag pad 3 convolutions

Packaging bag pad 5 convolutions

Over-suction preventing adapter Spherical type

Over-suction preventing adapter Plane type

With stainless steel mesh

Connection config. code

PB8

Connection type

Mount type

(Direct connection)

Pad dia. : ø30, ø40, ø50 mm (Exclusive to Vacuum pad for packaging bag)

VPA

VPE

Push-in fitting

Metric male thread

Parallel pipe male thread

Packaging bag pad 3 convolutions

Packaging bag pad 5 convolutions

Over-suction preventing adapter Spherical type

Over-suction preventing adapter Plane type

With stainless steel mesh

Connection config. code

PB15

Connection type

Mount type

(Direct connection)

Pad size : 2×4, 3.5×7, 4 to 6×10 mm (Exclusive to Oval type)

VPAE

VPBE

Push-in fitting

Push-in fitting

Barb fitting

Barb fitting

Metric female thread

Metric female thread

Oval pad

Connection config. code

E10

Connection type

Mount type

(Direct connection)

Pad size : 4 to 8×20 mm, 4 to 8×30 mm (Exclusive to Oval type)

VPAE

VPBE

Push-in fitting

Push-in fitting

Barb fitting

Barb fitting

Metric female thread

Metric female thread

Oval pad

Connection config. code

E20

Connection type

Mount type

(Direct connection)