

Vacuum Pad Multi-bellows Type

Vacuum pad for bag-like article conveyance. (Bellows convolution: 4)

Safety instructions for this product

Safety instructions, Common safety instructions for each product category and Detailed safety instructions for each product are in the end of this catalog and our website.

Model Designation (Example)

VP	C	10	-6	W	N	-ER	-6J	-DC	-ECV	-FH	-F15	(13)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)
		Optional		Optional		Optional		Optional		Optional		Optional

(1) Vacuum Pad

(2) Holder type

Holder type	Fixed type		Spring type				
	Mini	Standard	Mini	Slim	Standard	No cover	Low dust emission
Code							
Top port	MA	A	MC	SC	C	OC	LFC
Side port	MB	B	MD	-	D	OD	LFD
Direct mount	ME ⁽¹⁾	E	-	-	F	-	-
Connection config. code	T8	T8	T8	T8	T8	T8	T8
	M4	M6	M4	M6	M4	M6	M4

*1. ME holder is available only for configuration code: T8.

Holder type	Lightweight	Low profile
	Spring type	Direct mount
Code		
Top port	HC ⁽²⁾	-
Side port	HD	HE
Dual side port	HDW	HEW
Connection config. code	T8	T8
	M4	M6

*2. Configuration code: T8 is not available for HC holder.

(3) Pad dia.

Code	6	8	10	20	30	40	50
Pad dia. (mm)	ø6	ø8	ø10	ø20	ø30	ø40	ø50
Connection config. code	T8	M4	M6				

(4) Stroke (No code entry for Holder type: MA, A, MB, B, ME, E, F, HE and HEW)

Code	-2	-3	-4	-5	-6	-10	-15	-20	-25	-30	-40	-50
Stroke (mm)	2	3	4	5	6	10	15	20	25	30	40	50
Spring type holder code												
VPMC	●		●									
VPSC		●										
VPC		●										
VPOC												
VPLFC	●			●		●	●	●	●	●	●	●
VPM	●		●			●	●	●	●	●	●	●
VPD		●			●	●	●	●	●	●	●	●
VPOD						●	●	●	●	●	●	●
VPLFD				●	●	●	●	●	●	●	●	●
VPHC				●	●	●	●	●	●	●	●	●
VPHD				●	●	●	●	●	●	●	●	●
VPHW				●	●	●	●	●	●	●	●	●

(5) Pad type W : Multi-bellows

(6) Pad material

Code	N	S	YS2	YS4	U	F	NE	G	HN	EP
Rubber material	Nitrile	Silicone	Extra soft silicone Hardness 20° Hardness 40°		Urethane	Fluoro	Conductive NBR (Low resistance)	Food Sanit. Act compliant NBR	HNBR	EPDM

*1. Nitrile rubber (N), Conductive NBR (Low resistance, Volume resistance: 200Ω-cm or less) (NE), and Food Sanit. Act compliant NBR (G) are not suitable for use with ozone environment.

*2. Extra soft silicone is not available for pad dia. 10 mm or smaller.

*3. Urethane is not available for pad dia. 6 mm and 8 mm.

*4. Extra soft silicone is compliant with Food Sanitation Act and FDA.

(7) Pad surface treatment for suction mark-free

Code	No code	-DL	-ER	-FG
Surface treatment	None	DLC. coating	Reformed surface	Fluoro-coating
Applicable pad material	—	Silicone(S), Fluoro(F)	Nitrile(N), Conductive NBR (Low resistance)(NE)	Silicone(S), Extra soft silicone: Hardness 20°(YS2), Extra soft silicone: Hardness 40°(YS4)
Applicable pad dia.	—	ø10, ø20mm	ø6 to ø50mm	ø6 to ø50mm

*Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free.

Vacuum Pad Multi-bellows Type

Vacuum pad for bag-like article conveyance. (Bellows convolution: 4)

Safety instructions for this product

Safety instructions, Common safety instructions for each product category and Detailed safety instructions for each product are in the end of this catalog and our website.

Model Designation (Example)

VP	C	10	-6	W	N	-ER	-6J	-DC	-ECV	-FH	-F15	(13)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)
		Optional		Optional		Optional		Optional		Optional		Optional

(1) Vacuum Pad

(2) Holder type

Holder type	Fixed type		Spring type				
	Mini	Standard	Mini	Slim	Standard	No cover	Low dust emission
Code							
Top port	MA	A	MC	SC	C	OC	LFC
Side port	MB	B	MD	-	D	OD	LFD
Direct mount	ME ⁽¹⁾	E	-	-	F	-	-
Connection config. code	T8	T8	T8	T8	T8	T8	T8
	M4	M6	M4	M6	M4	M6	M4

*1. ME holder is available only for configuration code: T8.

Holder type	Lightweight	Low profile
	Spring type	Direct mount
Code		
Top port	HC ⁽²⁾	-
Side port	HD	HE
Dual side port	HDW	HEW
Connection config. code	T8	T8
	M4	M6

*2. Configuration code: T8 is not available for HC holder.

(3) Pad dia.

Code	6	8	10	20	30	40	50
Pad dia. (mm)	ø6	ø8	ø10	ø20	ø30	ø40	ø50
Connection config. code	T8	M4	M6				

(4) Stroke (No code entry for Holder type: MA, A, MB, B, ME, E, F, HE and HEW)

Code	-2	-3	-4	-5	-6	-10	-15	-20	-25	-30	-40	-50
Stroke (mm)	2	3	4	5	6	10	15	20	25	30	40	50
Spring type holder code												
VPMC	●		●									
VPSC		●										
VPC		●										
VPOC												
VPLFC	●			●		●	●	●	●	●	●	●
VPM	●		●			●	●	●	●	●	●	●
VPD		●			●	●	●	●	●	●	●	●
VPOD						●	●	●	●	●	●	●
VPLFD				●	●	●	●	●	●	●	●	●
VPHC				●	●	●	●	●	●	●	●	●
VPHD				●	●	●	●	●	●	●	●	●
VPHW				●	●	●	●	●	●	●	●	●

(5) Pad type W : Multi-bellows

(6) Pad material

Code	N	S	YS2	YS4	U	F	NE	G	HN	EP
Rubber material	Nitrile	Silicone	Extra soft silicone Hardness 20° Hardness 40°		Urethane	Fluoro	Conductive NBR (Low resistance)	Food Sanit. Act compliant NBR	HNBR	EPDM

*1. Nitrile rubber (N), Conductive NBR (Low resistance, Volume resistance: 200Ω-cm or less) (NE), and Food Sanit. Act compliant NBR (G) are not suitable for use with ozone environment.

*2. Extra soft silicone is not available for pad dia. 10 mm or smaller.

*3. Urethane is not available for pad dia. 6 mm and 8 mm.

*4. Extra soft silicone is compliant with Food Sanitation Act and FDA.

(7) Pad surface treatment for suction mark-free

Code	No code	-DL	-ER	-FG
Surface treatment	None	DLC. coating	Reformed surface	Fluoro-coating
Applicable pad material	—	Silicone(S), Fluoro(F)	Nitrile(N), Conductive NBR (Low resistance)(NE)	Silicone(S), Extra soft silicone: Hardness 20°(YS2), Extra soft silicone: Hardness 40°(YS4)
Applicable pad dia.	—	ø10, ø20mm	ø6 to ø50mm	ø6 to ø50mm

*Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free.

Push-in fitting

Barb fitting

Female thread

Direct
mount

[illegible]

Optional



Dust Catcher

***-SF1/4" is not selectable when 2 mm stroke is selected

1

A diagram of a Fall Prevention Valve assembly. It consists of a vertical pipe with several fittings. A label "Fall Prevention Valve" points to a specific component in the middle of the assembly.

■



The image shows two types of joints used in drilling. On the left is a 'Ball Swivel Joint', which consists of a ball joint and a swivel joint. On the right is a 'Flexible Swing Joint', which is a more complex joint designed for flexibility. Both joints are shown in a side-by-side comparison.

1

Diagram illustrating a pad direct mounting filter assembly. The assembly consists of a cylindrical filter housing with a central threaded rod and nut. A label points to the filter housing with the text "Pad Direct Mounting Filter".

*1. -S3 spec. is not available for the following fittings and holders

2. For each size point in $\mathbf{M}_{\text{size}}$, we calculate the order to write each $\mathbf{M}_{\text{size}}$ as spec.

◀ Dust Catcher

562


Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	13 -S3 spec	Connection config code	Pad dia. (mm)	Tube O.D. (inch)	Model code	13 -S3 spec	Connection config code
Fixed type, Top port, Push-in fitting, Mini VPM 	ø6	ø3	VPA6W[6]7-3J ²	—	T8	ø10	ø5/32	VPA10W[6]7-1/4J ¹³	○	M4
	ø8	ø3	VPA8W[6]7-3J ²	—		ø20	ø5/32	VPA20W[6]7-1/4J ¹³	○	
	ø10	ø3	VPA10W[6]7-3J ²	—	M4	ø30	ø5/32	VPA30W[6]7-1/4J ¹³	○	M6
		ø4	VPA10W[6]7-4J ¹³	○		ø40	ø5/32	VPA40W[6]7-1/4J ¹³	○	
	ø20	ø4	VPA20W[6]7-4J ¹³	○	M6	ø50	ø5/32	VPA50W[6]7-1/4J ¹³	○	
	ø30	ø4	VPA30W[6]7-4J ¹³	○						
ø40	ø4	VPA40W[6]7-4J ¹³	○							
ø50	ø4	VPA50W[6]7-4J ¹³	○							
Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	13 -S3 spec	Connection config code	Pad dia. (mm)	Tube O.D. (inch)	Model code	13 -S3 spec	Connection config code
Fixed type, Top port, Push-in fitting, Standard VPA 	ø6	ø4	VPA6W[6]7-4J ¹³	○	T8	ø6	ø5/32	VPA6W[6]7-1/4J ¹³	○	T8
		ø6	VPA6W[6]7-6J ¹³	—			ø1/4	VPA6W[6]7-1/4 ²	—	
	ø8	ø4	VPA8W[6]7-4J ¹³	○		M4	ø8	ø5/32	VPA8W[6]7-1/4J ¹³	
		ø6	VPA8W[6]7-6J ¹³	○	ø1/4			VPA8W[6]7-1/4 ²	—	
	ø10	ø6	VPA10W[6]7-6J ¹³	○	M6	ø10	ø1/4	VPA10W[6]7-1/4 ²	—	M6
		ø3	VPA20W[6]7-3J	—			ø20	ø5/32	VPA20W[6]7-1/4J ¹³	
	ø20	ø4	VPA20W[6]7-4J ¹³	○		ø30		ø1/4	VPA20W[6]7-1/4	
		ø6	VPA20W[6]7-6J ¹³	○	ø40		ø1/8	VPA30W[6]7-1/4	—	
	ø30	ø3	VPA30W[6]7-3J	—		ø50	ø5/32	VPA30W[6]7-1/4J ¹³	○	
		ø4	VPA30W[6]7-4J ¹³	○	ø1/4		VPA30W[6]7-1/4	—		
	ø40	ø6	VPA30W[6]7-6J ¹³	○		ø1/8	VPA40W[6]7-1/4	—		
		ø3	VPA40W[6]7-3J	—	ø5/32		VPA40W[6]7-1/4J ¹³	○		
	ø50	ø4	VPA40W[6]7-4J ¹³	○		ø1/4	VPA40W[6]7-1/4	—		
		ø6	VPA40W[6]7-6J ¹³	○	ø1/8		VPA50W[6]7-1/4	—		
ø30	ø3	VPA50W[6]7-3J	—	ø5/32		VPA50W[6]7-1/4J ¹³	○			
	ø4	VPA50W[6]7-4J ¹³	○		ø1/4	VPA50W[6]7-1/4	—			
ø6	VPA50W[6]7-6J ¹³	○								
Holder type	Pad dia. (mm)	Male thread size	Model code	13 -S3 spec	Connection config code					
Fixed type, Top port, Female thread, Standard VPA 	ø20	M6×1	VPA20W[6]7-M6 ¹³	○	M6					
	ø30	M6×1	VPA30W[6]7-M6 ¹³	○						
	ø40	M6×1	VPA40W[6]7-M6 ¹³	○						
	ø50	M6×1	VPA50W[6]7-M6 ¹³	○						

Optional items ⇒ P.584	Surface treatment	Fall Prevention Valve	Swivel Joint	Filter
---------------------------	---	---	--	--



Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	T8 : -S3 -S3 spec	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	T8 : -S3 -S3 spec	Connection config. code		
Fixed type, Side port, Push-in fitting, Mini VPMB 	ø6	e3	VPMB6W[6]T-3J ²	—	T8	ø6	e1/8	VPMB6W[6]T-4J ²	○	T8		
		e4	VPMB6W[6]T-4J ²	○			e5/32	VPMB6W[6]T-4mJ ²	○			
	ø8	e3	VPMB8W[6]T-3J ²	—		M4	ø8	e1/8	VPMB8W[6]T-4J ²		○	M4
		e4	VPMB8W[6]T-4J ²	○				e5/32	VPMB8W[6]T-4mJ ²		○	
	ø10	e3	VPMB10W[6]T-3J ²	—	M4		ø10	e1/8	VPMB10W[6]T-4J ²	—	M4	
		e4	VPMB10W[6]T-4J ²	○				e5/32	VPMB10W[6]T-4mJ ²	○		
		e6	VPMB10W[6]T-6J ²	○		e1/4		VPMB10W[6]T-4J ²	—			
		e3	VPMB20W[6]T-3J ²	—		M6		ø20	e1/8	VPMB20W[6]T-4J ²		—
	ø20	e4	VPMB20W[6]T-4J ²	○	e5/32		VPMB20W[6]T-4mJ ²		○			
		e6	VPMB20W[6]T-6J ²	○	e1/4		VPMB20W[6]T-4J ²		—			
	ø30	e3	VPMB30W[6]T-3J ²	—	M6		ø30		e1/8	VPMB30W[6]T-4J ²	—	M6
		e4	VPMB30W[6]T-4J ²	○		e5/32		VPMB30W[6]T-4mJ ²	○			
		e6	VPMB30W[6]T-6J ²	○		e1/4		VPMB30W[6]T-4J ²	—			
		e3	VPMB40W[6]T-3J ²	—		M6		ø40	e1/8	VPMB40W[6]T-4J ²	—	
	ø40	e4	VPMB40W[6]T-4J ²	○	e5/32		VPMB40W[6]T-4mJ ²		○			
		e6	VPMB40W[6]T-6J ²	○	e1/4		VPMB40W[6]T-4J ²		—			
	ø50	e3	VPMB50W[6]T-3J ²	—			ø50		e1/8	VPMB50W[6]T-4J ²	—	
		e4	VPMB50W[6]T-4J ²	○		e5/32		VPMB50W[6]T-4mJ ²	○			
		e6	VPMB50W[6]T-6J ²	○		e1/4		VPMB50W[6]T-4J ²	—			
Holder type	Pad dia. (mm)	Male thread size	Model code	T8 : -S3 -S3 spec	Connection config. code							
Fixed type, Side port, Female thread, Mini VPMB 	ø6	M3×0.5	VPMB6W[6]T-M3 ³	○	T8							
	ø8	M3×0.5	VPMB8W[6]T-M3 ³	○								
	ø10	M5×0.8	VPMB10W[6]T-M5 ³	○								
	ø20	M5×0.8	VPMB20W[6]T-M5 ³	○		M4						
	ø30	M5×0.8	VPMB30W[6]T-M5 ³	○								
	ø40	M5×0.8	VPMB40W[6]T-M5 ³	○	M6							
	ø50	M5×0.8	VPMB50W[6]T-M5 ³	○								

Optional items ⇒ P.584	Surface treatment	Fall Prevention Valve	Swivel Joint	Filter
---------------------------	--	---	--	--



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	13 : -S3 -S3 spec	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	13 : -S3 -S3 spec	Connection config. code
Spring type, Top port, Push-in fitting, Standard VPC 	ø20	6	ø3	VPC20-6W617-3J9	—	M6	ø20	6	ø1/8	VPC20-6W617-4J9	—	M6
			ø4	VPC20-6W617-4J9	○				ø5/32	VPC20-6W617-4J9	○	
			ø6	VPC20-6W617-6J9	○				ø1/4	VPC20-6W617-4J9	—	
		10	ø3	VPC20-10W617-3J9	—			10	ø1/8	VPC20-10W617-4J9	—	
			ø4	VPC20-10W617-4J9	—				ø5/32	VPC20-10W617-4J9	—	
			ø6	VPC20-10W617-6J9	—				ø1/4	VPC20-10W617-4J9	—	
		15	ø3	VPC20-15W617-3J9	—			15	ø1/8	VPC20-15W617-4J9	—	
			ø4	VPC20-15W617-4J9	—				ø5/32	VPC20-15W617-4J9	—	
			ø6	VPC20-15W617-6J9	—				ø1/4	VPC20-15W617-4J9	—	
		20	ø3	VPC20-20W617-3J9	—			20	ø1/8	VPC20-20W617-4J9	—	
			ø4	VPC20-20W617-4J9	—				ø5/32	VPC20-20W617-4J9	—	
			ø6	VPC20-20W617-6J9	—				ø1/4	VPC20-20W617-4J9	—	
	ø30	6	ø3	VPC30-6W617-3J9	—			ø30	6	ø1/8	VPC30-6W617-4J9	—
			ø4	VPC30-6W617-4J9	○				ø5/32	VPC30-6W617-4J9	○	
			ø6	VPC30-6W617-6J9	○				ø1/4	VPC30-6W617-4J9	—	
		10	ø3	VPC30-10W617-3J9	—				10	ø1/8	VPC30-10W617-4J9	—
			ø4	VPC30-10W617-4J9	—					ø5/32	VPC30-10W617-4J9	—
			ø6	VPC30-10W617-6J9	—					ø1/4	VPC30-10W617-4J9	—
		15	ø3	VPC30-15W617-3J9	—			15	ø1/8	VPC30-15W617-4J9	—	
			ø4	VPC30-15W617-4J9	—				ø5/32	VPC30-15W617-4J9	—	
			ø6	VPC30-15W617-6J9	—				ø1/4	VPC30-15W617-4J9	—	
		20	ø3	VPC30-20W617-3J9	—			20	ø1/8	VPC30-20W617-4J9	—	
			ø4	VPC30-20W617-4J9	—				ø5/32	VPC30-20W617-4J9	—	
			ø6	VPC30-20W617-6J9	—				ø1/4	VPC30-20W617-4J9	—	
	ø40	6	ø3	VPC40-6W617-3J9	—			ø40	6	ø1/8	VPC40-6W617-4J9	—
			ø4	VPC40-6W617-4J9	○				ø5/32	VPC40-6W617-4J9	○	
			ø6	VPC40-6W617-6J9	○				ø1/4	VPC40-6W617-4J9	—	
		10	ø3	VPC40-10W617-3J9	—				10	ø1/8	VPC40-10W617-4J9	—
			ø4	VPC40-10W617-4J9	—					ø5/32	VPC40-10W617-4J9	—
			ø6	VPC40-10W617-6J9	—					ø1/4	VPC40-10W617-4J9	—
		15	ø3	VPC40-15W617-3J9	—			15	ø1/8	VPC40-15W617-4J9	—	
			ø4	VPC40-15W617-4J9	—				ø5/32	VPC40-15W617-4J9	—	
			ø6	VPC40-15W617-6J9	—				ø1/4	VPC40-15W617-4J9	—	
		20	ø3	VPC40-20W617-3J9	—			20	ø1/8	VPC40-20W617-4J9	—	
			ø4	VPC40-20W617-4J9	—				ø5/32	VPC40-20W617-4J9	—	
			ø6	VPC40-20W617-6J9	—				ø1/4	VPC40-20W617-4J9	—	
	ø50	6	ø3	VPC50-6W617-3J9	—			ø50	6	ø1/8	VPC50-6W617-4J9	—
			ø4	VPC50-6W617-4J9	○				ø5/32	VPC50-6W617-4J9	○	
			ø6	VPC50-6W617-6J9	○				ø1/4	VPC50-6W617-4J9	—	
		10	ø3	VPC50-10W617-3J9	—				10	ø1/8	VPC50-10W617-4J9	—
			ø4	VPC50-10W617-4J9	—					ø5/32	VPC50-10W617-4J9	—
			ø6	VPC50-10W617-6J9	—					ø1/4	VPC50-10W617-4J9	—
		15	ø3	VPC50-15W617-3J9	—			15	ø1/8	VPC50-15W617-4J9	—	
			ø4	VPC50-15W617-4J9	—				ø5/32	VPC50-15W617-4J9	—	
			ø6	VPC50-15W617-6J9	—				ø1/4	VPC50-15W617-4J9	—	
		20	ø3	VPC50-20W617-3J9	—			20	ø1/8	VPC50-20W617-4J9	—	
			ø4	VPC50-20W617-4J9	—				ø5/32	VPC50-20W617-4J9	—	
			ø6	VPC50-20W617-6J9	—				ø1/4	VPC50-20W617-4J9	—	



Notes

- *1. Holders are also available in Push-in fitting type (limited to pad dia. 8 mm or smaller for VPC holders) for tube O.D. of 1.8 mm and 2 mm, and barb fitting type. Contact us for the details.
- *2. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
- *3. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

CAD data is available
at PISCO website.Packaging specifications
1 pc. /bag

Options

17 : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)

9 : -DC ⇒ Holder with dust catcher

13 : -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.

*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."



Vacuum Pad Multi-bellows Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	13 : -S3 -S3 spec	Connection config. code
Spring type, Top port, Female thread, Standard VPC 	ø6	3	M5×0.8	VPC6-3W617-M5913	○	TB
		10		VPC6-10W617-M591	—	
		15		VPC6-15W617-M591	—	
		20	M5×0.8	VPC6-20W617-M591	—	
		3		VPC8-3W617-M5913	○	
		10		VPC8-10W617-M591	—	
	ø8	3	M5×0.8	VPC8-3W617-M5913	○	TB
		10		VPC8-10W617-M591	—	
		15		VPC8-15W617-M591	—	
		20	M6×1	VPC8-20W617-M591	—	
		6		VPC10-6W617-M6913	○	
		10		VPC10-10W617-M691	—	
	ø10	3	M6×1	VPC10-3W617-M6913	○	M4
		10		VPC10-10W617-M691	—	
		15		VPC10-15W617-M691	—	
		20	M6×1	VPC10-20W617-M691	—	
		6		VPC20-6W617-M6913	○	
		10		VPC20-10W617-M691	—	
	ø20	3	M6×1	VPC20-3W617-M6913	○	M6
		10		VPC20-10W617-M691	—	
		15		VPC20-15W617-M691	—	
		20	M6×1	VPC20-20W617-M691	—	
		6		VPC30-6W617-M6913	○	
		10		VPC30-10W617-M691	—	
	ø30	3	M6×1	VPC30-3W617-M6913	○	M6
		10		VPC30-10W617-M691	—	
		15		VPC30-15W617-M691	—	
		20	M6×1	VPC30-20W617-M691	—	
		6		VPC40-6W617-M6913	○	
		10		VPC40-10W617-M691	—	
	ø40	3	M6×1	VPC40-3W617-M6913	○	M6
		10		VPC40-10W617-M691	—	
		15		VPC40-15W617-M691	—	
		20	M6×1	VPC40-20W617-M691	—	
		6		VPC50-6W617-M6913	○	
		10		VPC50-10W617-M691	—	
	ø50	3	M6×1	VPC50-3W617-M6913	○	M6
		10		VPC50-10W617-M691	—	
		15		VPC50-15W617-M691	—	
		20	M6×1	VPC50-20W617-M691	—	
		6		VPC50-6W617-M6913	○	
		10		VPC50-10W617-M691	—	



Notes

- *1. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
- *2. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

CAD data is available
at PISCO website.Packaging specifications
1 pc. /bag

Options

17 : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)

9 : -DC ⇒ Holder with dust catcher

13 : -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.

*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."



Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code	
Spring type, Top port, Push-in fitting, No cover VPOC  Pad dia. to 	ø6	20	ø3	VPOC8-20W[6]T-J-3J ²	T8	ø6	20	ø1/8	VPOC8-20W[6]T-J-3J ²	T8	
			ø4	VPOC8-20W[6]T-J-4J ²				ø5/32	VPOC8-20W[6]T-J-4J ²		
			ø6	VPOC8-20W[6]T-J-6J ²				ø1/4	VPOC8-20W[6]T-J-6J ²		
		30	ø3	VPOC8-30W[6]T-J-3J ²			30	ø1/8	VPOC8-30W[6]T-J-3J ²		
			ø4	VPOC8-30W[6]T-J-4J ²				ø5/32	VPOC8-30W[6]T-J-4J ²		
			ø6	VPOC8-30W[6]T-J-6J ²				ø1/4	VPOC8-30W[6]T-J-6J ²		
		40	ø3	VPOC8-40W[6]T-J-3J ²			40	ø1/8	VPOC8-40W[6]T-J-3J ²		
			ø4	VPOC8-40W[6]T-J-4J ²				ø5/32	VPOC8-40W[6]T-J-4J ²		
			ø6	VPOC8-40W[6]T-J-6J ²				ø1/4	VPOC8-40W[6]T-J-6J ²		
		50	ø3	VPOC8-50W[6]T-J-3J ²			50	ø1/8	VPOC8-50W[6]T-J-3J ²		
			ø4	VPOC8-50W[6]T-J-4J ²				ø5/32	VPOC8-50W[6]T-J-4J ²		
			ø6	VPOC8-50W[6]T-J-6J ²				ø1/4	VPOC8-50W[6]T-J-6J ²		
	ø8	20	ø3	VPOC8-20W[8]T-J-3J ²	ø8		20	ø1/8	VPOC8-20W[8]T-J-3J ²	ø8	
			ø4	VPOC8-20W[8]T-J-4J ²				ø5/32	VPOC8-20W[8]T-J-4J ²		
			ø6	VPOC8-20W[8]T-J-6J ²				ø1/4	VPOC8-20W[8]T-J-6J ²		
		30	ø4	VPOC8-30W[8]T-J-4J ²			30	ø5/32	VPOC8-30W[8]T-J-4J ²		
			ø6	VPOC8-30W[8]T-J-6J ²				ø1/4	VPOC8-30W[8]T-J-6J ²		
		40	ø3	VPOC8-40W[8]T-J-3J ²			40	ø1/8	VPOC8-40W[8]T-J-3J ²		
			ø4	VPOC8-40W[8]T-J-4J ²				ø5/32	VPOC8-40W[8]T-J-4J ²		
		50	ø6	VPOC8-40W[8]T-J-6J ²			50	ø1/4	VPOC8-40W[8]T-J-6J ²		
			ø3	VPOC8-50W[8]T-J-3J ²				ø1/8	VPOC8-50W[8]T-J-3J ²		
			ø4	VPOC8-50W[8]T-J-4J ²				ø5/32	VPOC8-50W[8]T-J-4J ²		
			ø6	VPOC8-50W[8]T-J-6J ²				ø1/4	VPOC8-50W[8]T-J-6J ²		
	ø10	20	ø3	VPOC10-20W[10]T-J-3J ²	M4		20	ø1/8	VPOC10-20W[10]T-J-3J ²	M4	
			ø4	VPOC10-20W[10]T-J-4J ²							



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Top port, Female thread, No cover VPOC 	ø6	20	M6×1	VPOC6-20W ^[7] -M6 ¹	T8
		30		VPOC6-30W ^[7] -M6 ¹	
		40		VPOC6-40W ^[7] -M6 ¹	
		50		VPOC6-50W ^[7] -M6 ¹	
	ø8	20	M6×1	VPOC8-20W ^[7] -M6 ¹	T8
		30		VPOC8-30W ^[7] -M6 ¹	
		40		VPOC8-40W ^[7] -M6 ¹	
		50		VPOC8-50W ^[7] -M6 ¹	
	ø10	20	M6×1	VPOC10-20W ^[7] -M6 ²	M4
		30		VPOC10-30W ^[7] -M6 ²	
		40		VPOC10-40W ^[7] -M6 ²	
		50		VPOC10-50W ^[7] -M6 ²	
	ø20	20	M6×1	VPOC20-20W ^[7] -M6	M6
		30		VPOC20-30W ^[7] -M6	
		40		VPOC20-40W ^[7] -M6	
		50		VPOC20-50W ^[7] -M6	
	ø30	20	M6×1	VPOC30-20W ^[7] -M6	M6
		30		VPOC30-30W ^[7] -M6	
		40		VPOC30-40W ^[7] -M6	
		50		VPOC30-50W ^[7] -M6	
	ø40	20	M6×1	VPOC40-20W ^[7] -M6	M6
		30		VPOC40-30W ^[7] -M6	
		40		VPOC40-40W ^[7] -M6	
		50		VPOC40-50W ^[7] -M6	
	ø50	20	M6×1	VPOC50-20W ^[7] -M6	M6
		30		VPOC50-30W ^[7] -M6	
		40		VPOC50-40W ^[7] -M6	
		50		VPOC50-50W ^[7] -M6	

Notes
 *1. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
 *2. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

CAD
 CAD data is available
 at PISCO website.

Packaging
 1 pc. /bag

Options
 [7] : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)

Optional items ⇒ P.584	Surface treatment	Fall Prevention Valve	Swivel Joint	Filter
---------------------------	----------------------	-----------------------------	--------------	--------

Vacuum Pad Multi-bellows Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Top port, Push-in fitting, Low dust emission VPLFC 	ø6	2	ø3	VPLFC6-2W ^[7] -3J ²	T8	ø6	2	ø1/8	VPLFC6-2W ^[7] -1/8J ²	T8
			ø4	VPLFC6-2W ^[7] -4J ²				ø5/32	VPLFC6-2W ^[7] -5/32J ²	
		5	ø3	VPLFC6-5W ^[7] -3J ²			5	ø1/8	VPLFC6-5W ^[7] -1/8J ²	
			ø4	VPLFC6-5W ^[7] -4J ²				ø5/32	VPLFC6-5W ^[7] -5/32J ²	
		10	ø3	VPLFC6-10W ^[7] -3J ²			10	ø1/8	VPLFC6-10W ^[7] -1/8J ²	
			ø4	VPLFC6-10W ^[7] -4J ²				ø5/32	VPLFC6-10W ^[7] -5/32J ²	
		15	ø3	VPLFC6-15W ^[7] -3J ²			15	ø1/8	VPLFC6-15W ^[7] -1/8J ²	
			ø4	VPLFC6-15W ^[7] -4J ²				ø5/32	VPLFC6-15W ^[7] -5/32J ²	
		20	ø3	VPLFC6-20W ^[7] -3J ²			20	ø1/8	VPLFC6-20W ^[7] -1/8J ²	
			ø4	VPLFC6-20W ^[7] -4J ²				ø5/32	VPLFC6-20W ^[7] -5/32J ²	
	ø8	2	ø3	VPLFC8-2W ^[7] -3J ²	T8	ø8	2	ø1/8	VPLFC8-2W ^[7] -1/8J ²	T8
			ø4	VPLFC8-2W ^[7] -4J ²				ø5/32	VPLFC8-2W ^[7] -5/32J ²	
		5	ø3	VPLFC8-5W ^[7] -3J ²			5	ø1/8	VPLFC8-5W ^[7] -1/8J ²	
			ø4	VPLFC8-5W ^[7] -4J ²				ø5/32	VPLFC8-5W ^[7] -5/32J ²	
		10	ø3	VPLFC8-10W ^[7] -3J ²			10	ø1/8	VPLFC8-10W ^[7] -1/8J ²	
			ø4	VPLFC8-10W ^[7] -4J ²				ø5/32	VPLFC8-10W ^[7] -5/32J ²	
		15	ø3	VPLFC8-15W ^[7] -3J ²			15	ø1/8	VPLFC8-15W ^[7] -1/8J ²	
			ø4	VPLFC8-15W ^[7] -4J ²				ø5/32	VPLFC8-15W ^[7] -5/32J ²	
		20	ø3	VPLFC8-20W ^[7] -3J ²			20	ø1/8	VPLFC8-20W ^[7] -1/8J ²	
			ø4	VPLFC8-20W ^[7] -4J ²				ø5/32	VPLFC8-20W ^[7] -5/32J ²	
	ø10	2	ø3	VPLFC10-2W ^[7] -3J ²	M4	ø10	2	ø1/8	VPLFC10-2W ^[7] -1/8J ²	M4
			ø4	VPLFC10-2W ^[7] -4J ²				ø5/32	VPLFC10-2W ^[7] -5/32J ²	
		5	ø3	VPLFC10-5W ^[7] -3J ²			5	ø1/8	VPLFC10-5W ^[7] -1/8J ²	
			ø4	VPLFC10-5W ^[7] -4J ²				ø5/32	VPLFC10-5W ^[7] -5/32J ²	
		10	ø3	VPLFC10-10W ^[7] -3J ²			10	ø1/8	VPLFC10-10W ^[7] -1/8J ²	
			ø4	VPLFC10-10W ^[7] -4J ²				ø5/32	VPLFC10-10W ^[7] -5/32J ²	
		15	ø3	VPLFC10-15W ^[7] -3J ²			15	ø1/8	VPLFC10-15W ^[7] -1/8J ²	
			ø4	VPLFC10-15W ^[7] -4J ²				ø5/32	VPLFC10-15W ^[7] -5/32J ²	
		20	ø3	VPLFC10-20W ^[7] -3J ²			20	ø1/8	VPLFC10-20W ^[7] -1/8J ²	
			ø4	VPLFC10-20W ^[7] -4J ²				ø5/32	VPLFC10-20W ^[7] -5/32J ²	

Notes
 *1. Barb fitting type holders are also selectable. Contact us for the details.
 *2. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
 *3. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

Packaging specifications
 1 pc. /bag

Options
 [7] : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)
 [9] : -SF1/4 ⇒ Spring load 1/4

Optional items ⇒ P.584	Surface treatment	Fall Prevention Valve	Swivel Joint	Filter
---------------------------	----------------------	-----------------------------	--------------	--------

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Top port, Push-in fitting, Low dust emission	ø20	5	ø3	VPLFC20-5W ^[7] -3J ^[9]	M6	ø20	5	ø1/8	VPLFC20-5W ^[7] -VJ ^[9]	M6
			ø4	VPLFC20-5W ^[7] -4J ^[9]				ø5/32	VPLFC20-5W ^[7] -VJ ^[9]	
			ø6	VPLFC20-5W ^[7] -6J ^[9]				ø1/4	VPLFC20-5W ^[7] -VJ ^[9]	
		10	ø3	VPLFC20-10W ^[7] -3J ^[9]			10	ø1/8	VPLFC20-10W ^[7] -VJ ^[9]	
			ø4	VPLFC20-10W ^[7] -4J ^[9]				ø5/32	VPLFC20-10W ^[7] -VJ ^[9]	
			ø6	VPLFC20-10W ^[7] -6J ^[9]				ø1/4	VPLFC20-10W ^[7] -VJ ^[9]	
		15	ø3	VPLFC20-15W ^[7] -3J ^[9]			15	ø1/8	VPLFC20-15W ^[7] -VJ ^[9]	
			ø4	VPLFC20-15W ^[7] -4J ^[9]				ø5/32	VPLFC20-15W ^[7] -VJ ^[9]	
			ø6	VPLFC20-15W ^[7] -6J ^[9]				ø1/4	VPLFC20-15W ^[7] -VJ ^[9]	
		20	ø3	VPLFC20-20W ^[7] -3J ^[9]			20	ø1/8	VPLFC20-20W ^[7] -VJ ^[9]	
			ø4	VPLFC20-20W ^[7] -4J ^[9]				ø5/32	VPLFC20-20W ^[7] -VJ ^[9]	
			ø6	VPLFC20-20W ^[7] -6J ^[9]				ø1/4	VPLFC20-20W ^[7] -VJ ^[9]	
	ø30	5	ø3	VPLFC30-5W ^[7] -3J ^[9]		ø30	5	ø1/8	VPLFC30-5W ^[7] -VJ ^[9]	
			ø4	VPLFC30-5W ^[7] -4J ^[9]				ø5/32	VPLFC30-5W ^[7] -VJ ^[9]	
			ø6	VPLFC30-5W ^[7] -6J ^[9]				ø1/4	VPLFC30-5W ^[7] -VJ ^[9]	
		10	ø3	VPLFC30-10W ^[7] -3J ^[9]			10	ø1/8	VPLFC30-10W ^[7] -VJ ^[9]	
			ø4	VPLFC30-10W ^[7] -4J ^[9]				ø5/32	VPLFC30-10W ^[7] -VJ ^[9]	
			ø6	VPLFC30-10W ^[7] -6J ^[9]				ø1/4	VPLFC30-10W ^[7] -VJ ^[9]	
		15	ø3	VPLFC30-15W ^[7] -3J ^[9]			15	ø1/8	VPLFC30-15W ^[7] -VJ ^[9]	
			ø4	VPLFC30-15W ^[7] -4J ^[9]				ø5/32	VPLFC30-15W ^[7] -VJ ^[9]	
			ø6	VPLFC30-15W ^[7] -6J ^[9]				ø1/4	VPLFC30-15W ^[7] -VJ ^[9]	
		20	ø3	VPLFC30-20W ^[7] -3J ^[9]			20	ø1/8	VPLFC30-20W ^[7] -VJ ^[9]	
			ø4	VPLFC30-20W ^[7] -4J ^[9]				ø5/32	VPLFC30-20W ^[7] -VJ ^[9]	
			ø6	VPLFC30-20W ^[7] -6J ^[9]				ø1/4	VPLFC30-20W ^[7] -VJ ^[9]	
	ø40	5	ø3	VPLFC40-5W ^[7] -3J ^[9]		ø40	5	ø1/8	VPLFC40-5W ^[7] -VJ ^[9]	
			ø4	VPLFC40-5W ^[7] -4J ^[9]				ø5/32	VPLFC40-5W ^[7] -VJ ^[9]	
			ø6	VPLFC40-5W ^[7] -6J ^[9]				ø1/4	VPLFC40-5W ^[7] -VJ ^[9]	
		10	ø3	VPLFC40-10W ^[7] -3J ^[9]			10	ø1/8	VPLFC40-10W ^[7] -VJ ^[9]	
			ø4	VPLFC40-10W ^[7] -4J ^[9]				ø5/32	VPLFC40-10W ^[7] -VJ ^[9]	
			ø6	VPLFC40-10W ^[7] -6J ^[9]				ø1/4	VPLFC40-10W ^[7] -VJ ^[9]	
		15	ø3	VPLFC40-15W ^[7] -3J ^[9]			15	ø1/8	VPLFC40-15W ^[7] -VJ ^[9]	
			ø4	VPLFC40-15W ^[7] -4J ^[9]				ø5/32	VPLFC40-15W ^[7] -VJ ^[9]	
			ø6	VPLFC40-15W ^[7] -6J ^[9]				ø1/4	VPLFC40-15W ^[7] -VJ ^[9]	
		20	ø3	VPLFC40-20W ^[7] -3J ^[9]			20	ø1/8	VPLFC40-20W ^[7] -VJ ^[9]	
			ø4	VPLFC40-20W ^[7] -4J ^[9]				ø5/32	VPLFC40-20W ^[7] -VJ ^[9]	
			ø6	VPLFC40-20W ^[7] -6J ^[9]				ø1/4	VPLFC40-20W ^[7] -VJ ^[9]	
	ø50	5	ø3	VPLFC50-5W ^[7] -3J ^[9]		ø50	5	ø1/8	VPLFC50-5W ^[7] -VJ ^[9]	
			ø4	VPLFC50-5W ^[7] -4J ^[9]				ø5/32	VPLFC50-5W ^[7] -VJ ^[9]	
			ø6	VPLFC50-5W ^[7] -6J ^[9]				ø1/4	VPLFC50-5W ^[7] -VJ ^[9]	
		10	ø3	VPLFC50-10W ^[7] -3J ^[9]			10	ø1/8	VPLFC50-10W ^[7] -VJ ^[9]	
			ø4	VPLFC50-10W ^[7] -4J ^[9]				ø5/32	VPLFC50-10W ^[7] -VJ ^[9]	
			ø6	VPLFC50-10W ^[7] -6J ^[9]				ø1/4	VPLFC50-10W ^[7] -VJ ^[9]	
		15	ø3	VPLFC50-15W ^[7] -3J ^[9]			15	ø1/8	VPLFC50-15W ^[7] -VJ ^[9]	
			ø4	VPLFC50-15W ^[7] -4J ^[9]				ø5/32	VPLFC50-15W ^[7] -VJ ^[9]	
			ø6	VPLFC50-15W ^[7] -6J ^[9]				ø1/4	VPLFC50-15W ^[7] -VJ ^[9]	
		20	ø3	VPLFC50-20W ^[7] -3J ^[9]			20	ø1/8	VPLFC50-20W ^[7] -VJ ^[9]	
			ø4	VPLFC50-20W ^[7] -4J ^[9]				ø5/32	VPLFC50-20W ^[7] -VJ ^[9]	
			ø6	VPLFC50-20W ^[7] -6J ^[9]				ø1/4	VPLFC50-20W ^[7] -VJ ^[9]	

Notes
*Barb fitting type holders are also selectable. Contact us for the details.

Packaging specifications
1 pc./bag

Options
[7] : Surface treatment (DLC, coating, Reformed surface, and Fluoro-coating)
[9] : -SF1/4 ⇒ Spring load 1/4

Optional items
⇒ P.584

Surface
treatment

Fall
Prevention
Valve

Swivel Joint

Filter

Vacuum Pad Multi-bellows Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Top port, Female thread, Low dust emission	ø6	2	M5×0.8	VPLFC6-2W ^[7] -M5 ^[9]	T8
		5	M5×0.8	VPLFC6-5W ^[7] -M5 ^[9]	
		10	M5×0.8	VPLFC6-10W ^[7] -M5 ^[9]	
		15	M5×0.8	VPLFC6-15W ^[7] -M5 ^[9]	
		20	M5×0.8	VPLFC6-20W ^[7] -M5 ^[9]	
		2	M5×0.8	VPLFC6-2W ^[7] -M5 ^[9]	
	ø8	2	M5×0.8	VPLFC8-2W ^[7] -M5 ^[9]	T8
		5	M5×0.8	VPLFC8-5W ^[7] -M5 ^[9]	
		10	M5×0.8	VPLFC8-10W ^[7] -M5 ^[9]	
		15	M5×0.8	VPLFC8-15W ^[7] -M5 ^[9]	
		20	M5×0.8	VPLFC8-20W ^[7] -M5 ^[9]	
		2	M5×0.8	VPLFC8-2W ^[7] -M5 ^[9]	
	ø10	2	M5×0.8	VPLFC10-2W ^[7] -M5 ^[9]	M4
		5	M5×0.8	VPLFC10-5W ^[7] -M5 ^[9]	
		10	M5×0.8	VPLFC10-10W ^[7] -M5 ^[9]	
		15	M5×0.8	VPLFC10-15W ^[7] -M5 ^[9]	
		20	M5×0.8	VPLFC10-20W ^[7] -M5 ^[9]	
		2	M5×0.8	VPLFC10-2W ^[7] -M5 ^[9]	
	ø20	5	M6×1	VPLFC20-5W ^[7] -M6 ^[9]	M6
		10	M6×1	VPLFC20-10W ^[7] -M6 ^[9]	
		15	M6×1	VPLFC20-15W ^[7] -M6 ^[9]	
		20	M6×1	VPLFC20-20W ^[7] -M6 ^[9]	
		5	M6×1	VPLFC30-5W ^[7] -M6 ^[9]	
		10	M6×1	VPLFC30-10W ^[7] -M6 ^[9]	
	ø30	15	M6×1	VPLFC30-15W ^[7] -M6 ^[9]	M6
		20	M6×1	VPLFC30-20W ^[7] -M6 ^[9]	
		5	M6×1	VPLFC40-5W ^[7] -M6 ^[9]	
		10	M6×1	VPLFC40-10W ^[7] -M6 ^[9]	
		15	M6×1	VPLFC40-15W ^[7] -M6 ^[9]	
		20	M6×1	VPLFC40-20W ^[7] -M6 ^[9]	
	ø40	5	M6×1	VPLFC50-5W ^[7] -M6 ^[9]	M6
		10	M6×1	VPLFC50-10W ^[7] -M6 ^[9]	
		15	M6×1	VPLFC50-15W ^[7] -M6 ^[9]	
		20	M6×1	VPLFC50-20W ^[7] -M6 ^[9]	
	ø50	5	M6×1	VPLFC50-5W ^[7] -M6 ^[9]	M6
		10	M6×1	VPLFC50-10W ^[7] -M6 ^[9]	
		15	M6×1	VPLFC50-15W ^[7] -M6 ^[9]	
		20	M6×1	VPLFC50-20W ^[7] -M6 ^[9]	

Notes
*1. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
*2. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

Packaging specifications
1 pc./bag

Options
[7] : Surface treatment (DLC, coating, Reformed surface, and Fluoro-coating)
[9] : -SF1/4 ⇒ Spring load 1/4

Optional items
⇒ P.584

Surface
treatment

Fall
Prevention
Valve

Swivel Joint

Filter

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	TS : -S3 -S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	TS : -S3 -S3 spec.	Connection config. code
Spring type, Side port, Push-in fitting, Mini VPMD 	ø6	ø3	VPMD6-2W617-3J ²	—	T8	ø6	ø1/8	VPMD6-2W617-4J9 ²	○	T8
		ø4	VPMD6-2W617-4J9 ²	○			ø5/32	VPMD6-2W617-4J9 ²	○	
	ø8	ø3	VPMD8-2W617-3J ²	—		ø8	ø1/8	VPMD8-2W617-4J9 ²	○	
		ø4	VPMD8-2W617-4J9 ²	○			ø5/32	VPMD8-2W617-4J9 ²	○	
	ø10	ø3	VPMD10-4W617-3J ²	—		ø10	ø1/8	VPMD10-4W617-4J9 ²	○	M4
		ø4	VPMD10-4W617-4J9 ²	○			ø5/32	VPMD10-4W617-4J9 ²	○	
	ø20	ø6	VPMD10-4W617-6J9 ²	○		ø20	ø1/4	VPMD10-4W617-4J9 ²	—	
		ø3	VPMD20-4W617-3J ²	—		ø20	ø1/8	VPMD20-4W617-4J9 ²	—	
	ø30	ø4	VPMD20-4W617-4J9 ²	○		ø30	ø5/32	VPMD20-4W617-4J9 ²	○	M6
		ø6	VPMD20-4W617-6J9 ²	○			ø1/4	VPMD20-4W617-4J9 ²	—	
	ø40	ø3	VPMD30-4W617-3J ²	—		ø40	ø1/8	VPMD30-4W617-4J9 ²	—	
		ø4	VPMD30-4W617-4J9 ²	○		ø40	ø5/32	VPMD30-4W617-4J9 ²	○	
	ø50	ø6	VPMD40-4W617-6J9 ²	○		ø50	ø1/4	VPMD40-4W617-4J9 ²	—	
		ø3	VPMD40-4W617-3J ²	—		ø50	ø1/8	VPMD40-4W617-4J9 ²	○	
		ø4	VPMD50-4W617-4J9 ²	○			ø5/32	VPMD50-4W617-4J9 ²	○	
		ø6	VPMD50-4W617-6J9 ²	○			ø1/4	VPMD50-4W617-4J9 ²	—	

Holder type	Pad dia. (mm)	Male thread size	Model code	TS : -S3 -S3 spec.	Connection config. code
Spring type, Side port, Female thread, Mini VPMD 	ø6	M3×0.5	VPMD6-2W617-M39 ²	○	T8
	ø8	M3×0.5	VPMD8-2W617-M39 ²	○	
	ø10	M5×0.8	VPMD10-4W617-M59 ²	○	M4
	ø20	M5×0.8	VPMD20-4W617-M59 ²	○	
	ø30	M5×0.8	VPMD30-4W617-M59 ²	○	M6
	ø40	M5×0.8	VPMD40-4W617-M59 ²	○	
	ø50	M5×0.8	VPMD50-4W617-M59 ²	○	

- Notes**
- *1. Holders are also available in Push-in fitting type for tube O.D. of 1.8 mm and 2 mm, and barb fitting type. Contact us for the details.
 - *2. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
 - *3. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

CAD data is available
at PISCO website.

Packaging specifications
1 pc. /bag

- Options**
- [7] : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)
- [8] : -S3 ⇒ -S3 spec. (○ in the lists: Available)
- *1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
- *2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items ⇒ P.584	Surface treatment	Fall Prevention Valve	Swivel Joint	Filter
				

Vacuum Pad Multi-bellows Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	TS : -S3 -S3 spec.	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	TS : -S3 -S3 spec.	Connection config. code
Spring type, Side port, Push-in fitting, Standard VPD 	ø6	3	ø3	VPD6-3W617-3J9 ²	—	T8	ø6	3	ø1/8	VPD6-3W617-4J9 ²	—	T8
			ø4	VPD6-3W617-4J9 ²	○				ø5/32	VPD6-3W617-4J9 ²	○	
			ø6	VPD6-3W617-6J9 ²	○				ø1/4	VPD6-3W617-4J9 ²	—	
		10	ø3	VPD6-10W617-3J9 ²	—			10	ø1/8	VPD6-10W617-4J9 ²	—	
			ø4	VPD6-10W617-4J9 ²	—				ø5/32	VPD6-10W617-4J9 ²	—	
			ø6	VPD6-10W617-6J9 ²	—				ø1/4	VPD6-10W617-4J9 ²	—	
		15	ø3	VPD6-15W617-3J9 ²	—			15	ø1/8	VPD6-15W617-4J9 ²	—	
			ø4	VPD6-15W617-4J9 ²	—				ø5/32	VPD6-15W617-4J9 ²	—	
			ø6	VPD6-15W617-6J9 ²	—				ø1/4	VPD6-15W617-4J9 ²	—	
		20	ø3	VPD6-20W617-3J9 ²	—			20	ø1/8	VPD6-20W617-4J9 ²	—	
			ø4	VPD6-20W617-4J9 ²	—				ø5/32	VPD6-20W617-4J9 ²	—	
			ø6	VPD6-20W617-6J9 ²	—				ø1/4	VPD6-20W617-4J9 ²	—	
	ø8	3	ø3	VPD8-3W617-3J9 ²	—		ø8	3	ø1/8	VPD8-3W617-4J9 ²	—	
			ø4	VPD8-3W617-4J9 ²	○				ø5/32	VPD8-3W617-4J9 ²	○	
			ø6	VPD8-3W617-6J9 ²	○				ø1/4	VPD8-3W617-4J9 ²	—	
		10	ø3	VPD8-10W617-3J9 ²	—			10	ø1/8	VPD8-10W617-4J9 ²	—	
			ø4	VPD8-10W617-4J9 ²	—				ø5/32	VPD8-10W617-4J9 ²	—	
			ø6	VPD8-10W617-6J9 ²	—				ø1/4	VPD8-10W617-4J9 ²	—	
		15	ø3	VPD8-15W617-3J9 ²	—			15	ø1/8	VPD8-15W617-4J9 ²	—	
			ø4	VPD8-15W617-4J9 ²	—				ø5/32	VPD8-15W617-4J9 ²	—	
			ø6	VPD8-15W617-6J9 ²	—				ø1/4	VPD8-15W617-4J9 ²	—	
		20	ø3	VPD8-20W617-3J9 ²	—			20	ø1/8	VPD8-20W617-4J9 ²	—	
			ø4	VPD8-20W617-4J9 ²	—				ø5/32	VPD8-20W617-4J9 ²	—	
			ø6	VPD8-20W617-6J9 ²	—				ø1/4	VPD8-20W617-4J9 ²	—	
	ø10	6	ø3	VPD10-6W617-3J9 ²	—	M4	ø10	6	ø1/8	VPD10-6W617-4J9 ²	—	M4
			ø4	VPD10-6W617-4J9 ²	○				ø5/32	VPD10-6W617-4J9 ²	○	
			ø6	VPD10-6W617-6J9 ²	○				ø1/4	VPD10-6W617-4J9 ²	—	
		10	ø3	VPD10-10W617-3J9 ²	—			10	ø1/8	VPD10-10W617-4J9 ²	—	
			ø4	VPD10-10W617-4J9 ²	—				ø5/32	VPD10-10W617-4J9 ²	—	
			ø6	VPD10-10W617-6J9 ²	—				ø1/4	VPD10-10W617-4J9 ²	—	
		15	ø3	VPD10-15W617-3J9 ²	—			15	ø1/8	VPD10-15W617-4J9 ²	—	
			ø4	VPD10-15W617-4J9 ²	—				ø5/32	VPD10-15W617-4J9 ²	—	
			ø6	VPD10-15W617-6J9 ²	—				ø1/4	VPD10-15W617-4J9 ²	—	
		20	ø3	VPD10-20W617-3J9 ²	—			20	ø1/8	VPD10-20W617-4J9 ²	—	
			ø4	VPD10-20W617-4J9 ²	—				ø5/32	VPD10-20W617-4J9 ²	—	
			ø6	VPD10-20W617-6J9 ²	—				ø1/4	VPD10-20W617-4J9 ²	—	

- Notes**
- *1. Holders are also available in Push-in fitting type (limited to pad dia. 8 mm or smaller) for tube O.D. of 1.8 mm and 2 mm, and barb fitting type. Contact us for the details.
 - *2. Extra soft silicone (YS2/YS4) and Urethane (U) are not available.
 - *3. Extra soft silicone (YS2/YS4) is available only when Fluoro-coating treatment is selected.

CAD data is available
at PISCO website.

Packaging specifications
1 pc. /bag

- Options**
- [7] : Surface treatment (DLC. coating, Reformed surface, and Fluoro-coating)
- [9] : -DC ⇒ Holder with dust catcher
- [8] : -S3 ⇒ -S3 spec. (○ in the lists: Available)
- *1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
- *2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items ⇒ P.584	Surface treatment	Dust Catcher (VPD)	Fall Prevention Valve	Swivel Joint	Filter
					

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, No cover  Pad dia.  to 	ø6	20	ø3	VP0D6-20W[6]T-J ³ J ²	T8	20	ø1/8	VP0D6-20W[6]T-J ³ J ²	T8	
			ø4	VP0D6-20W[6]T-J ⁴ J ²			ø5/32	VP0D6-20W[6]T-J ⁴ J ²		
			ø6	VP0D6-20W[6]T-J ⁶ J ²			ø1/4	VP0D6-20W[6]T-J ⁶ J ²		
		30	ø3	VP0D6-30W[6]T-J ³ J ²		30	ø1/8	VP0D6-30W[6]T-J ³ J ²		
			ø4	VP0D6-30W[6]T-J ⁴ J ²			ø5/32	VP0D6-30W[6]T-J ⁴ J ²		
			ø6	VP0D6-30W[6]T-J ⁶ J ²			ø1/4	VP0D6-30W[6]T-J ⁶ J ²		
		40	ø3	VP0D6-40W[6]T-J ³ J ²		40	ø1/8	VP0D6-40W[6]T-J ³ J ²		
			ø4	VP0D6-40W[6]T-J ⁴ J ²			ø5/32	VP0D6-40W[6]T-J ⁴ J ²		
			ø6	VP0D6-40W[6]T-J ⁶ J ²			ø1/4	VP0D6-40W[6]T-J ⁶ J ²		
		50	ø3	VP0D6-50W[6]T-J ³ J ²		50	ø1/8	VP0D6-50W[6]T-J ³ J ²		
			ø4	VP0D6-50W[6]T-J ⁴ J ²			ø5/32	VP0D6-50W[6]T-J ⁴ J ²		
			ø6	VP0D6-50W[6]T-J ⁶ J ²			ø1/4	VP0D6-50W[6]T-J ⁶ J ²		
	ø8	20	ø3	VP0D8-20W[8]T-J ³ J ²	ø8	20	ø1/8	VP0D8-20W[8]T-J ³ J ²	ø8	
			ø4	VP0D8-20W[8]T-J ⁴ J ²			ø5/32	VP0D8-20W[8]T-J ⁴ J ²		
			ø6	VP0D8-20W[8]T-J ⁶ J ²			ø1/4	VP0D8-20W[8]T-J ⁶ J ²		
		30	ø3	VP0D8-30W[8]T-J ³ J ²		30	ø1/8	VP0D8-30W[8]T-J ³ J ²		
			ø4	VP0D8-30W[8]T-J ⁴ J ²			ø5/32	VP0D8-30W[8]T-J ⁴ J ²		
			ø6	VP0D8-30W[8]T-J ⁶ J ²			ø1/4	VP0D8-30W[8]T-J ⁶ J ²		
		40	ø3	VP0D8-40W[8]T-J ³ J ²		40	ø1/8	VP0D8-40W[8]T-J ³ J ²		
			ø4	VP0D8-40W[8]T-J ⁴ J ²			ø5/32	VP0D8-40W[8]T-J ⁴ J ²		
			ø6	VP0D8-40W[8]T-J ⁶ J ²			ø1/4	VP0D8-40W[8]T-J ⁶ J ²		
		50	ø3	VP0D8-50W[8]T-J ³ J ²		50	ø1/8	VP0D8-50W[8]T-J ³ J ²		
			ø4	VP0D8-50W[8]T-J ⁴ J ²			ø5/32	VP0D8-50W[8]T-J ⁴ J ²		
			ø6	VP0D8-50W[8]T-J ⁶ J ²			ø1/4	VP0D8-50W[8]T-J ⁶ J ²		
	ø10	20	ø3	VP0D10-20W[10]T-J ³ J ²	M4	20	ø1/8	VP0D10-20W[10]T-J ³ J ²	M4	
			ø4	VP0D10-20W[10]T-J ⁴ J ²			ø5/32	VP0D10-20W[10]T-J ⁴ J ²		
			ø6	VP0D10-20W[10]T-J ⁶ J ²			ø1/4	VP0D10-20W[10]T-J		



Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config code
Spring type, Side port, Push-in fitting, No cover VPOD  Pad dia.  to 	ø20	20	ø3	VPOD20-20W[7]-3J	MS	ø20	20	ø1/8	VPOD20-20W[7]-4J	MS
			ø4	VPOD20-20W[6]-4J				ø5/32	VPOD20-20W[6]-4J	
			ø6	VPOD20-20W[6]-6J				ø1/4	VPOD20-20W[6]-4J	
		30	ø3	VPOD20-30W[7]-3J			30	ø1/8	VPOD20-30W[7]-4J	
			ø4	VPOD20-30W[6]-4J				ø5/32	VPOD20-30W[6]-4J	
			ø6	VPOD20-30W[6]-6J				ø1/4	VPOD20-30W[6]-4J	
		40	ø3	VPOD20-40W[7]-3J			40	ø1/8	VPOD20-40W[7]-4J	
			ø4	VPOD20-40W[6]-4J				ø5/32	VPOD20-40W[6]-4J	
			ø6	VPOD20-40W[6]-6J				ø1/4	VPOD20-40W[6]-4J	
		50	ø3	VPOD20-50W[7]-3J			50	ø1/8	VPOD20-50W[7]-4J	
			ø4	VPOD20-50W[6]-4J				ø5/32	VPOD20-50W[6]-4J	
			ø6	VPOD20-50W[6]-6J				ø1/4	VPOD20-50W[6]-4J	
	ø30	20	ø3	VPOD30-20W[7]-3J		ø30	20	ø1/8	VPOD30-20W[7]-4J	
			ø4	VPOD30-20W[6]-4J				ø5/32	VPOD30-20W[6]-4J	
			ø6	VPOD30-20W[6]-6J				ø1/4	VPOD30-20W[6]-4J	
		30	ø3	VPOD30-30W[7]-3J			30	ø1/8	VPOD30-30W[7]-4J	
			ø4	VPOD30-30W[6]-4J				ø5/32	VPOD30-30W[6]-4J	
			ø6	VPOD30-30W[6]-6J				ø1/4	VPOD30-30W[6]-4J	
		40	ø3	VPOD30-40W[7]-3J			40	ø1/8	VPOD30-40W[7]-4J	
			ø4	VPOD30-40W[6]-4J				ø5/32	VPOD30-40W[6]-4J	
			ø6	VPOD30-40W[6]-6J				ø1/4	VPOD30-40W[6]-4J	
		50	ø3	VPOD30-50W[7]-3J			50	ø1/8	VPOD30-50W[7]-4J	
			ø4	VPOD30-50W[6]-4J				ø5/32	VPOD30-50W[6]-4J	
			ø6	VPOD30-50W[6]-6J				ø1/4	VPOD30-50W[6]-4J	
	ø40	20	ø3	VPOD40-20W[7]-3J		ø40	20	ø1/8	VPOD40-20W[7]-4J	
			ø4	VPOD40-20W[6]-4J				ø5/32	VPOD40-20W[6]-4J	
			ø6	VPOD40-20W[6]-6J				ø1/4	VPOD40-20W[6]-4J	
		30	ø3	VPOD40-30W[7]-3J			30	ø1/8	VPOD40-30W[7]-4J	
			ø4	VPOD40-30W[6]-4J				ø5/32	VPOD40-30W[6]-4J	
			ø6	VPOD40-30W[6]-6J				ø1/4	VPOD40-30W[6]-4J	
		40	ø3	VPOD40-40W[7]-3J			40	ø1/8	VPOD40-40W[7]-4J	

Optional items ⇒ P.584	Surface treatment 	Fall Prevention Valve 	Swivel Joint 	Filter 
---------------------------	--	---	--	--



	Packaging specifications
	1 pc. /bag

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Side port, Female thread, No cover VPOD	ø6	20	M6×1	VPOD6-20W617-M6 ²	T8
		30		VPOD6-30W617-M6 ²	
		40		VPOD6-40W617-M6 ²	
		50		VPOD6-50W617-M6 ²	
	ø8	20	M6×1	VPOD8-20W617-M6 ²	T8
		30		VPOD8-30W617-M6 ²	
		40		VPOD8-40W617-M6 ²	
		50		VPOD8-50W617-M6 ²	
	ø10	20	M6×1	VPOD10-20W617-M6 ²	M4
		30		VPOD10-30W617-M6 ²	
		40		VPOD10-40W617-M6 ²	
		50		VPOD10-50W617-M6 ²	
	ø20	20	M6×1	VPOD20-20W617-M6	M6
		30		VPOD20-30W617-M6	
		40		VPOD20-40W617-M6	
		50		VPOD20-50W617-M6	
	ø30	20	M6×1	VPOD30-20W617-M6	M6
		30		VPOD30-30W617-M6	
		40		VPOD30-40W617-M6	
		50		VPOD30-50W617-M6	
	ø40	20	M6×1	VPOD40-20W617-M6	M6
		30		VPOD40-30W617-M6	
		40		VPOD40-40W617-M6	
		50		VPOD40-50W617-M6	
	ø50	20	M6×1	VPOD50-20W617-M6	M6
		30		VPOD50-30W617-M6	
		40		VPOD50-40W617-M6	
		50		VPOD50-50W617-M6	
Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, Low dust emission VPLFD	ø6	5	ø3	VPLFD6-5W617-3J ²	T8
			ø4	VPLFD6-5W617-4J ²	
		10	ø3	VPLFD6-10W617-3J ²	
			ø4	VPLFD6-10W617-4J ²	
		15	ø3	VPLFD6-15W617-3J ²	
			ø4	VPLFD6-15W617-4J ²	
		20	ø3	VPLFD6-20W617-3J ²	
			ø4	VPLFD6-20W617-4J ²	
	ø8	5	ø3	VPLFD8-5W617-3J ²	T8
			ø4	VPLFD8-5W617-4J ²	
		10	ø3	VPLFD8-10W617-3J ²	
			ø4	VPLFD8-10W617-4J ²	
		15	ø3	VPLFD8-15W617-3J ²	
			ø4	VPLFD8-15W617-4J ²	
		20	ø3	VPLFD8-20W617-3J ²	
			ø4	VPLFD8-20W617-4J ²	
	ø10	5	ø3	VPLFD10-5W617-3J ²	M4
			ø4	VPLFD10-5W617-4J ²	
		10	ø3	VPLFD10-10W617-3J ²	
			ø4	VPLFD10-10W617-4J ²	
		15	ø3	VPLFD10-15W617-3J ²	
			ø4	VPLFD10-15W617-4J ²	
		20	ø3	VPLFD10-20W617-3J ²	
			ø4	VPLFD10-20W617-4J ²	
Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, Low dust emission VPLFD	ø6	5	ø1/8	VPLFD6-5W617-1/8J ²	T8
			ø5/32	VPLFD6-5W617-1/16J ²	
		10	ø1/8	VPLFD6-10W617-1/8J ²	
			ø5/32	VPLFD6-10W617-1/16J ²	
		15	ø1/8	VPLFD6-15W617-1/8J ²	
			ø5/32	VPLFD6-15W617-1/16J ²	
		20	ø1/8	VPLFD6-20W617-1/8J ²	
			ø5/32	VPLFD6-20W617-1/16J ²	
	ø8	5	ø1/8	VPLFD8-5W617-1/8J ²	T8
			ø5/32	VPLFD8-5W617-1/16J ²	
		10	ø1/8	VPLFD8-10W617-1/8J ²	
			ø5/32	VPLFD8-10W617-1/16J ²	
		15	ø1/8	VPLFD8-15W617-1/8J ²	
			ø5/32	VPLFD8-15W617-1/16J ²	
		20	ø1/8	VPLFD8-20W617-1/8J ²	
			ø5/32	VPLFD8-20W617-1/16J ²	
	ø10	5	ø1/8	VPLFD10-5W617-1/8J ²	M4
			ø5/32	VPLFD10-5W617-1/16J ²	
		10	ø1/8	VPLFD10-10W617-1/8J ²	
			ø5/32	VPLFD10-10W617-1/16J ²	
		15	ø1/8	VPLFD10-15W617-1/8J ²	
			ø5/32	VPLFD10-15W617-1/16J ²	
		20	ø1/8	VPLFD10-20W617-1/8J ²	
			ø5/32	VPLFD10-20W617-1/16J ²	

Vacuum Pad Multi-bellows Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, Low dust emission VPLFD 	ø20	5	ø3	VPLFD20-5W617-3J	ø20	5	ø1/8	VPLFD20-5W617-1/8J	ø20	
			ø4	VPLFD20-5W617-4J			ø5/32	VPLFD20-5W617-1/16J		
			ø6	VPLFD20-5W617-6J			ø1/4	VPLFD20-5W617-1/4J		
		10	ø3	VPLFD20-10W617-3J		10	ø1/8	VPLFD20-10W617-1/8J		
			ø4	VPLFD20-10W617-4J			ø5/32	VPLFD20-10W617-1/16J		
			ø6	VPLFD20-10W617-6J			ø1/4	VPLFD20-10W617-1/4J		
		15	ø3	VPLFD20-15W617-3J		15	ø1/8	VPLFD20-15W617-1/8J		
			ø4	VPLFD20-15W617-4J			ø5/32	VPLFD20-15W617-1/16J		
			ø6	VPLFD20-15W617-6J			ø1/4	VPLFD20-15W617-1/4J		
		20	ø3	VPLFD20-20W617-3J		20	ø1/8	VPLFD20-20W617-1/8J		
			ø4	VPLFD20-20W617-4J			ø5/32	VPLFD20-20W617-1/16J		
			ø6	VPLFD20-20W617-6J			ø1/4	VPLFD20-20W617-1/4J		
	ø30	5	ø3	VPLFD30-5W617-3J	ø30	5	ø1/8	VPLFD30-5W617-1/8J	ø30	
			ø4	VPLFD30-5W617-4J			ø5/32	VPLFD30-5W617-1/16J		
			ø6	VPLFD30-5W617-6J			ø1/4	VPLFD30-5W617-1/4J		
		10	ø3	VPLFD30-10W617-3J		10	ø1/8	VPLFD30-10W617-1/8J		
			ø4	VPLFD30-10W617-4J			ø5/32	VPLFD30-10W617-1/16J		
			ø6	VPLFD30-10W617-6J			ø1/4	VPLFD30-10W617-1/4J		
		15	ø3	VPLFD30-15W617-3J		15	ø1/8	VPLFD30-15W617-1/8J		
			ø4	VPLFD30-15W617-4J			ø5/32	VPLFD30-15W617-1/16J		
			ø6	VPLFD30-15W617-6J			ø1/4	VPLFD30-15W617-1/4J		
		20	ø3	VPLFD30-20W617-3J		20	ø1/8	VPLFD30-20W617-1/8J		
			ø4	VPLFD30-20W617-4J			ø5/32	VPLFD30-20W617-1/16J		
			ø6	VPLFD30-20W617-6J			ø1/4	VPLFD30-20W617-1/4J		
ø40	5	ø3	VPLFD40-5W617-3J	ø40	5	ø1/8	VPLFD40-5W617-1/8J	ø40		
		ø4	VPLFD40-5W617-4J			ø5/32	VPLFD40-5W617-1/16J			
		ø6	VPLFD40-5W617-6J			ø1/4	VPLFD40-5W617-1/4J			
	10	ø3	VPLFD40-10W617-3J		10	ø1/8	VPLFD40-10W617-1/8J			
		ø4	VPLFD40-10W617-4J			ø5/32	VPLFD40-10W617-1/16J			
		ø6	VPLFD40-10W617-6J			ø1/4	VPLFD40-10W617-1/4J			
	15	ø3	VPLFD40-15W617-3J		15	ø1/8	VPLFD40-15W617-1/8J			
		ø4	VPLFD40-15W617-4J			ø5/32	VPLFD40-15W617-1/16J			
		ø6	VPLFD40-15W617-6J			ø1/4	VPLFD40-15W617-1/4J			
	20	ø3	VPLFD40-20W617-3J		20	ø1/8	VPLFD40-20W617-1/8J			
		ø4	VPLFD40-20W617-4J			ø5/32	VPLFD40-20W617-1/16J			
		ø6	VPLFD40-20W617-6J			ø1/4	VPLFD40-20W617-1/4J			
ø50	5	ø3	VPLFD50-5W617-3J	ø50	5	ø1/8	VPLFD50-5W617-1/8J	ø50		
		ø4	VPLFD50-5W617-4J			ø5/32	VPLFD50-5W617-1/16J			
		ø6	VPLFD50-5W617-6J			ø1/4	VPLFD50-5W617-1/4J			
	10	ø3	VPLFD50-10W617-3J		10	ø1/8	VPLFD50-10W617-1/8J			
		ø4	VPLFD50-10W617-4J			ø5/32	VPLFD50-10W617-1/16J			
		ø6	VPLFD50-10W617-6J			ø1/4	VPLFD50-10W617-1/4J			
	15	ø3	VPLFD50-15W617-3J		15	ø1/8	VPLFD50-15W617-1/8J			
		ø4	VPLFD50-15W617-4J			ø5/32	VPLFD50-15W617-1/16J			
		ø6	VPLFD50-15W617-6J			ø1/4	VPLFD50-15W617-1/4J			
	20	ø3	VPLFD50-20W617-3J		20	ø1/8	VPLFD50-20W617-1/8J			
		ø4	VPLFD50-20W617-4J			ø5/32	VPLFD50-20W617-1/16J			
		ø6	VPLFD50-20W617-6J			ø1/4	VPLFD50-20W617-1/4J			

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code	Holder type	Pad dia. (mm)	Female thread size	Model code	IS : -S3 -S3 spec	Connection config. code	
Spring type, Female thread, Low dust emission VPLFD 	ø6	5	M5×0.8	VPLFD6-SW617-M5 ²	TB	Fixed type, Direct mount, Mini VPME 	ø6	M5×0.8	VPME6W617-M513 ²	○	TB	
		10	M5×0.8	VPLFD6-10W617-M5 ²			ø8	M5×0.8	VPME8W617-M513 ²	○		
		15	M5×0.8	VPLFD6-15W617-M5 ²								
	ø8	20	M5×0.8	VPLFD6-20W617-M5 ²								
		5	M5×0.8	VPLFD8-SW617-M5 ²								
		10	M5×0.8	VPLFD8-10W617-M5 ²								
	ø10	15	M5×0.8	VPLFD8-15W617-M5 ²								
		20	M5×0.8	VPLFD8-20W617-M5 ²								
		5	M5×0.8	VPLFD10-SW617-M5 ²		M4						
	10	M5×0.8	VPLFD10-10W617-M5 ²									
	ø20	15	M5×0.8	VPLFD10-15W617-M5 ²								
		20	M5×0.8	VPLFD10-20W617-M5 ²								
		5	M6×1	VPLFD20-SW617-M6		M6						
	10	M6×1	VPLFD20-10W617-M6									
	ø30	15	M6×1	VPLFD20-15W617-M6								
		20	M6×1	VPLFD20-20W617-M6								
		5	M6×1	VPLFD30-SW617-M6		M6						
	10	M6×1	VPLFD30-10W617-M6									
	ø40	15	M6×1	VPLFD30-15W617-M6								
		20	M6×1	VPLFD30-20W617-M6								
		5	M6×1	VPLFD40-SW617-M6		M6						
	10	M6×1	VPLFD40-10W617-M6									
ø50	15	M6×1	VPLFD40-15W617-M6									
	20	M6×1	VPLFD40-20W617-M6									
	5	M6×1	VPLFD50-SW617-M6									
	10	M6×1	VPLFD50-10W617-M6									
	15	M6×1	VPLFD50-15W617-M6									
	20	M6×1	VPLFD50-20W617-M6									
Holder type	Pad dia. (mm)	Female thread size	Model code	IS : -S3 -S3 spec	Connection config. code							
Fixed type, Direct mount, Standard VPE 	ø6	M5×0.8	VPE6W617-M513 ²	○	TB	VPE holders are available with metric male/female threads, taper pipe threads, parallel pipe threads and NPT threads. See Pad holder only (page 399) for variations. *Pads with the same configuration code as the holder can be connected. [See Pad rubber only (page 380)]. Applicable Screws Metric male thread: M5, M8, M10, M12, M14 Metric female thread: M5, M8 Taper pipe thread: R1/8, R1/4, R3/8, R1/2 Parallel pipe thread: G1/8, G1/4, G3/8, G1/2 NPT thread: NPT1/4, NPT3/8, NPT1/2						
	ø8	M5×0.8	VPE8W617-M513 ²	○								
Holder type	Pad dia. (mm)	Female thread size	Model code	IS : -S3 -S3 spec	Connection config. code							
Spring type, Direct mount VPF 	ø6	M10×1	VPF6W6171913 ²	○	TB							
	ø8	M10×1	VPF8W6171913 ²	○								
	ø10	M14×1	VPF10W6171913 ²	○		M4						
	ø20	M14×1	VPF20W6171913	○								
	ø30	M14×1	VPF30W6171913	○		M6						
	ø40	M14×1	VPF40W6171913	○								
	ø50	M14×1	VPF50W6171913	○								

Vacuum Pad Multi-bellows Type

Optional items (○ : Available)

7 Pad surface treatment (Suction mark-free)

Pad dia. (mm)	7 Surface treatment code			Connection config. code
	-DL DLC coating	-ER Reformed surface	-FG Fluoro-coating (S) (YS2, YS4)	
ø6	—	○	—	TB
ø8	—	○	○	
ø10	○	○	○	M4
ø20	○	○	○	
ø30	—	○	○	M6
ø40	—	○	○	
ø50	—	○	○	
Material	S, F	N, NE	S, YS2, YS4	

*For Extra soft silicone pads, dia. 10 mm can be selected only when Fluoro-coating treatment is selected.

Characteristics of surface treatment ▶ P.370

9 Dust Catcher: -DC

Optional	Connection config. code	-S3 spec.
Dust Catcher (-DC)	TB	○
Holder type	M4	○
	M6	○
VPSC		
VPC		
VPD		
VPF		

*VPSC holder is available only for configuration code: TB.

Characteristics of Dust Catcher ▶ P.371

10 Fall Prevention Valve: -ECV

Optional	Connection config. code	Model code
Fall Prevention Valve (-ECV)	M4	ECVM4-FM4
	TB	ECVM5-FM5(*)
	M6	ECVM6-FM6

*Limited to M5 threads of VPME and VPE holders.

Characteristics of Fall Prevention Valve ▶ P.722

11 Swivel Joint: -FH, -FHH, -CFH

Optional	Swivel angle	Connection config. code	Model code
Ball Swivel Joint (-FH) (-FHH) 	30° (-FH)	M4	FH10
		M6	FH20
	15° (-FHH)	M4	FH10-15
		M6	FH20-15

Characteristics of Ball Swivel Joint ▶ P.724

Optional	Connection config. code	-S3 spec.	Model code (*)
Flexible Swivel Joint (-CFH) 	M4	○	CFHM4-FM4
	TB	○	CFHM5-FM5(*)
	M6	○	CFHM6-FM6

*1. When ordering a Flexible Swivel Joint alone, please enter "-S3" at the end of the model code for -S3 specification.

*2. Limited to M5 threads of VPME and VPE holders.

Characteristics of Flexible Swivel Joint ▶ P.725


12 Filter: -F15, -F30

Optional	Filter area	Connection config. code	Model code
Pad Direct Mounting Filter (-F15) (-F30) 	1.7cm ² (-F15)	M4	VFF15-M4
		M6	VFF15-M6
	7cm ² (-F30)	M6	VFF30-M6


Characteristics of Filter ▶ P.726

See the page 560 for the model designation including optional items.


Replacement parts (○: -S3 spec. is available)




Pad screw Model code	○ -S3 spec	Applicable pad dia. (mm)	Connection config. code
VPM46-6	○	ø10	M4
VPM610-8	○	ø20	
VPM612-10	○	ø30	M6
VPM610-15	○	ø40, ø50	



Plain washer Model code	Applicable pad dia. (mm)	Connection config. code
HW8.4×15.5×1.6	ø20, ø30	
HW8.5×22×1.6	ø40, ø50	M6




Pad support Model code	Applicable pad dia. (mm)	Connection config. code
VPW40	ø40	
VPW50	ø50	M6




Gasket Model code	Applicable pad dia. (mm)	Connection config. code
VPFG10	ø10 to ø50	M4 M6

Rearrangement parts (○: -S3 spec. is available)




Model code of Adapter for pad connection type conversion	○ -S3 spec	Applicable pad dia. (mm)	Connection config. code Before → After
FVPLT8-M4	○	ø6, ø8	T8 → M4
FVPLT8-M6	○		M6

- *1. These adapters are used to mount 6 to 8 mm dia. Multi-bellows pads on a holder with M4 or M6 configuration code.
- *2. Gasket for adapter is equipped with an Adapter.




Model code of Adapter for pad connection type conversion	○ -S3 spec	Applicable pad dia. (mm)	Connection config. code Before → After
FVPL-FM4-M6	○	ø10	M4 → M6

- *1. This adapter is used to mount a pad & screw set with M4 configuration code on a pad holder with M6 configuration code.
- *2. Gasket for adapter is equipped with an Adapter.



Pad screw Model code	○ -S3 spec	Applicable pad dia. (mm)
VPM56-7	○	ø10
VPM510-8	○	ø20
VPM512-9	○	ø30
VPM510-13	○	ø40, ø50

1. PISCO's Vacuum pad series consists of the combination of vacuum pads and holders.




2. Vacuum pad and pad holder have a specific connection type depending on the size and shape.

Pad connection type	Insert type (Direct connection)		Mount type (Direct connection)		Screw type (Connection with screw)	
Connection configuration code	H3		T4 T8 T15 T40 (Exclusive to soft type & soft bellows type vacuum pads) PB8 PB15 (Exclusive to Vacuum pad for packaging bag) E10 E20 (Exclusive to Oval type vacuum pad)	M4 M6 M10 M20 G1 G2 G3 G4		

*As shown in above drawings, Vacuum pad and pad holder are connected with a screw or a rim.

3. Any Vacuum pad and pad holder can be connected, as long as their connection configuration codes are same.



If you have purchased a pad and holder set but want to install a different pad or replace the holder with a different one...
→Please check the connection configuration code of your pad or pad holder and select the one that matches the configuration code.

4. Please refer to the below chart for the "Connection Configuration Code". *Configuration codes are also listed on the page of model code list for each product.

Connection configuration code list (Holder)

Common holder

	Fixed type		Mini	Slim	Spring type		No cover	Low dust emission
	Mini	Standard			Standard			
Code	VPMA	VPA	VMC	VPSC	VPC	VPOC	VPLFC	
Type								
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	H3 T8	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPMB	VPB	VPMD	—	VPD	VPOD	VPLFD	
Type				—				
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	—	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPME	VPE	—	—	VPF	*Holders with configuration code: G1 to G4 can be connected to VPE holders.		
Type			—	—		 VPE holder (Male thread: G1, G2, G3, and G4)		
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 T15 T40	—	—	H3 T8 M4 M6			

Common holder (Lightweight/Low profile)

	Top port		Side port	Dual side port
	Code	VPHC		
Type				
Configuration code	T15 T40 M4 M6	T15 T40 M4 M6	T15 T40 M4 M6	T15 T40 M4 M6
Code	—	VPHE	VPHEW	—
Type	—			—
Configuration code	—	T15 T40 M4 M6	T15 T40 M4 M6	—

Special holder *Pads of other shapes cannot be installed.

	Top port		Side port
	Code	VPA	
Type			
Configuration code	E10 E20	E10 E20	E10 E20
Code	VPA	VPE	—
Type			—
Configuration code	PB8 PB15	PB8 PB15	—


Connection configuration code list (Pad) (○: Available)

Pad type or application	Standard														Pad type or application
	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Pat Large suction flow type	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	
Code	R	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	E
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

Some combinations are possible by using a conversion screw adapter.

H3, T4 and T8 can be converted to M4 or M6. M4 to M6 conversion is also available. For details, please see "Rearrangement parts" of each pad type.

Model Designation (Example)



(1) Vacuum Pad

(2) Pad size (3) Pad type (6) Connection configuration code *Required for Pad & screw set only. (○: Available)

Pad type or application	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Flat (Large suction flow type)	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	Pad type or application
Code	RM	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	Code
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	2x4
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	3.5x7
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x10
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x10
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x10
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x20
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x30
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x30
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x30
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x20
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x30
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

(4) Pad material (○: Available)

Code	N	S	U	F	SE	NE	G	HN	EP	FS	NH	YS2	YS4	MSF3	MSF5	MSS3	MSS5
Rubber material	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	Food Sanit. Act compliant NBR	HNBR	EPDM	Fluoro-silicone	Oil proof NBR	Extra soft silicone	Iron powder type	SUS powder type	Metal detectable silicone		
Pad color	Black	Clear white	Dark blue	Gray	Black	Black	Light gray	Black	Black	Red-orange	Black	Pink	Blue	Reddish-brown	Dark-green	Brown	Green
Material code marking ¹⁾	None	None	None	None	SE	NE	None	HN	EP	None	None	None	None	SF	SF	SS	SS
Standard	General	Deep	Small	Soft	Soft bellows	Skidproof	Bellows	Multi-bellows	For packaging bag	Metal Detectable	Ribs (Bellows with bumps)	Ultrathin	Flat	Flat large suction flow	Oval		
Code	R	A	RM	L	LB	K	B	W	PB	BE	BD	P	F	FH	E		

● Mark-free type (Pad type code: Q)

Code	K	M	KE
Resin material	PEEK	POM	Conductive PEEK
Pad color	Beige	White	Black

● Sponge type (Pad type code: S)

Code	S	C
Rubber material	Silicone	Chloroprene
Pad color	Dark-orange	Black

*1. For vacuum pads in black color (SE: Conductive silicone, NE: Conductive NBR (low resistance), HN: HNBR and EP: EPDM) and Vacuum pad Metal Detectable type, the pad material code is marked on the top or the side of the vacuum pad for material identification. (The marking on black vacuum pads has started since Oct. 2023 gradually.)



*2. Some materials are not available depending on pad size. Please see the catalog for details.

*3. Pad color of pads for Packaging bag. Lip hardness 20° (Pink) Lip hardness 40° (Blue)

*4. The Conductive Silicone rubber (SE) is a silicon rubber capable of releasing static electricity. (Volume resistance: More than 200 Ω·cm and 10⁵ Ω·cm or less)

*5. Nitrile rubber (N), Conductive NBR (Low resistance, Volume resistance: 200Ω·cm or less) (NE), Food Sanitation Act-compliant NBR (G), Oil proof NBR (NH) are not suitable for use with ozone environment.

*6. Extra soft silicone (YS2/YS4), Metal detectable silicone and Silicone for Packaging bag are compliant with Food Sanitation Act and FDA.

*7. Volume resistance of Conductive PEEK (KE) is 10⁵ to 10⁶ Ω·cm.

(5) Surface treatment (Optional) (○: Available)

Code			No code	-NF	-SF	-DL	-ER	-FG
Surface treatment			None	Fiber surface		DLC. coating	Reformed surface	Fluoro-coating
				Nylon fiber	Silk fiber			
			—					
Applicable pad material			—	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F) Conductive silicone (SE)	Nitrile (N) Conductive NBR (NE)	Silicone (S) Conductive silicone (SE) Extra soft silicone (YS2, YS4)
Pad type	Standard	General	R	—	—	○	○	○
		Deep	A	—	—	—	○	○
		Small	RM	—	—	—	—	○
	Soft		L	—	○	○	○	○
	Soft bellows		LB	—	○	○	○	○
	Skidproof		K	—	—	—	—	—
	Bellows		B	—	○	○	○	○
	Multi-bellows		W	—	—	○	○	○
	For packaging bag		PB	—	—	—	—	○
	Metal Detectable		BE,BD	—	—	—	—	—
	Ultrathin		P	—	—	—	○	○
	Flat		F	—	—	—	○	○
	Flat large suction flow		FH	—	—	—	○	○
	Mark-free		Q	—	—	—	—	—
Sponge		S	—	—	—	—	—	
Oval		E	—	—	—	○	○	

*Some surface treatments are not available depending on pad size.

Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free.


(6) Connection configuration code (Required for Pad & screw set only.) Please refer to the Pad size and type list on the 374 page.

Code	No code	-M4	-M6	-M10	-M20	-M5 ^(*)
Connection config. code	—	M4	M6	M10	M20	—
Thread size	Pad rubber only	M4×0.7	M6×1	M10×1.5	M20×2	M5×0.8

*M5 thread is used for mounting on non-PISCO holders. Contact us for the price of screw set.

(7) Mark-free resin attachment material (Bellows type only) (Optional)

Code	No code	-QK	-QM	-QKE
Resin material	—	PEEK	POM	Conductive PEEK (Volume resistance: 10 ⁵ to 10 ⁶ Ω·cm)
	—			



*1. Selectable for Bellows type pad dia. 10 to 30 mm.

*2. Resin attachment cannot be installed when selecting surface treatment.

*3. Resin attachment cannot be installed when selecting Extra soft silicone for pad material.

(8) -S3 spec. (Required for Pad & screw set only) (Optional)

Code	No code	-S3
Metal material	Standard	No copper-based metallic materials used in flow paths

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code" (M4, M6 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).



Multi-bellows series,
Pad rubber alone

○: Available as standard item

④ Pad rubber material

Model code	N	S	YS2	YS4	U	F	NE	G	HN	EP	Connection config. code
	Nitrile	Silicone	Extra soft silicone ⁽¹⁾ Hardness 20°	Hardness 40°	Urethane	Fluoro	Conductive NBR Low resistance	Food Sant. Act compliant NBR	HNBR	EPDM	
VP6W④⑤	○	○	—	—	—	○	○	○	○	○	T8
VP8W④⑤	○	○	—	—	—	○	○	○	○	○	M4②
VP10W④⑤	○	○	(*)3	(*)3	○	○	○	○	○	○	M6②
VP20W④⑤	○	○	○	○	○	○	○	○	○	○	M8②
VP30W④⑤	○	○	○	○	○	○	○	○	○	○	
VP40W④⑤	○	○	○	○	○	○	○	○	○	○	
VP50W④⑤	○	○	○	○	○	○	○	○	○	○	



Multi-bellows series,
Pad & screw set


P.560

○: Available as standard item												Connection config. code
Model code	④ Pad rubber material										⑧	
	N	S	YS2	YS4	U	F	NE	G	HN	EP	-S3	
	Nitrile	Silicone	Extra soft silicone ^(*) Hardness 20°	Hardness 40°	Urethane	Fluoro	Conductive NBR (Low resistance)	Food Sant. Act compliant NBR	HNBR	EPDM	-S3 spec.	
VP10W④⑤-M4⑧	○	○	(*)3	(*)3	○	○	○	○	○	○	○	M4
VP20W④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP30W④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP40W④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP50W④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	M6

P.586		P.586		P.586		P.586	
Packaging bag 3 cnvls Lip hardness 20° Pad rubber alone		Packaging bag 3 cnvls Lip hardness 40° Pad rubber alone		Packaging bag 5 cnvls Lip hardness 20° Pad rubber alone		Packaging bag 5 cnvls Lip hardness 40° Pad rubber alone	
Model code	Connection config. code	Model code	Connection config. code	Model code	Connection config. code	Model code	Connection config. code
VP20PBS23⑤	PB8	VP20PBS43⑤	PB8	VP20PBS25⑤	PB8	VP20PBS45⑤	PB8
VP25PBS23⑤		VP25PBS43⑤		VP25PBS25⑤		VP25PBS45⑤	
VP30PBS23⑤		VP30PBS43⑤		VP30PBS25⑤		VP30PBS45⑤	
VP40PBS23⑤	PB15	VP40PBS43⑤	PB15	VP40PBS25⑤	PB15	VP40PBS45⑤	PB15
VP50PBS23⑤		VP50PBS43⑤		VP50PBS25⑤		VP50PBS45⑤	

P.586		P.586		P.586		P.586	
Oversuction preventing adapter Spherical type (exclusive to packaging bag pad)		Oversuction preventing adapter Spherical type with stainless steel mesh (exclusive to packaging bag pad)		Oversuction preventing adapter Plane type (exclusive to packaging bag pad)		Oversuction preventing adapter Plane type with stainless steel mesh (exclusive to packaging bag pad)	
Model code	Pad dia. (mm)	Model code	Pad dia. (mm)	Model code	Pad dia. (mm)	Model code	Pad dia. (mm)
VP20PB-FS	ø20	VP20PB-MS	ø20	VP20PB-FF	ø20	VP20PB-MF	ø20
VP25PB-FS	ø25	VP25PB-MS	ø25	VP25PB-FF	ø25	VP25PB-MF	ø25
VP30PB-FS	ø30	VP30PB-MS	ø30	VP30PB-FF	ø30	VP30PB-MF	ø30
VP40PB-FS	ø40	VP40PB-MS	ø40	VP40PB-FF	ø40	VP40PB-MF	ø40
VP50PB-FS	ø50	VP50PB-MS	ø50	VP50PB-FF	ø50	VP50PB-MF	ø50

■ Available pad size and material for surface treatment (Multi-bellows series)

Pad dia. (mm)	⑤ Surface treatment code		
	-DL	-ER	-FG
	DLC. Reformed coating	Reformed surface	Fluoro-coating (S) (YS2, YS4)
ø6	—	○	—
ø8	—	○	—
ø10	○	○	—
ø20	○	○	○
ø30	—	○	○
ø40	—	○	○
ø50	—	○	○
Material	S, F	N, NE	S, YS2, YS4

*3. Fluoro-coating of Extra soft silicone (YS2, YS4)
For Extra soft silicone pads, dia. 10 mm can be selected only when Fluoro-coating treatment is selected.

Model code	YS2	YS4	⑧	Connection config. code
	Extra soft silicone ^(*) Hardness 20°	Hardness 40°	-S3 spec.	
VP10W④-FG	○	○	—	M4②
Pad & screw set				
VP10W④-FG-M4⑧	○	○	○	M4

■ Available pad size and material for surface treatment (For Packaging bag)

Pad dia. (mm)	⑤ Surface treatment code	
	-FG	
	Fluoro-coating (3 cnvls)	(5 cnvls)
ø20	○	○
ø25	○	○
ø30	○	○
ø40	○	○
ø50	○	○

Holders with the same "connection configuration code" (M4, M6 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

	New				P.590						
Metal Detectable series (Bellows with bumps and ribs), Pad rubber alone											
Model code	○: Available as standard item				Connection config. code	Model code	○: Available as standard item				Connection config. code
	④ Pad rubber material						④ Pad rubber material				
	MSF3	MSF5	MSS3	MSS5			MSF3	MSF5	MSS3	MSS5	
	Metal detectable silicone						Metal detectable silicone				
	Iron powder type SUS powder type						Iron powder type SUS powder type				
Hardness 30°		Hardness 50°		Hardness 30°		Hardness 50°		Hardness 30°		Hardness 50°	
VP10BE④	○	○	○	○	M4①	VP10BE④-M4⑧	○	○	○	○	M4
VP15BE④	○	○	○	○	M4①	VP15BE④-M4⑧	○	○	○	○	M4
VP20BE④	○	○	○	○	M6①	VP20BE④-M6⑧	○	○	○	○	M6



New

P.590

Metal Detectable series (Bellows with bumps and no ribs), Pad rubber alone

Model code	○: Available as standard item				Connection config. code
	④ Pad rubber material				
	MSF3	MSF5	MSS3	MSS5	
	Metal detectable silicone				
	Iron powder type SUS powder type				
	Hardness 30°	Hardness 50°	Hardness 30°	Hardness 50°	
VP10BD④	○	○	○	○	M4①
VP15BD④	○	○	○	○	M6①
VP20BD④	○	○	○	○	



New

P.590

Metal Detectable series (Bellows with bumps and no ribs), Pad & screw set

Model code	○: Available as standard item				Connection config. code
	④ Pad rubber material				
	MSF3	MSF5	MSS3	MSS5	
	Metal detectable silicone				
	Iron powder type SUS powder type				
	Hardness 30°	Hardness 50°	Hardness 30°	Hardness 50°	
VP10BD④-M4⑧	○	○	○	○	M4
VP15BD④-M4⑧	○	○	○	○	M6
VP20BD④-M6⑧	○	○	○	○	

Ultrathin series, Pad rubber alone											P.604	
Model code	○: Available as standard item										Connection config. code	
	④ Pad rubber material											
	N	S	U	F	FS	NE						
	Nitrile	Silicone	Urethane	Fluoro	Fluoro silicone	Conductive NBR Low resistance						
VP8P④⑤	○	○	○	○	○	○					T8	
VP10P④⑤	○	○	○	○	○	○						
VP15P④⑤	○	○	○	○	○	○						
VP20P④⑤	○	○	○	○	○	○						

Notes
*A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.

CAD data is available at PISCO website.

Packaging specifications
1 pc./bag

Options
⑤: Surface treatment
⑧: -S3 ⇒ -S3 spec.

■ Available pad size and material for surface treatment (Ultrathin series)

Pad dia. (mm)	⑤ Surface treatment code		
	-DL	-ER	-FG
	DLC. Reformed coating	Reformed surface	Fluoro-coating
ø8	○	○	○
ø10	○	○	○
ø15	○	○	○
ø20	○	○	○
Material	S, F	N, NE	S

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code" (M4, M6 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Flat series, Pad rubber alone										Flat series, Pad & screw set									
○: Available as standard item										○: Available as standard item									
Model code	④ Pad rubber material						Connection config. code	Model code	④ Pad rubber material						Connection config. code				
	N	S	U	F	SE	NE			N	S	U	F	SE	NE		-S3			
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.			
VP10F④⑤	○	○	○	○	○	○	M4⑧⑨	VP10F④⑤-M4⑧	○	○	○	○	○	○	○	M4			
VP15F④⑤	○	○	○	○	○	○		VP15F④⑤-M4⑧	○	○	○	○	○	○	○				
VP20F④⑤	○	○	○	○	○	○	M6⑧⑨	VP20F④⑤-M6⑧	○	○	○	○	○	○	○	M6			
VP25F④⑤	○	○	○	○	○	○		VP25F④⑤-M6⑧	○	○	○	○	○	○	○				
VP30F④⑤	○	○	○	○	○	○		VP30F④⑤-M6⑧	○	○	○	○	○	○	○				

 Flat large suction flow series, Pad rubber alone							 Flat large suction flow series, Pad & screw set							
○: Available as standard item							○: Available as standard item							
Model code	④ Pad rubber material					Connection config. code	Model code	④ Pad rubber material					Connection config. code	
	N	S	F	SE	NE			N	S	F	SE	NE		⑤
	Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.
VP10FH④⑤	○	○	○	○	○	M4⑧	VP10FH④⑤-M4⑧	○	○	○	○	○	○	M4
VP15FH④⑤	○	○	○	○	○		VP15FH④⑤-M4⑧	○	○	○	○	○	○	
VP20FH④⑤	○	○	○	○	○	M6⑧	VP20FH④⑤-M6⑧	○	○	○	○	○	○	M6
VP25FH④⑤	○	○	○	○	○		VP25FH④⑤-M6⑧	○	○	○	○	○	○	
VP30FH④⑤	○	○	○	○	○		VP30FH④⑤-M6⑧	○	○	○	○	○	○	

									
Mark-free series, Resin pad alone				Mark-free series, with Flexible Swing Joint					
Model code	○: Available as standard item			Connection config. code	Model code	○: Available as standard item			Connection config. code
	④ Pad rubber material					④ Pad rubber material			
	K	M	KE			K	M	KE	
	PEEK	POM	Conductive PEEK			PEEK	POM	Conductive PEEK	-S3 spec.
VP10Q④	○	○	○	M4①	VP10Q④-M4⑧	○	○	○	M4
VP20Q④	○	○	○	M6①	VP20Q④-M6⑧	○	○	○	M6
VP30Q④	○	○	○		VP30Q④-M6⑧	○	○	○	



Sponge series,
Pad rubber alone


P656



Sponge series,
Pad & screw set


P656

Model code	○: Available as standard item		Connection config. code	Model code	○: Available as standard item			Connection config. code
	④ Pad rubber material				④ Pad rubber material			
	C	S			C	S	-S3	
	Chloroprene	Silicone			Chloroprene	Silicone	-S3 spec.	
VP10S④	○	○	M8④①	VP10S④-M6⑧	○	○	○	M8
VP15S④	○	○		VP15S④-M6⑧	○	○	○	
VP20S④	○	○		VP20S④-M6⑧	○	○	○	
VP25S④	○	○		VP25S④-M6⑧	○	○	○	
VP30S④	○	○		VP30S④-M6⑧	○	○	○	
VP35S④	○	○	M10④①	VP35S④-M6⑧	○	○	○	M10
VP50S④	○	○		VP50S④-M6⑧	○	○	○	
VP70S④	○	○		VP70S④-M10	○	○	(*)	
VP100S④	○	○		VP100S④-M10	○	○	(*)	

- Notes**
- *1. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- *2. A Flexible Swing Joint is required to mount on the holder. If you do not have a Flexible Swing Joint, please select from the Mark-free series, with Flexible Swing Joint set.
- *3. For Pad & screw set of Sponge series 70 mm and 100 mm pad dia., the standard spec. is equivalent to "-S3" spec.

CAD data is available at PISCO website.

Packaging specifications 1 pc./bag

Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Holders with the same "connection configuration code" (E10, E20 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Oval series, Pad rubber alone												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP				
VP2×4E④⑤	○	○	○	○	○	○	○	○				
VP3.5×7E④⑤	○	○	○	○	○	○	○	○				
VP4×10E④⑤	○	○	○	○	○	○	○	○				
VP4×20E④⑤	○	○	○	○	○	○	○	○				
VP4×30E④⑤	○	○	○	○	○	○	○	○				
VP5×10E④⑤	○	○	○	○	○	○	○	○				
VP5×20E④⑤	○	○	○	○	○	○	○	○				
VP5×30E④⑤	○	○	○	○	○	○	○	○				
VP6×10E④⑤	○	○	○	○	○	○	○	○				
VP6×20E④⑤	○	○	○	○	○	○	○	○				
VP6×30E④⑤	○	○	○	○	○	○	○	○				
VP8×20E④⑤	○	○	○	○	○	○	○	○				
VP8×30E④⑤	○	○	○	○	○	○	○	○				

Oval series, Pad & screw set												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP	-S3			
VP2×4E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP3.5×7E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			


- Notes**
- *A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- CAD data is available at PISCO website.
- Packaging specifications 1 pc./bag
- Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Available pad size and material for surface treatment (Oval series)


Pad dia. (mm)	⑤ Surface treatment code		
	-DL	-ER	-FG
2×4	○	○	○
3.5×7	○	○	○
4×10	○	○	○
4×20	○	○	○
4×30	○	○	○
5×10	○	○	○
5×20	○	○	○
5×30	○	○	○
6×10	○	○	○
6×20	○	○	○
6×30	○	○	○
8×20	○	○	○
8×30	○	○	○
Material	S, F, SE	N, NE	S, SE

Vacuum Pad Configuration


Pad dia. : $\phi 0.7, \phi 1, \phi 1.5, \phi 2, \phi 3, \phi 4$ mm





Pad dia. : $\phi 1, \phi 2, \phi 3, \phi 4$ mm



Pad dia. : $\phi 6, \phi 8, \phi 10, \phi 15, \phi 20$ mm






Pad dia. : $\phi 4, \phi 6, \phi 8, \phi 10, \phi 15$ mm






Vacuum Pad Configuration




Pad dia. : $\varnothing 10$, $\varnothing 15$, $\varnothing 20$, $\varnothing 25$, $\varnothing 30$, $\varnothing 35$, $\varnothing 40$, $\varnothing 50$ mm



Pad dia. : $\varnothing 60$, $\varnothing 70$, $\varnothing 80$, $\varnothing 100$ mm





Pad dia. : $\varnothing 150$, $\varnothing 200$ mm





Vacuum Pad Configuration



Pad dia. : $\varnothing 4$, $\varnothing 6$, $\varnothing 8$, $\varnothing 10$, $\varnothing 15$ mm (Exclusive to Soft and Soft Bellows type)





Pad dia. : $\varnothing 20$, $\varnothing 30$, $\varnothing 40$ mm (Exclusive to Soft and Soft Bellows type)





Pad dia. : $\varnothing 20$, $\varnothing 25$ mm (Exclusive to Vacuum pad for packaging bag)



Pad dia. : $\varnothing 30$, $\varnothing 40$, $\varnothing 50$ mm (Exclusive to Vacuum pad for packaging bag)



Pad size : 2×4, 3.5×7, 4 to 6×10 mm (Exclusive to Oval type)



Pad size : 4 to 8×20 mm, 4 to 8×30 mm (Exclusive to Oval type)

