

Vacuum Pad Skidproof Type

Vacuum pad for oil-coated components, such as press parts.

⚠ Safety instructions for this product

Safety instructions, Common safety instructions for each product category and Detailed safety instructions for each product are in the end of this catalog and our website.

Model Designation (Example)

VP	C	10	-6	K	NH	-6J	-DC	-ECV	-FH	-F15	(12)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
							Optional	Optional	Optional	Optional	Optional

(1) Vacuum Pad

(2) Holder type

Holder type	Fixed type		Spring type				Holder type	Lightweight	Low profile
	Mini	Standard	Mini	Standard	No cover	Low dust emission		Spring type	Direct mount
Code	Top port	MA	A	MC	C	OC	LFC	HC	-
	Side port	MB	B	MD	D	OD	LFD	HD	HE
	Direct mount	-	E	-	F	-	-	HDW	HEW
	Connection config. code	M4 M6	M4 M6	M4 M6	M4 M6	M4 M6	M4 M6	M4 M6	M4 M6

(3) Pad dia.

Code	10	20	30	40	50
Pad dia. (mm)	ø10	ø20	ø30	ø40	ø50
Connection config. code	M4			M6	

(4) Stroke (No code entry for Holder type: MA, A, MB, B, E, F, HE and HEW)

Code	-2	-4	-5	-6	-10	-15	-20	-25	-30	-40	-50	Connection config. code
Stroke (mm)	2	4	5	6	10	15	20	25	30	40	50	
Spring type holder code	VPMC											
	VPC											
	VPOC											
	VPLFC											
	VPMD											
	VPD											
	VPOD											
	VPLFD											
	VPHC											
	VPHD											
	VPHDW											

(5) Pad type K: Skidproof

(6) Pad material

Code	NH	S	U	F	NE
Rubber material	Oil-proof NBR	Silicone	Urethane	Fluoro	Conductive NBR (Low resistance)

*Oil-proof NBR (NH) and Conductive NBR (Low resistance type, Volume resistance: 2000 Ω·cm or less) (NE) are not suitable for use with ozone environment.

(7) Vacuum port size and joint type (No code entry for Holder type: F) (○: Available)

Type	Push-in fitting								Barb fitting				Female thread		
Code	mm size (mm)				inch size (inch)				mm size (mm)			inch size (inch)	Metric thread		
	-180J	-2J	-3J	-4J	-6J	-1/8J	-5/32J	-1/4J	-3B	-4B*	-6B	-1/4B	-M5	-M6	
Tube O.D.	ø1.8	ø2	ø3	ø4	ø6	ø1/8	ø5/32	ø1/4							
Tube I.D.									ø2	ø2.5	ø4	Polyurethane tube ø0.163 Nylon tube ø0.180			
Thread size														M5×0.8	M6×1
Holder type	VPMA			○	○		○	○	○	○	○			○	
	VPA			○	○		○	○	○	○	○			○	
	VPMB	○	○			○	○	○	○	○	○		○		
	VPB			○	○	○	○	○	○	○	○			○	
	VPMC	○	○						○	○	○				
	VPC			○	○	○	○	○	○	○	○			○	
	VPOC			○	○	○	○	○	○	○	○			○	
	VPLFC			○	○	○	○	○	○	○	○			○	
	VPMD	○	○			○	○	○	○	○	○		○	○	
	VPD			○	○	○	○	○	○	○	○			○	
	VPOD			○	○	○	○	○	○	○	○			○	
	VPLFD			○	○	○	○	○	○	○	○			○	
	VPHC	○	○			○	○	○	○	○	○		○		
	VPHD	○	○			○	○	○	○	○	○		○		
	VPHDW	○	○			○	○	○	○	○	○		○		
VPHE	○	○			○	○	○	○	○	○		○			
VPHEW	○	○			○	○	○	○	○	○		○			

Push-in fitting Barb fitting Female thread

*The barb fitting of 5/32" size is common with 4 mm size. Please order with the code: -4B.
*Available port size varies depending on pad dia. See model code lists on the following pages.

Type	Male thread														Female thread		Direct mount	
	Metric thread				Taper pipe thread				Parallel pipe thread				NPT thread					Metric thread
Code	-M8	-M10	-M12	-M14	-R1	-R2	-R3	-R4	-G1	-G2	-G3	-G4	-N1	-N2	-N3	-N4	-FM5	-FM8
Thread size	M8×1.25	M10×1.5	M12×1.75	M14×2	R1/8	R1/4	R3/8	R1/2	G1/8	G1/4	G3/8	G1/2	NPT1/8	NPT1/4	NPT3/8	NPT1/2	M5×0.8	M8×1.25
Holder type	VPE																	



(8) Dust Catcher (Holder type: C, D and F only) Optional

Code	No code	-DC
Dust Catcher	None	Installed

*Note that the holder stroke becomes shorter when a dust catcher is installed. Please visit our website for details.



(8) Spring load (Holder type: LFC only)

Code	No code	-SF1/4
Load	Standard load	Low load (1/4 of standard load)

**"-SF1/4" is not selectable when 2 mm stroke is selected.

(9) Fall Prevention Valve Optional

Code	No code	-ECV
Fall Prevention Valve	None	Installed


*-S3 spec. is not selectable when Fall Prevention Valve is selected.



(10) Swivel Joint for vacuum pad Optional

Code	No code	-FH	-FHH	-CFH
Option	None	Ball Swivel Joint (Swivel angle: 30°)	Ball Swivel Joint (Swivel angle: 15°)	Flexible Swing Joint (Swing angle: 8°)

*-S3 spec. is not selectable when Ball Swivel Joint is selected.



(11) Filter Optional

Code	No code	-F15	-F30
Filter	None	Installed (Filter area 1.7 cm ²)	Installed (Filter area 7 cm ²)
Applicable config. code	—	M4, M6	M6



*1. -S3 spec. is not selectable when Filter is selected.
*2. "-F30" is recommended when much dust is expected at sucking work pieces.


(12) -S3 spec. Optional

Code	No code	-S3
Metal material	Standard	No copper-based metallic materials used in flow paths.
Seal rubber material	Standard	HNBR or FKM
Release ring color	Black	Dark blue

*1. -S3 spec. is not available for the following fittings and holders:
Push-in fitting with dia. size of 1.8, 2, 3 mm and inch sizes except dia. 1/8" (some) and 5/32".
Barb fitting with dia. of 1/4".
Pad holder with stroke length 10 mm or longer (except for VPHC holders).
VPLFC and VPLFD holders.
*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."


Characteristics

Optimal for transporting oil-coated components, such as press parts.



The work-piece skids less because of the groove.

Greasy and slippery work-piece



Pad dia. 5 types
ø10 to ø50mm
Pad material 5 types

Silicone (S) is Food-safe Act compliant.


(Holder is not compliant. Vacuum pad complies only at work-piece contact area.)

*See page 6 for the details of the Food-safe Act.

Wide variations of Pad holders.

The following combinations of holder and pad rubber are also available although it is not listed on the model code list from the next page. Contact us for the details.

- Lightweight VPHC holder that is made of resin and aluminum.
- Lightweight VPHD and VPHDW holders with spring type without cover.
- VPHE and VPHEW holders with reduced height.
- VPHDW and VPHEW holders with dual side vacuum ports, suitable for piping connection of multiple vacuum pads.



Low dust emission holders (VPLFC, VPLFD) with low noise and less wear from sliding are available to prevent dust generation.

VPLFC holder with top port has a separate shaft on the pad side and the vacuum port side, so there is no effect on the stroke caused by the tension of the tube. Low load type is also available to suppress impact when contacting the work-piece.

Wide variations of fixed type direct mount holder (VPE) for various thread sizes.

Metric male threads, metric female threads, taper pipe threads, parallel pipe threads and NPT threads are available.

*Only a part of the combinations are shown on the model code list from the next page onward. Contact us for the details.

Holder with dust catcher (Optional)

Collects wear debris generated by sliding spring type holders.

Low-cost, simple holder with receiver tray added.

Applicable to VPC, VPD and VPF holders.



Accessories (Optional)

Fall Prevention Valve, Swivel (Ball Swivel Joint, Flexible Swing Joint) and Filter options are available.

-S3 spec. (Optional)

No copper-based metallic materials used in flow paths.

The sealing rubber material of the fitting is HNBR or FKM, with good ozone resistance.

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code
Fixed type, Top port, Push-in fitting, Mini VPMA	ø10	ø3	VPMA10K[6]-3J	—	M4	ø10	ø5/32	VPMA10K[6]-4/32J12	○	M4
		ø4	VPMA10K[6]-4J12	○			ø5/32	VPMA20K[6]-4/32J12	○	
	ø20	ø4	VPMA20K[6]-4J12	○	M6	ø20	ø5/32	VPMA30K[6]-4/32J12	○	M6
		ø6	VPMA20K[6]-6J12	○			ø5/32	VPMA40K[6]-4/32J12	○	
	ø30	ø4	VPMA30K[6]-4J12	○		ø30	ø5/32	VPMA50K[6]-4/32J12	○	
		ø6	VPMA30K[6]-6J12	○			ø5/32	VPMA50K[6]-5/32J12	○	
	ø40	ø4	VPMA40K[6]-4J12	○		ø40	ø5/32	VPMA50K[6]-4/32J12	○	
		ø6	VPMA40K[6]-6J12	○		ø50	ø5/32	VPMA50K[6]-4/32J12	○	
	ø50	ø4	VPMA50K[6]-4J12	○			ø5/32	VPMA50K[6]-4/32J12	○	
		ø6	VPMA50K[6]-6J12	○			ø5/32	VPMA50K[6]-4/32J12	○	

Notes
*Barb fitting type holders are also available. Contact us for the details.

Options
12: -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items
⇒ P.525

Fall Prevention Valve

Swivel Joint for vacuum pad

Filter

CAD data is available at PISCO website.

Packaging specifications
1 pc./bag

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 -S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	12-S3 -S3 spec.	Connection config. code
Fixed type, Top port, Push-in fitting, Standard VPA 	ø10	ø6	VPA10K[6]-6J12	○	M4	ø10	ø1/4	VPA10K[6]-1/4J	—	M4
		ø3	VPA20K[6]-3J	—			ø1/8	VPA20K[6]-1/8J	—	
		ø4	VPA20K[6]-4J12	○			ø5/32	VPA20K[6]-5/32J12	○	
	ø20	ø6	VPA20K[6]-6J12	○		ø1/4	VPA20K[6]-1/4J	—		
		ø3	VPA30K[6]-3J	—		ø1/8	VPA30K[6]-1/8J	—		
		ø4	VPA30K[6]-4J12	○		ø5/32	VPA30K[6]-5/32J12	○		
	ø30	ø6	VPA30K[6]-6J12	○		ø1/4	VPA30K[6]-1/4J	—		
		ø3	VPA40K[6]-3J	—		ø1/8	VPA40K[6]-1/8J	—		
		ø4	VPA40K[6]-4J12	○		ø5/32	VPA40K[6]-5/32J12	○		
	ø40	ø6	VPA40K[6]-6J12	○		ø1/4	VPA40K[6]-1/4J	—		
		ø3	VPA50K[6]-3J	—		ø1/8	VPA50K[6]-1/8J	—		
		ø4	VPA50K[6]-4J12	○		ø5/32	VPA50K[6]-5/32J12	○		
	ø50	ø6	VPA50K[6]-6J12	○		ø1/4	VPA50K[6]-1/4J	—		
		ø3	VPA50K[6]-3J	—		ø1/8	VPA50K[6]-1/8J	—		
		ø4	VPA50K[6]-4J12	○		ø5/32	VPA50K[6]-5/32J12	○		
	ø6	VPA50K[6]-6J12	○	ø1/4		VPA50K[6]-1/4J	—			

Holder type	Pad dia. (mm)	Male thread size	Model code	12-S3 spec.	Connection config. code
Fixed type, Top port, Female thread, Standard VPA	ø20	M6×1	VPA20K[6]-M612	○	M6
	ø30	M6×1	VPA30K[6]-M612	○	
	ø40	M6×1	VPA40K[6]-M612	○	
	ø50	M6×1	VPA50K[6]-M612	○	

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code
Fixed type, Side port, Push-in fitting, Mini VPMB	ø10	ø3	VPMB10K[6]-3J	—	M4	ø10	ø1/8	VPMB10K[6]-1/8J	—	M4
		ø4	VPMB10K[6]-4J12	○			ø5/32	VPMB10K[6]-5/32J12	○	
		ø6	VPMB10K[6]-6J12	○			ø1/4	VPMB10K[6]-1/4J	—	
	ø20	ø3	VPMB20K[6]-3J	—		ø20	ø1/8	VPMB20K[6]-1/8J	—	
		ø4	VPMB20K[6]-4J12	○			ø5/32	VPMB20K[6]-5/32J12	○	
		ø6	VPMB20K[6]-6J12	○			ø1/4	VPMB20K[6]-1/4J	—	
	ø30	ø3	VPMB30K[6]-3J	—		ø30	ø1/8	VPMB30K[6]-1/8J	—	
		ø4	VPMB30K[6]-4J12	○			ø5/32	VPMB30K[6]-5/32J12	○	
		ø6	VPMB30K[6]-6J12	○			ø1/4	VPMB30K[6]-1/4J	—	
	ø40	ø3	VPMB40K[6]-3J	—	M6	ø40	ø1/8	VPMB40K[6]-1/8J	—	M6
		ø4	VPMB40K[6]-4J12	○			ø5/32	VPMB40K[6]-5/32J12	○	
		ø6	VPMB40K[6]-6J12	○			ø1/4	VPMB40K[6]-1/4J	—	
Fixed type, Side port, Female thread, Mini VPMB	ø10	ø3	VPMB50K[6]-3J	—		ø50	ø1/8	VPMB50K[6]-1/8J	—	
		ø4	VPMB50K[6]-4J12	○			ø5/32	VPMB50K[6]-5/32J12	○	
		ø6	VPMB50K[6]-6J12	○			ø1/4	VPMB50K[6]-1/4J	—	

Notes

*Barb fitting type holders are also selectable. VPMB holders are also available in Push-in fitting type for tube O.D. of 1.8 mm and 2 mm. Contact us for the details.

CAD data is available at PISCO website.

Packaging specifications
1 pc./bag

Options

12: -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items
⇒ P.525

Fall Prevention Valve

Swivel Joint for vacuum pad

Filter

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	12-S3 spec.	Connection config. code
Fixed type, Side port, Push-in fitting, Standard VPB 	ø10	ø3	VPB10K(6)-3J	—	M4	ø10	ø1/8	VPB10K(6)-1/8J	—	M4
		ø4	VPB10K(6)-4J12	○			ø5/32	VPB10K(6)-5/32J12	○	
		ø6	VPB10K(6)-6J12	○			ø1/4	VPB10K(6)-1/4J	—	
	ø20	ø3	VPB20K(6)-3J	—	M6	ø20	ø1/8	VPB20K(6)-1/8J	—	M6
		ø4	VPB20K(6)-4J12	○			ø5/32	VPB20K(6)-5/32J12	○	
		ø6	VPB20K(6)-6J12	○			ø1/4	VPB20K(6)-1/4J	—	
	ø30	ø3	VPB30K(6)-3J	—	M6	ø30	ø1/8	VPB30K(6)-1/8J	—	M6
		ø4	VPB30K(6)-4J12	○			ø5/32	VPB30K(6)-5/32J12	○	
		ø6	VPB30K(6)-6J12	○			ø1/4	VPB30K(6)-1/4J	—	
	ø40	ø3	VPB40K(6)-3J	—	M6	ø40	ø1/8	VPB40K(6)-1/8J	—	M6
		ø4	VPB40K(6)-4J12	○			ø5/32	VPB40K(6)-5/32J12	○	
		ø6	VPB40K(6)-6J12	○			ø1/4	VPB40K(6)-1/4J	—	
	ø50	ø3	VPB50K(6)-3J	—	M6	ø50	ø1/8	VPB50K(6)-1/8J	—	M6
		ø4	VPB50K(6)-4J12	○			ø5/32	VPB50K(6)-5/32J12	○	
		ø6	VPB50K(6)-6J12	○			ø1/4	VPB50K(6)-1/4J	—	

Holder type	Pad dia. (mm)	Male thread size	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	12-S3 spec.	Connection config. code
Fixed type, Side port, Female thread, Standard VPB 	ø10	M6×1	VPB10K(6)-M612	○	M4	ø10	ø1/8	VPMC10-4K(6)-1/8J	—	M4
	ø20	M6×1	VPB20K(6)-M612	○	M6		ø5/32	VPMC10-4K(6)-5/32J12	○	M6
	ø30	M6×1	VPB30K(6)-M612	○			ø1/8	VPMC20-4K(6)-1/8J	—	
	ø40	M6×1	VPB40K(6)-M612	○			ø5/32	VPMC20-4K(6)-5/32J12	○	
	ø50	M6×1	VPB50K(6)-M612	○			ø1/4	VPMC30-4K(6)-1/4J	—	

Holder type	Pad dia. (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Tube O.D. (inch)	Model code	12-S3 spec.	Connection config. code
Spring type, Top port, Push-in fitting, Mini VPMC 	ø10	ø3	VPMC10-4K(6)-3J	—	M4	ø10	ø1/8	VPMC10-4K(6)-1/8J	—	M4
		ø4	VPMC10-4K(6)-4J12	○			ø5/32	VPMC10-4K(6)-5/32J12	○	
		ø6	VPMC10-4K(6)-6J12	○			ø1/4	VPMC10-4K(6)-1/4J	—	
	ø20	ø3	VPMC20-4K(6)-3J	—	M6	ø20	ø1/8	VPMC20-4K(6)-1/8J	—	M6
		ø4	VPMC20-4K(6)-4J12	○			ø5/32	VPMC20-4K(6)-5/32J12	○	
		ø6	VPMC20-4K(6)-6J12	○			ø1/4	VPMC20-4K(6)-1/4J	—	
	ø30	ø3	VPMC30-4K(6)-3J	—	M6	ø30	ø1/8	VPMC30-4K(6)-1/8J	—	M6
		ø4	VPMC30-4K(6)-4J12	○			ø5/32	VPMC30-4K(6)-5/32J12	○	
		ø6	VPMC30-4K(6)-6J12	○			ø1/4	VPMC30-4K(6)-1/4J	—	
	ø40	ø3	VPMC40-4K(6)-3J	—	M6	ø40	ø1/8	VPMC40-4K(6)-1/8J	—	M6
		ø4	VPMC40-4K(6)-4J12	○			ø5/32	VPMC40-4K(6)-5/32J12	○	
		ø6	VPMC40-4K(6)-6J12	○			ø1/4	VPMC40-4K(6)-1/4J	—	
	ø50	ø3	VPMC50-4K(6)-3J	—	M6	ø50	ø1/8	VPMC50-4K(6)-1/8J	—	M6
		ø4	VPMC50-4K(6)-4J12	○			ø5/32	VPMC50-4K(6)-5/32J12	○	
		ø6	VPMC50-4K(6)-6J12	○			ø1/4	VPMC50-4K(6)-1/4J	—	

Stroke 4mm

Notes
 *Barb fitting type holders are also selectable. VPMC holders are also available in Push-in fitting type for tube O.D. of 1.8 mm and 2 mm. Contact us for the details.

Options
 12-S3 ⇒ -S3 spec. (○ in the lists: Available)
 *1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
 *2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

CAD data is available
 at PISCO website.

Packaging specifications
 1 pc./bag

Optional items
 ⇒ P.525

Fall Prevention Valve

Swivel Joint for vacuum pad

Filter

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	12-S3 spec.	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	12-S3 spec.	Connection config. code		
Spring type, Top port, Push-in fitting, Standard VPC 	ø10	6	ø3	VPC10-6K(6)-3J(8)	—	M4	ø10	6	ø1/8	VPC10-6K(6)-1/8J(8)	—	M4		
			ø4	VPC10-6K(6)-4J(8)12	○				ø5/32	VPC10-6K(6)-5/32J(8)12	○			
			ø6	VPC10-6K(6)-6J(8)12	○				ø1/4	VPC10-6K(6)-1/4J(8)	—			
		10	ø3	VPC10-10K(6)-3J(8)	—			10	ø1/8	VPC10-10K(6)-1/8J(8)	—			
			ø4	VPC10-10K(6)-4J(8)	—				ø5/32	VPC10-10K(6)-5/32J(8)	—			
			ø6	VPC10-10K(6)-6J(8)	—				ø1/4	VPC10-10K(6)-1/4J(8)	—			
		15	ø3	VPC10-15K(6)-3J(8)	—			15	ø1/8	VPC10-15K(6)-1/8J(8)	—			
			ø4	VPC10-15K(6)-4J(8)	—				ø5/32	VPC10-15K(6)-5/32J(8)	—			
			ø6	VPC10-15K(6)-6J(8)	—				ø1/4	VPC10-15K(6)-1/4J(8)	—			
		20	ø3	VPC10-20K(6)-3J(8)	—			20	ø1/8	VPC10-20K(6)-1/8J(8)	—			
			ø4	VPC10-20K(6)-4J(8)	—				ø5/32	VPC10-20K(6)-5/32J(8)	—			
			ø6	VPC10-20K(6)-6J(8)	—				ø1/4	VPC10-20K(6)-1/4J(8)	—			
	ø20	6	ø3	VPC20-6K(6)-3J(8)	—	M6	ø20	6	ø1/8	VPC20-6K(6)-1/8J(8)	—	M6		
			ø4	VPC20-6K(6)-4J(8)12	○				ø5/32	VPC20-6K(6)-5/32J(8)12	○			
			ø6	VPC20-6K(6)-6J(8)12	○				ø1/4	VPC20-6K(6)-1/4J(8)	—			
			10	ø3	VPC20-10K(6)-3J(8)				—	10	ø1/8		VPC20-10K(6)-1/8J(8)	—
				ø4	VPC20-10K(6)-4J(8)				—		ø5/32		VPC20-10K(6)-5/32J(8)	—
				ø6	VPC20-10K(6)-6J(8)				—		ø1/4		VPC20-10K(6)-1/4J(8)	—
		15	ø3	VPC20-15K(6)-3J(8)	—			15	ø1/8	VPC20-15K(6)-1/8J(8)	—			
			ø4	VPC20-15K(6)-4J(8)	—				ø5/32	VPC20-15K(6)-5/32J(8)	—			
			ø6	VPC20-15K(6)-6J(8)	—				ø1/4	VPC20-15K(6)-1/4J(8)	—			
		20	ø3	VPC20-20K(6)-3J(8)	—			20	ø1/8	VPC20-20K(6)-1/8J(8)	—			
			ø4	VPC20-20K(6)-4J(8)	—				ø5/32	VPC20-20K(6)-5/32J(8)	—			
			ø6	VPC20-20K(6)-6J(8)	—				ø1/4	VPC20-20K(6)-1/4J(8)	—			
ø30	6		ø3	VPC30-6K(6)-3J(8)	—	M6	ø30		6	ø1/8	VPC30-6K(6)-1/8J(8)	—	M6	
			ø4	VPC30-6K(6)-4J(8)12	○					ø5/32	VPC30-6K(6)-5/32J(8)12	○		
			ø6	VPC30-6K(6)-6J(8)12	○					ø1/4	VPC30-6K(6)-1/4J(8)	—		
	10	ø3	VPC30-10K(6)-3J(8)	—	10			ø1/8	VPC30-10K(6)-1/8J(8)	—				
		ø4	VPC30-10K(6)-4J(8)	—				ø5/32	VPC30-10K(6)-5/32J(8)	—				
		ø6	VPC30-10K(6)-6J(8)	—				ø1/4	VPC30-10K(6)-1/4J(8)	—				
15	ø3	VPC30-15K(6)-3J(8)	—	15	ø1/8		VPC30-15K(6)-1/8J(8)	—						
	ø4	VPC30-15K(6)-4J(8)	—		ø5/32		VPC30-15K(6)-5/32J(8)	—						
	ø6	VPC30-15K(6)-6J(8)	—		ø1/4		VPC30-15K(6)-1/4J(8)	—						
20	ø3	VPC30-20K(6)-3J(8)	—	20	ø1/8		VPC30-20K(6)-1/8J(8)	—						
	ø4	VPC30-20K(6)-4J(8)	—		ø5/32		VPC30-20K(6)-5/32J(8)	—						
	ø6	VPC30-20K(6)-6J(8)	—		ø1/4		VPC30-20K(6)-1/4J(8)	—						
	ø40	6	ø3		VPC40-6K(6)-3J(8)	—	M6	ø40	6	ø1/8	VPC40-6K(6)-1/8J(8)	—	M6	
			ø4		VPC40-6K(6)-4J(8)12	○				ø5/32	VPC40-6K(6)-5/32J(8)12	○		
			ø6		VPC40-6K(6)-6J(8)12	○				ø1/4	VPC40-6K(6)-1/4J(8)	—		
10			ø3	VPC40-10K(6)-3J(8)	—	10				ø1/8	VPC40-10K(6)-1/8J(8)	—		
			ø4	VPC40-10K(6)-4J(8)	—					ø5/32	VPC40-10K(6)-5/32J(8)	—		
			ø6	VPC40-10K(6)-6J(8)	—					ø1/4	VPC40-10K(6)-1/4J(8)	—		
15		ø3	VPC40-15K(6)-3J(8)	—	15	ø1/8			VPC40-15K(6)-1/8J(8)	—				
		ø4	VPC40-15K(6)-4J(8)	—		ø5/32			VPC40-15K(6)-5/32J(8)	—				
		ø6	VPC40-15K(6)-6J(8)	—		ø1/4			VPC40-15K(6)-1/4J(8)	—				
20		ø3	VPC40-20K(6)-3J(8)	—	20	ø1/8			VPC40-20K(6)-1/8J(8)	—				
		ø4	VPC40-20K(6)-4J(8)	—		ø5/32			VPC40-20K(6)-5/32J(8)	—				
		ø6	VPC40-20K(6)-6J(8)	—		ø1/4			VPC40-20K(6)-1/4J(8)	—				
	ø50	6	ø3	VPC50-6K(6)-3J(8)		—	M6	ø50	6	ø1/8	VPC50-6K(6)-1/8J(8)	—	M6	
			ø4	VPC50-6K(6)-4J(8)12		○				ø5/32	VPC50-6K(6)-5/32J(8)12	○		
			ø6	VPC50-6K(6)-6J(8)12		○				ø1/4	VPC50-6K(6)-1/4J(8)	—		
10		ø3	VPC50-10K(6)-3J(8)	—	10	ø1/8			VPC50-10K(6)-1/8J(8)	—				
		ø4	VPC50-10K(6)-4J(8)	—		ø5/32			VPC50-10K(6)-5/32J(8)	—				
		ø6	VPC50-10K(6)-6J(8)	—		ø1/4			VPC50-10K(6)-1/4J(8)	—				
15	ø3	VPC50-15K(6)-3J(8)	—	15	ø1/8	VPC50-15K(6)-1/8J(8)		—						
	ø4	VPC50-15K(6)-4J(8)	—		ø5/32	VPC50-15K(6)-5/32J(8)		—						
	ø6	VPC50-15K(6)-6J(8)	—		ø1/4	VPC50-15K(6)-1/4J(8)		—						
20	ø3	VPC50-20K(6)-3J(8)	—	20	ø1/8	VPC50-20K(6)-1/8J(8)		—						
	ø4	VPC50-20K(6)-4J(8)	—		ø5/32	VPC50-20K(6)-5/32J(8)		—						
	ø6	VPC50-20K(6)-6J(8)	—		ø1/4	VPC50-20K(6)-1/4J(8)		—						

Vacuum Pad Skidproof Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code (mm size)	⑫-⑬ -S3 spec.	Connection config. code
Spring type, Top port, Female thread, Standard VPC 	ø10	6	M6×1	VPC10-6K⑥-M6⑧⑫	○	M4
		10		VPC10-10K⑥-M6⑧	—	
		15		VPC10-15K⑥-M6⑧	—	
		20		VPC10-20K⑥-M6⑧	—	
	ø20	6	M6×1	VPC20-6K⑥-M6⑧⑫	○	M6
		10		VPC20-10K⑥-M6⑧	—	
		15		VPC20-15K⑥-M6⑧	—	
		20		VPC20-20K⑥-M6⑧	—	
	ø30	6	M6×1	VPC30-6K⑥-M6⑧⑫	○	M6
		10		VPC30-10K⑥-M6⑧	—	
		15		VPC30-15K⑥-M6⑧	—	
		20		VPC30-20K⑥-M6⑧	—	
	ø40	6	M6×1	VPC40-6K⑥-M6⑧⑫	○	M6
		10		VPC40-10K⑥-M6⑧	—	
		15		VPC40-15K⑥-M6⑧	—	
		20		VPC40-20K⑥-M6⑧	—	
	ø50	6	M6×1	VPC50-6K⑥-M6⑧⑫	○	M6
		10		VPC50-10K⑥-M6⑧	—	
		15		VPC50-15K⑥-M6⑧	—	
		20		VPC50-20K⑥-M6⑧	—	

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Options
⑫: -DC ⇒ Holder with dust catcher
⑬: -S3 ⇒ S3 spec. (○ in the lists: Available)
*1. For "S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
*2. For inch size push-in fitting, the release ring color is white even for "S3 spec."



PISCO®


>>> <https://www.pisco.co.jp/en>

Notes
*Barb fitting type
holders are also
available. Contact
us for the details.

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Optional items
⇒ P.525



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Top port, Push-in fitting, No cover VPOC 	ø10	20	ø3	VPOC10-20K⑥-3J	M4	ø10	20	ø1/8	VPOC10-20K⑥-1/8J	M4
			ø4	VPOC10-20K⑥-4J				ø5/32	VPOC10-20K⑥-5/32J	
			ø6	VPOC10-20K⑥-6J				ø1/4	VPOC10-20K⑥-1/4J	
			ø8	VPOC10-20K⑥-8J				ø1/8	VPOC10-20K⑥-1/8J	
		30	ø3	VPOC10-30K⑥-3J			30	ø1/8	VPOC10-30K⑥-1/8J	
			ø4	VPOC10-30K⑥-4J				ø5/32	VPOC10-30K⑥-5/32J	
			ø6	VPOC10-30K⑥-6J				ø1/4	VPOC10-30K⑥-1/4J	
			ø8	VPOC10-30K⑥-8J				ø1/8	VPOC10-30K⑥-1/8J	
		40	ø3	VPOC10-40K⑥-3J			40	ø1/8	VPOC10-40K⑥-1/8J	
			ø4	VPOC10-40K⑥-4J				ø5/32	VPOC10-40K⑥-5/32J	
			ø6	VPOC10-40K⑥-6J				ø1/4	VPOC10-40K⑥-1/4J	
			ø8	VPOC10-40K⑥-8J				ø1/8	VPOC10-40K⑥-1/8J	
		50	ø3	VPOC10-50K⑥-3J			50	ø1/8	VPOC10-50K⑥-1/8J	
			ø4	VPOC10-50K⑥-4J				ø5/32	VPOC10-50K⑥-5/32J	
			ø6	VPOC10-50K⑥-6J				ø1/4	VPOC10-50K⑥-1/4J	
			ø8	VPOC10-50K⑥-8J				ø1/8	VPOC10-50K⑥-1/8J	
	ø20	20	ø3	VPOC20-20K⑥-3J	M4	ø20	20	ø1/8	VPOC20-20K⑥-1/8J	M4
			ø4	VPOC20-20K⑥-4J				ø5/32	VPOC20-20K⑥-5/32J	
			ø6	VPOC20-20K⑥-6J				ø1/4	VPOC20-20K⑥-1/4J	
			ø8	VPOC20-20K⑥-8J				ø1/8	VPOC20-20K⑥-1/8J	
		30	ø3	VPOC20-30K⑥-3J			30	ø1/8	VPOC20-30K⑥-1/8J	
			ø4	VPOC20-30K⑥-4J				ø5/32	VPOC20-30K⑥-5/32J	
			ø6	VPOC20-30K⑥-6J				ø1/4	VPOC20-30K⑥-1/4J	
			ø8	VPOC20-30K⑥-8J				ø1/8	VPOC20-30K⑥-1/8J	
		40	ø3	VPOC20-40K⑥-3J			40	ø1/8	VPOC20-40K⑥-1/8J	
			ø4	VPOC20-40K⑥-4J				ø5/32	VPOC20-40K⑥-5/32J	
			ø6	VPOC20-40K⑥-6J				ø1/4	VPOC20-40K⑥-1/4J	
			ø8	VPOC20-40K⑥-8J				ø1/8	VPOC20-40K⑥-1/8J	
		50	ø3	VPOC20-50K⑥-3J			50	ø1/8	VPOC20-50K⑥-1/8J	
			ø4	VPOC20-50K⑥-4J				ø5/32	VPOC20-50K⑥-5/32J	
			ø6	VPOC20-50K⑥-6J				ø1/4	VPOC20-50K⑥-1/4J	
			ø8	VPOC20-50K⑥-8J				ø1/8	VPOC20-50K⑥-1/8J	
	ø30	20	ø3	VPOC30-20K⑥-3J	M6	ø30	20	ø1/8	VPOC30-20K⑥-1/8J	M6
			ø4	VPOC30-20K⑥-4J				ø5/32	VPOC30-20K⑥-5/32J	
			ø6	VPOC30-20K⑥-6J				ø1/4	VPOC30-20K⑥-1/4J	
			ø8	VPOC30-20K⑥-8J				ø1/8	VPOC30-20K⑥-1/8J	
		30	ø3	VPOC30-30K⑥-3J			30	ø1/8	VPOC30-30K⑥-1/8J	
			ø4	VPOC30-30K⑥-4J				ø5/32	VPOC30-30K⑥-5/32J	
			ø6	VPOC30-30K⑥-6J				ø1/4	VPOC30-30K⑥-1/4J	
			ø8	VPOC30-30K⑥-8J				ø1/8	VPOC30-30K⑥-1/8J	
		40	ø3	VPOC30-40K⑥-3J			40	ø1/8	VPOC30-40K⑥-1/8J	
			ø4	VPOC30-40K⑥-4J				ø5/32	VPOC30-40K⑥-5/32J	
			ø6	VPOC30-40K⑥-6J				ø1/4	VPOC30-40K⑥-1/4J	
			ø8	VPOC30-40K⑥-8J				ø1/8	VPOC30-40K⑥-1/8J	
		50	ø3	VPOC30-50K⑥-3J			50	ø1/8	VPOC30-50K⑥-1/8J	
			ø4	VPOC30-50K⑥-4J				ø5/32	VPOC30-50K⑥-5/32J	
			ø6	VPOC30-50K⑥-6J				ø1/4	VPOC30-50K⑥-1/4J	
			ø8	VPOC30-50K⑥-8J				ø1/8	VPOC30-50K⑥-1/8J	
	ø40	20	ø3	VPOC40-20K⑥-3J	M6	ø40	20	ø1/8	VPOC40-20K⑥-1/8J	M6
			ø4	VPOC40-20K⑥-4J				ø5/32	VPOC40-20K⑥-5/32J	
			ø6	VPOC40-20K⑥-6J				ø1/4	VPOC40-20K⑥-1/4J	
			ø8	VPOC40-20K⑥-8J				ø1/8	VPOC40-20K⑥-1/8J	
		30	ø3	VPOC40-30K⑥-3J			30	ø1/8	VPOC40-30K⑥-1/8J	
			ø4	VPOC40-30K⑥-4J				ø5/32	VPOC40-30K⑥-5/32J	
			ø6	VPOC40-30K⑥-6J				ø1/4	VPOC40-30K⑥-1/4J	
			ø8	VPOC40-30K⑥-8J				ø1/8	VPOC40-30K⑥-1/8J	
		40	ø3	VPOC40-40K⑥-3J			40	ø1/8	VPOC40-40K⑥-1/8J	
			ø4	VPOC40-40K⑥-4J				ø5/32	VPOC40-40K⑥-5/32J	
			ø6	VPOC40-40K⑥-6J				ø1/4	VPOC40-40K⑥-1/4J	
			ø8	VPOC40-40K⑥-8J				ø1/8	VPOC40-40K⑥-1/8J	
		50	ø3	VPOC40-50K⑥-3J			50	ø1/8	VPOC40-50K⑥-1/8J	
			ø4	VPOC40-50K⑥-4J				ø5/32	VPOC40-50K⑥-5/32J	
			ø6	VPOC40-50K⑥-6J				ø1/4	VPOC40-50K⑥-1/4J	
			ø8	VPOC40-50K⑥-8J				ø1/8	VPOC40-50K⑥-1/8J	
	ø50	20	ø3	VPOC50-20K⑥-3J	M6	ø50	20	ø1/8	VPOC50-20K⑥-1/8J	M6
			ø4	VPOC50-20K⑥-4J				ø5/32	VPOC50-20K⑥-5/32J	
			ø6	VPOC50-20K⑥-6J				ø1/4	VPOC50-20K⑥-1/4J	
			ø8	VPOC50-20K⑥-8J				ø1/8	VPOC50-20K⑥-1/8J	
		30	ø3	VPOC50-30K⑥-3J			30	ø1/8	VPOC50-30K⑥-1/8J	
			ø4	VPOC50-30K⑥-4J				ø5/32	VPOC50-30K⑥-5/32J	
			ø6	VPOC50-30K⑥-6J				ø1/4	VPOC50-30K⑥-1/4J	
			ø8	VPOC50-30K⑥-8J				ø1/8	VPOC50-30K⑥-1/8J	
		40	ø3	VPOC50-40K⑥-3J			40	ø1/8	VPOC50-40K⑥-1/8J	
			ø4	VPOC50-40K⑥-4J				ø5/32	VPOC50-40K⑥-5/32J	
			ø6	VPOC50-40K⑥-6J				ø1/4	VPOC50-40K⑥-1/4J	
			ø8	VPOC50-40K⑥-8J				ø1/8	VPOC50-40K⑥-1/8J	
		50	ø3	VPOC50-50K⑥-3J			50	ø1/8	VPOC50-50K⑥-1/8J	
			ø4	VPOC50-50K⑥-4J	ø5/32	VPOC50-50K⑥-5/32J				
ø6	VPOC50-50K⑥-6J	ø1/4	VPOC50-50K⑥-1/4J							

Vacuum Pad Skidproof Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Top port, Female thread, No cover VPOC 	ø10	20	M6×1	VPOC10-20K-1/8-M6	M4
		30		VPOC10-30K-1/8-M6	
		40		VPOC10-40K-1/8-M6	
		50		VPOC10-50K-1/8-M6	
	ø20	20	M6×1	VPOC20-20K-1/8-M6	M4
		30		VPOC20-30K-1/8-M6	
		40		VPOC20-40K-1/8-M6	
		50		VPOC20-50K-1/8-M6	
	ø30	20	M6×1	VPOC30-20K-1/8-M6	M6
		30		VPOC30-30K-1/8-M6	
		40		VPOC30-40K-1/8-M6	
		50		VPOC30-50K-1/8-M6	
	ø40	20	M6×1	VPOC40-20K-1/8-M6	M6
		30		VPOC40-30K-1/8-M6	
		40		VPOC40-40K-1/8-M6	
		50		VPOC40-50K-1/8-M6	
	ø50	20	M6×1	VPOC50-20K-1/8-M6	M6
		30		VPOC50-30K-1/8-M6	
		40		VPOC50-40K-1/8-M6	
		50		VPOC50-50K-1/8-M6	

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Optional items
⇒ P.525

Fall
Prevention
Valve



Swivel
Joint for
vacuum pad



Filter



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Top port, Push-in fitting, Low dust emission VPLFC 	ø10	2	ø3	VPLFC10-2K-1/8-3J	M4	ø10	2	ø1/8	VPLFC10-2K-1/8-1/4J	M4
			ø4	VPLFC10-2K-1/8-4J				ø5/32	VPLFC10-2K-1/8-5/32J	
		5	ø3	VPLFC10-5K-1/8-3J			5	ø1/8	VPLFC10-5K-1/8-1/4J	
			ø4	VPLFC10-5K-1/8-4J				ø5/32	VPLFC10-5K-1/8-5/32J	
		10	ø3	VPLFC10-10K-1/8-3J			10	ø1/8	VPLFC10-10K-1/8-1/4J	
			ø4	VPLFC10-10K-1/8-4J				ø5/32	VPLFC10-10K-1/8-5/32J	
		15	ø3	VPLFC10-15K-1/8-3J			15	ø1/8	VPLFC10-15K-1/8-1/4J	
			ø4	VPLFC10-15K-1/8-4J				ø5/32	VPLFC10-15K-1/8-5/32J	
		20	ø3	VPLFC10-20K-1/8-3J			20	ø1/8	VPLFC10-20K-1/8-1/4J	
			ø4	VPLFC10-20K-1/8-4J				ø5/32	VPLFC10-20K-1/8-5/32J	
	ø20	5	ø3	VPLFC20-5K-1/8-3J	M6	ø20	5	ø1/8	VPLFC20-5K-1/8-1/4J	M6
			ø4	VPLFC20-5K-1/8-4J				ø5/32	VPLFC20-5K-1/8-5/32J	
		10	ø4	VPLFC20-10K-1/8-4J			10	ø1/4	VPLFC20-10K-1/8-1/4J	
			ø6	VPLFC20-10K-1/8-6J				ø1/8	VPLFC20-10K-1/8-1/4J	
		15	ø3	VPLFC20-15K-1/8-3J			15	ø1/8	VPLFC20-15K-1/8-1/4J	
			ø4	VPLFC20-15K-1/8-4J				ø5/32	VPLFC20-15K-1/8-5/32J	
		20	ø6	VPLFC20-20K-1/8-6J			20	ø1/4	VPLFC20-20K-1/8-1/4J	
			ø3	VPLFC20-20K-1/8-3J				ø1/8	VPLFC20-20K-1/8-1/4J	
	ø30	5	ø3	VPLFC30-5K-1/8-3J	M6	ø30	5	ø1/8	VPLFC30-5K-1/8-1/4J	M6
			ø4	VPLFC30-5K-1/8-4J				ø5/32	VPLFC30-5K-1/8-5/32J	
		10	ø6	VPLFC30-10K-1/8-6J			10	ø1/4	VPLFC30-10K-1/8-1/4J	
			ø3	VPLFC30-10K-1/8-3J				ø1/8	VPLFC30-10K-1/8-1/4J	
		15	ø4	VPLFC30-15K-1/8-4J			15	ø1/8	VPLFC30-15K-1/8-1/4J	
			ø6	VPLFC30-15K-1/8-6J				ø5/32	VPLFC30-15K-1/8-5/32J	
		20	ø3	VPLFC30-20K-1/8-3J			20	ø1/8	VPLFC30-20K-1/8-1/4J	
			ø4	VPLFC30-20K-1/8-4J				ø5/32	VPLFC30-20K-1/8-5/32J	
	ø40	5	ø3	VPLFC40-5K-1/8-3J	M6	ø40	5	ø1/8	VPLFC40-5K-1/8-1/4J	M6
			ø4	VPLFC40-5K-1/8-4J				ø5/32	VPLFC40-5K-1/8-5/32J	
		10	ø6	VPLFC40-10K-1/8-6J			10	ø1/4	VPLFC40-10K-1/8-1/4J	
			ø3	VPLFC40-10K-1/8-3J				ø1/8	VPLFC40-10K-1/8-1/4J	
		15	ø4	VPLFC40-15K-1/8-4J			15	ø1/8	VPLFC40-15K-1/8-1/4J	
			ø6	VPLFC40-15K-1/8-6J				ø5/32	VPLFC40-15K-1/8-5/32J	
		20	ø3	VPLFC40-20K-1/8-3J			20	ø1/8	VPLFC40-20K-1/8-1/4J	
			ø4	VPLFC40-20K-1/8-4J				ø5/32	VPLFC40-20K-1/8-5/32J	
	ø50	5	ø6	VPLFC50-5K-1/8-6J	M6	ø50	5	ø1/4	VPLFC50-5K-1/8-1/4J	M6
			ø3	VPLFC50-5K-1/8-3J				ø1/8	VPLFC50-5K-1/8-1/4J	
		10	ø4	VPLFC50-10K-1/8-4J			10	ø1/8	VPLFC50-10K-1/8-1/4J	
			ø6	VPLFC50-10K-1/8-6J				ø5/32	VPLFC50-10K-1/8-5/32J	
		15	ø3	VPLFC50-15K-1/8-3J			15	ø1/8	VPLFC50-15K-1/8-1/4J	
			ø4	VPLFC50-15K-1/8-4J				ø5/32	VPLFC50-15K-1/8-5/32J	
		20	ø6	VPLFC50-20K-1/8-6J			20	ø1/4	VPLFC50-20K-1/8-1/4J	
			ø3	VPLFC50-20K-1/8-3J				ø1/8	VPLFC50-20K-1/8-1/4J	
	ø50	5	ø4	VPLFC50-5K-1/8-4J	M6	ø50	5	ø1/8	VPLFC50-5K-1/8-1/4J	M6
			ø6	VPLFC50-5K-1/8-6J				ø5/32	VPLFC50-5K-1/8-5/32J	
		10	ø3	VPLFC50-10K-1/8-3J			10	ø1/8	VPLFC50-10K-1/8-1/4J	
			ø4	VPLFC50-10K-1/8-4J				ø5/32	VPLFC50-10K-1/8-5/32J	
		15	ø6	VPLFC50-15K-1/8-6J			15	ø1/4	VPLFC50-15K-1/8-1/4J	
			ø3	VPLFC50-15K-1/8-3J				ø1/8	VPLFC50-15K-1/8-1/4J	
		20	ø4	VPLFC50-20K-1/8-4J			20	ø1/8	VPLFC50-20K-1/8-1/4J	
			ø6	VPLFC50-20K-1/8-6J				ø5/32	VPLFC50-20K-1/8-5/32J	



Notes

*Barb fitting type holders are also available.
Contact us for the details.



Packaging specifications
1 pc./bag



Options

⇒ -SF1/4 ⇒ Spring load 1/4

Optional items
⇒ P.525

Fall
Prevention
Valve



Swivel
Joint for
vacuum pad



Filter



Vacuum Pad Skidproof Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Top port, Female thread, Low dust emission VPLFC 	ø10	2	M5×0.8	VPLFC10-2K[5]-M5	M4
		5	M5×0.8	VPLFC10-5K[5]-M5	
		10	M5×0.8	VPLFC10-10K[5]-M5	
		15	M5×0.8	VPLFC10-15K[5]-M5	
	ø20	20	M5×0.8	VPLFC10-20K[5]-M5	M6
		5	M6×1	VPLFC20-5K[5]-M6	
		10	M6×1	VPLFC20-10K[5]-M6	
		15	M6×1	VPLFC20-15K[5]-M6	
	ø30	20	M6×1	VPLFC20-20K[5]-M6	M6
		5	M6×1	VPLFC30-5K[5]-M6	
		10	M6×1	VPLFC30-10K[5]-M6	
		15	M6×1	VPLFC30-15K[5]-M6	
Spring type, Side port, Push-in fitting, Standard VPD 	ø10	6	ø3	VPD10-6K[5]-3J[5]	M4
		10	ø4	VPD10-10K[5]-3J[5]	
		15	ø6	VPD10-15K[5]-3J[5]	
		20	ø8	VPD10-20K[5]-3J[5]	
	ø20	6	ø4	VPD20-6K[5]-4J[5]	M6
		10	ø6	VPD20-10K[5]-4J[5]	
		15	ø8	VPD20-15K[5]-4J[5]	
		20	ø10	VPD20-20K[5]-4J[5]	
	ø30	6	ø6	VPD30-6K[5]-6J[5]	M6
		10	ø8	VPD30-10K[5]-6J[5]	
		15	ø10	VPD30-15K[5]-6J[5]	
		20	ø12	VPD30-20K[5]-6J[5]	
Spring type, Push-in fitting, Mini VPMD 	ø10	ø3	VPMD10-4K[5]-3J	—	M4
		ø4	VPMD10-4K[5]-4J[5]	—	
		ø6	VPMD10-4K[5]-6J[5]	—	
		ø8	VPMD10-4K[5]-8J[5]	—	
	ø20	ø3	VPMD20-4K[5]-3J	—	M6
		ø4	VPMD20-4K[5]-4J[5]	—	
		ø6	VPMD20-4K[5]-6J[5]	—	
		ø8	VPMD20-4K[5]-8J[5]	—	
	ø30	ø3	VPMD30-4K[5]-3J	—	M6
		ø4	VPMD30-4K[5]-4J[5]	—	
		ø6	VPMD30-4K[5]-6J[5]	—	
		ø8	VPMD30-4K[5]-8J[5]	—	
Spring type, Side port, Female thread, Mini VPMD 	ø10	M5×0.8	VPMD10-4K[5]-M5	—	M4
		M5×0.8	VPMD20-4K[5]-M5	—	
		M5×0.8	VPMD30-4K[5]-M5	—	
		M5×0.8	VPMD40-4K[5]-M5	—	
	ø20	M5×0.8	VPMD20-4K[5]-M5	—	M6
		M5×0.8	VPMD30-4K[5]-M5	—	
		M5×0.8	VPMD40-4K[5]-M5	—	
		M5×0.8	VPMD50-4K[5]-M5	—	
	ø30	M5×0.8	VPMD30-4K[5]-M5	—	M6
		M5×0.8	VPMD40-4K[5]-M5	—	
		M5×0.8	VPMD50-4K[5]-M5	—	
		M5×0.8	VPMD60-4K[5]-M5	—	

Notes
 *VPMD holders are also available in Push-in fitting type for tube O.D. of 1.8 mm and 2 mm, and barb fitting type. Contact us for the details.

CAD
 CAD data is available at PISCO website.

Packaging
 Packaging specifications 1 pc./bag

Options
 [5] -SF1/4 ⇒ Spring load 1/4
 [5] -S3 ⇒ -S3 spec. (○ in the lists: Available)
 *1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
 *2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items
 ⇒ P.525
 Fall Prevention Valve, Swivel Joint for vacuum pad, Filter

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	[5] -S3 -S3 spec.	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	[5] -S3 -S3 spec.	Connection config. code
Spring type, Side port, Push-in fitting, Standard VPD 	ø10	6	ø3	VPD10-6K[5]-3J[5]	—	M4	ø10	6	ø1/8	VPD10-6K[5]-1/8J[5]	—	M4
		10	ø4	VPD10-10K[5]-3J[5]	—			10	ø5/32	VPD10-10K[5]-5/32J[5]	—	
		15	ø6	VPD10-15K[5]-3J[5]	—			15	ø1/4	VPD10-15K[5]-1/4J[5]	—	
		20	ø8	VPD10-20K[5]-3J[5]	—			20	ø5/32	VPD10-20K[5]-5/32J[5]	—	
	ø20	6	ø4	VPD20-6K[5]-4J[5]	—	M6	ø20	6	ø1/8	VPD20-6K[5]-1/8J[5]	—	M6
		10	ø6	VPD20-10K[5]-4J[5]	—			10	ø5/32	VPD20-10K[5]-5/32J[5]	—	
		15	ø8	VPD20-15K[5]-4J[5]	—			15	ø1/4	VPD20-15K[5]-1/4J[5]	—	
		20	ø10	VPD20-20K[5]-4J[5]	—			20	ø5/32	VPD20-20K[5]-5/32J[5]	—	
	ø30	6	ø6	VPD30-6K[5]-6J[5]	—	M6	ø30	6	ø1/8	VPD30-6K[5]-1/8J[5]	—	M6
		10	ø8	VPD30-10K[5]-6J[5]	—			10	ø5/32	VPD30-10K[5]-5/32J[5]	—	
		15	ø10	VPD30-15K[5]-6J[5]	—			15	ø1/4	VPD30-15K[5]-1/4J[5]	—	
		20	ø12	VPD30-20K[5]-6J[5]	—			20	ø5/32	VPD30-20K[5]-5/32J[5]	—	
Spring type, Side port, Push-in fitting, Standard VPD 	ø10	6	ø3	VPD10-6K[5]-3J[5]	—	M4	ø10	6	ø1/8	VPD10-6K[5]-1/8J[5]	—	M4
		10	ø4	VPD10-10K[5]-3J[5]	—			10	ø5/32	VPD10-10K[5]-5/32J[5]	—	
		15	ø6	VPD10-15K[5]-3J[5]	—			15	ø1/4	VPD10-15K[5]-1/4J[5]	—	
		20	ø8	VPD10-20K[5]-3J[5]	—			20	ø5/32	VPD10-20K[5]-5/32J[5]	—	
	ø20	6	ø4	VPD20-6K[5]-4J[5]	—	M6	ø20	6	ø1/8	VPD20-6K[5]-1/8J[5]	—	M6
		10	ø6	VPD20-10K[5]-4J[5]	—			10	ø5/32	VPD20-10K[5]-5/32J[5]	—	
		15	ø8	VPD20-15K[5]-4J[5]	—			15	ø1/4	VPD20-15K[5]-1/4J[5]	—	
		20	ø10	VPD20-20K[5]-4J[5]	—			20	ø5/32	VPD20-20K[5]-5/32J[5]	—	
	ø30	6	ø6	VPD30-6K[5]-6J[5]	—	M6	ø30	6	ø1/8	VPD30-6K[5]-1/8J[5]	—	M6
		10	ø8	VPD30-10K[5]-6J[5]	—			10	ø5/32	VPD30-10K[5]-5/32J[5]	—	
		15	ø10	VPD30-15K[5]-6J[5]	—			15	ø1/4	VPD30-15K[5]-1/4J[5]	—	
		20	ø12	VPD30-20K[5]-6J[5]	—			20	ø5/32	VPD30-20K[5]-5/32J[5]	—	
Spring type, Side port, Push-in fitting, Standard VPD 	ø10	6	ø3	VPD10-6K[5]-3J[5]	—	M4	ø10	6	ø1/8	VPD10-6K[5]-1/8J[5]	—	M4
		10	ø4	VPD10-10K[5]-3J[5]	—			10	ø5/32	VPD10-10K[5]-5/32J[5]	—	
		15	ø6	VPD10-15K[5]-3J[5]	—			15	ø1/4	VPD10-15K[5]-1/4J[5]	—	
		20	ø8	VPD10-20K[5]-3J[5]	—			20	ø5/32	VPD10-20K[5]-5/32J[5]	—	
	ø20	6	ø4	VPD20-6K[5]-4J[5]	—	M6	ø20	6	ø1/8	VPD20-6K[5]-1/8J[5]	—	M6
		10	ø6	VPD20-10K[5]-4J[5]	—			10	ø5/32	VPD20-10K[5]-5/32J[5]	—	
		15	ø8	VPD20-15K[5]-4J[5]	—			15	ø1/4	VPD20-15K[5]-1/4J[5]	—	
		20	ø10	VPD20-20K[5]-4J[5]	—			20	ø5/32	VPD20-20K[5]-5/32J[5]	—	
	ø30	6	ø6	VPD30-6K[5]-6J[5]	—	M6	ø30	6	ø1/8	VPD30-6K[5]-1/8J[5]	—	M6
		10	ø8	VPD30-10K[5]-6J[5]	—			10	ø5/32	VPD30-10K[5]-5/32J[5]	—	
		15	ø10	VPD30-15K[5]-6J[5]	—			15	ø1/4	VPD30-15K[5]-1/4J[5]	—	
		20	ø12	VPD30-20K[5]-6J[5]	—			20	ø5/32	VPD30-20K[5]-5/32J[5]	—	

Notes
 *Barb fitting type holders are also available. Contact us for the details.

CAD
 CAD data is available at PISCO website.

Packaging
 Packaging specifications 1 pc./bag

Options
 [5] -DC ⇒ Holder with dust catcher
 [5] -S3 ⇒ -S3 spec. (○ in the lists: Available)
 *1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.
 *2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items
 ⇒ P.525
 Dust Catcher (VPD), Fall Prevention Valve, Swivel Joint for vacuum pad, Filter

Vacuum Pad Skidproof Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	⑫-⑬ -S3 spec.	Connection config. code
Spring type, Side port, Female thread, Standard VPD 	ø10	6	M6×1	VPD10-6K⑥-M6⑧⑩⑫	○	M4
		10		VPD10-10K⑥-M6⑧	—	
		15		VPD10-15K⑥-M6⑧	—	
		20		VPD10-20K⑥-M6⑧	—	
	ø20	6	M6×1	VPD20-6K⑥-M6⑧⑩⑫	○	
		10		VPD20-10K⑥-M6⑧	—	
		15		VPD20-15K⑥-M6⑧	—	
		20		VPD20-20K⑥-M6⑧	—	
	ø30	6	M6×1	VPD30-6K⑥-M6⑧⑩⑫	○	
		10		VPD30-10K⑥-M6⑧	—	
		15		VPD30-15K⑥-M6⑧	—	
		20		VPD30-20K⑥-M6⑧	—	
	ø40	6	M6×1	VPD40-6K⑥-M6⑧⑩⑫	○	M6
		10		VPD40-10K⑥-M6⑧	—	
		15		VPD40-15K⑥-M6⑧	—	
		20		VPD40-20K⑥-M6⑧	—	
	ø50	6	M6×1	VPD50-6K⑥-M6⑧⑩⑫	○	
		10		VPD50-10K⑥-M6⑧	—	
		15		VPD50-15K⑥-M6⑧	—	
		20		VPD50-20K⑥-M6⑧	—	

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Options

⑧1: -DC ⇒ Holder with dust catcher

⑩⑫: -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For "-S3 spec.", the release ring color is dark blue, and the gasket material is FKM+SUS316.

*2. For inch size push-in fitting, the release ring color is white even for "-S3 spec."

Optional items ⇒ P.525	Dust Catcher (VPD)	Fall Prevention Valve	Swivel Joint for vacuum pad	Filter
---------------------------	--------------------------	-----------------------------	-----------------------------------	--------

RoHS2 (2011/65/EU+EU2015/863) compliant


Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, No cover VPOD 	ø10	20	ø3	VPOD10-20K⑥-3J	M4	ø10	20	ø1/8	VPOD10-20K⑥-1/8J	M4
			ø4	VPOD10-20K⑥-4J				ø5/32	VPOD10-20K⑥-5/32J	
			ø6	VPOD10-20K⑥-6J				ø1/4	VPOD10-20K⑥-1/4J	
			ø3	VPOD10-30K⑥-3J			30	ø1/8	VPOD10-30K⑥-1/8J	
			ø4	VPOD10-30K⑥-4J				ø5/32	VPOD10-30K⑥-5/32J	
			ø6	VPOD10-30K⑥-6J				ø1/4	VPOD10-30K⑥-1/4J	
		40	ø3	VPOD10-40K⑥-3J			40	ø1/8	VPOD10-40K⑥-1/8J	
			ø4	VPOD10-40K⑥-4J				ø5/32	VPOD10-40K⑥-5/32J	
			ø6	VPOD10-40K⑥-6J				ø1/4	VPOD10-40K⑥-1/4J	
		50	ø3	VPOD10-50K⑥-3J			50	ø1/8	VPOD10-50K⑥-1/8J	
			ø4	VPOD10-50K⑥-4J				ø5/32	VPOD10-50K⑥-5/32J	
			ø6	VPOD10-50K⑥-6J				ø1/4	VPOD10-50K⑥-1/4J	
	ø20	20	ø3	VPOD20-20K⑥-3J	M6	ø20	20	ø1/8	VPOD20-20K⑥-1/8J	M6
			ø4	VPOD20-20K⑥-4J				ø5/32	VPOD20-20K⑥-5/32J	
			ø6	VPOD20-20K⑥-6J				ø1/4	VPOD20-20K⑥-1/4J	
		30	ø3	VPOD20-30K⑥-3J			30	ø1/8	VPOD20-30K⑥-1/8J	
			ø4	VPOD20-30K⑥-4J				ø5/32	VPOD20-30K⑥-5/32J	
			ø6	VPOD20-30K⑥-6J				ø1/4	VPOD20-30K⑥-1/4J	
		40	ø3	VPOD20-40K⑥-3J			40	ø1/8	VPOD20-40K⑥-1/8J	
			ø4	VPOD20-40K⑥-4J				ø5/32	VPOD20-40K⑥-5/32J	
			ø6	VPOD20-40K⑥-6J				ø1/4	VPOD20-40K⑥-1/4J	
		50	ø3	VPOD20-50K⑥-3J			50	ø1/8	VPOD20-50K⑥-1/8J	
			ø4	VPOD20-50K⑥-4J				ø5/32	VPOD20-50K⑥-5/32J	
			ø6	VPOD20-50K⑥-6J				ø1/4	VPOD20-50K⑥-1/4J	
	ø30	20	ø3	VPOD30-20K⑥-3J	M6	ø30	20	ø1/8	VPOD30-20K⑥-1/8J	M6
			ø4	VPOD30-20K⑥-4J				ø5/32	VPOD30-20K⑥-5/32J	
			ø6	VPOD30-20K⑥-6J				ø1/4	VPOD30-20K⑥-1/4J	
		30	ø3	VPOD30-30K⑥-3J			30	ø1/8	VPOD30-30K⑥-1/8J	
			ø4	VPOD30-30K⑥-4J				ø5/32	VPOD30-30K⑥-5/32J	
			ø6	VPOD30-30K⑥-6J				ø1/4	VPOD30-30K⑥-1/4J	
		40	ø3	VPOD30-40K⑥-3J			40	ø1/8	VPOD30-40K⑥-1/8J	
			ø4	VPOD30-40K⑥-4J				ø5/32	VPOD30-40K⑥-5/32J	
			ø6	VPOD30-40K⑥-6J				ø1/4	VPOD30-40K⑥-1/4J	
		50	ø3	VPOD30-50K⑥-3J			50	ø1/8	VPOD30-50K⑥-1/8J	
			ø4	VPOD30-50K⑥-4J				ø5/32	VPOD30-50K⑥-5/32J	
			ø6	VPOD30-50K⑥-6J				ø1/4	VPOD30-50K⑥-1/4J	
	ø40	20	ø3	VPOD40-20K⑥-3J	M6	ø40	20	ø1/8	VPOD40-20K⑥-1/8J	M6
			ø4	VPOD40-20K⑥-4J				ø5/32	VPOD40-20K⑥-5/32J	
			ø6	VPOD40-20K⑥-6J				ø1/4	VPOD40-20K⑥-1/4J	
		30	ø3	VPOD40-30K⑥-3J			30	ø1/8	VPOD40-30K⑥-1/8J	
			ø4	VPOD40-30K⑥-4J				ø5/32	VPOD40-30K⑥-5/32J	
			ø6	VPOD40-30K⑥-6J				ø1/4	VPOD40-30K⑥-1/4J	
		40	ø3	VPOD40-40K⑥-3J			40	ø1/8	VPOD40-40K⑥-1/8J	
			ø4	VPOD40-40K⑥-4J				ø5/32	VPOD40-40K⑥-5/32J	
			ø6	VPOD40-40K⑥-6J				ø1/4	VPOD40-40K⑥-1/4J	
		50	ø3	VPOD40-50K⑥-3J			50	ø1/8	VPOD40-50K⑥-1/8J	
			ø4	VPOD40-50K⑥-4J				ø5/32	VPOD40-50K⑥-5/32J	
			ø6	VPOD40-50K⑥-6J				ø1/4	VPOD40-50K⑥-1/4J	
	ø50	20	ø3	VPOD50-20K⑥-3J	M6	ø50	20	ø1/8	VPOD50-20K⑥-1/8J	M6
			ø4	VPOD50-20K⑥-4J				ø5/32	VPOD50-20K⑥-5/32J	
			ø6	VPOD50-20K⑥-6J				ø1/4	VPOD50-20K⑥-1/4J	
		30	ø3	VPOD50-30K⑥-3J			30	ø1/8	VPOD50-30K⑥-1/8J	
			ø4	VPOD50-30K⑥-4J				ø5/32	VPOD50-30K⑥-5/32J	
			ø6	VPOD50-30K⑥-6J				ø1/4	VPOD50-30K⑥-1/4J	
		40	ø3	VPOD50-40K⑥-3J			40	ø1/8	VPOD50-40K⑥-1/8J	
			ø4	VPOD50-40K⑥-4J				ø5/32	VPOD50-40K⑥-5/32J	
			ø6	VPOD50-40K⑥-6J				ø1/4	VPOD50-40K⑥-1/4J	
		50	ø3	VPOD50-50K⑥-3J			50	ø1/8	VPOD50-50K⑥-1/8J	
			ø4	VPOD50-50K⑥-4J				ø5/32	VPOD50-50K⑥-5/32J	
			ø6	VPOD50-50K⑥-6J				ø1/4	VPOD50-50K⑥-1/4J	

Notes
*Barb fitting type
holders are also
available. Contact
us for the details.

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Optional items
⇒ P.525



Vacuum Pad Skidproof Type

RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Side port, Female thread, No cover VPOD 	ø10	20	M6×1	VPOD10-20K-1/6J	M4
		30		VPOD10-30K-1/6J	
		40		VPOD10-40K-1/6J	
		50		VPOD10-50K-1/6J	
	ø20	20	M6×1	VPOD20-20K-1/6J	M6
		30		VPOD20-30K-1/6J	
		40		VPOD20-40K-1/6J	
		50		VPOD20-50K-1/6J	
	ø30	20	M6×1	VPOD30-20K-1/6J	M6
		30		VPOD30-30K-1/6J	
		40		VPOD30-40K-1/6J	
		50		VPOD30-50K-1/6J	
	ø40	20	M6×1	VPOD40-20K-1/6J	M6
		30		VPOD40-30K-1/6J	
		40		VPOD40-40K-1/6J	
		50		VPOD40-50K-1/6J	
	ø50	20	M6×1	VPOD50-20K-1/6J	M6
		30		VPOD50-30K-1/6J	
		40		VPOD50-40K-1/6J	
		50		VPOD50-50K-1/6J	

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Optional items
⇒ P.525

Fall
Prevention
Valve



Swivel
Joint for
vacuum pad



Filter



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Tube O.D. (mm)	Model code	Connection config. code	Pad dia. (mm)	Stroke (mm)	Tube O.D. (inch)	Model code	Connection config. code
Spring type, Side port, Push-in fitting, Low dust emission VPLFD 	ø10	5	ø3	VPLFD10-5K-1/6J	M4	ø10	5	ø1/8	VPLFD10-5K-1/6J	M4
			ø4	VPLFD10-5K-1/4J				ø5/32	VPLFD10-5K-1/32J	
		10	ø3	VPLFD10-10K-1/6J			10	ø1/8	VPLFD10-10K-1/6J	
			ø4	VPLFD10-10K-1/4J				ø5/32	VPLFD10-10K-1/32J	
		15	ø3	VPLFD10-15K-1/6J			15	ø1/8	VPLFD10-15K-1/6J	
			ø4	VPLFD10-15K-1/4J				ø5/32	VPLFD10-15K-1/32J	
		20	ø3	VPLFD10-20K-1/6J			20	ø1/8	VPLFD10-20K-1/6J	
			ø4	VPLFD10-20K-1/4J				ø5/32	VPLFD10-20K-1/32J	
	ø20	5	ø3	VPLFD20-5K-1/6J	M6	ø20	5	ø1/8	VPLFD20-5K-1/6J	M6
			ø4	VPLFD20-5K-1/4J				ø5/32	VPLFD20-5K-1/32J	
		10	ø6	VPLFD20-5K-1/6J			10	ø1/4	VPLFD20-5K-1/4J	
			ø3	VPLFD20-10K-1/6J				ø1/8	VPLFD20-10K-1/6J	
		15	ø4	VPLFD20-10K-1/4J			15	ø5/32	VPLFD20-10K-1/32J	
			ø6	VPLFD20-10K-1/6J				ø1/4	VPLFD20-10K-1/4J	
		20	ø3	VPLFD20-15K-1/6J			20	ø1/8	VPLFD20-15K-1/6J	
			ø4	VPLFD20-15K-1/4J				ø5/32	VPLFD20-15K-1/32J	
	ø30	5	ø6	VPLFD20-15K-1/6J		ø30	5	ø1/4	VPLFD20-15K-1/4J	M6
			ø3	VPLFD30-5K-1/6J				ø1/8	VPLFD30-5K-1/6J	
		10	ø4	VPLFD30-5K-1/4J			10	ø5/32	VPLFD30-5K-1/32J	
			ø6	VPLFD30-5K-1/6J				ø1/4	VPLFD30-5K-1/4J	
		15	ø3	VPLFD30-10K-1/6J			15	ø1/8	VPLFD30-10K-1/6J	
			ø4	VPLFD30-10K-1/4J				ø5/32	VPLFD30-10K-1/32J	
		20	ø6	VPLFD30-10K-1/6J			20	ø1/4	VPLFD30-10K-1/4J	
			ø3	VPLFD30-15K-1/6J				ø1/8	VPLFD30-15K-1/6J	
	ø40	5	ø4	VPLFD30-15K-1/4J		ø40	5	ø5/32	VPLFD30-15K-1/32J	M6
			ø6	VPLFD30-15K-1/6J				ø1/4	VPLFD30-15K-1/4J	
		10	ø3	VPLFD30-20K-1/6J			10	ø1/8	VPLFD30-20K-1/6J	
			ø4	VPLFD30-20K-1/4J				ø5/32	VPLFD30-20K-1/32J	
		15	ø6	VPLFD30-20K-1/6J			15	ø1/4	VPLFD30-20K-1/4J	
			ø3	VPLFD40-5K-1/6J			20	ø1/8	VPLFD40-5K-1/6J	
		20	ø4	VPLFD40-5K-1/4J			20	ø5/32	VPLFD40-5K-1/32J	
			ø6	VPLFD40-5K-1/6J				ø1/4	VPLFD40-5K-1/4J	
	ø50	5	ø3	VPLFD40-10K-1/6J		ø50	5	ø1/8	VPLFD40-10K-1/6J	M6
			ø4	VPLFD40-10K-1/4J				ø5/32	VPLFD40-10K-1/32J	
		10	ø6	VPLFD40-10K-1/6J			10	ø1/4	VPLFD40-10K-1/4J	
			ø3	VPLFD40-15K-1/6J			15	ø1/8	VPLFD40-15K-1/6J	
		15	ø4	VPLFD40-15K-1/4J			15	ø5/32	VPLFD40-15K-1/32J	
			ø6	VPLFD40-15K-1/6J			20	ø1/4	VPLFD40-15K-1/4J	
		20	ø3	VPLFD40-20K-1/6J			20	ø1/8	VPLFD40-20K-1/6J	
			ø4	VPLFD40-20K-1/4J				ø5/32	VPLFD40-20K-1/32J	
	ø50	5	ø6	VPLFD40-20K-1/6J		ø50	5	ø1/4	VPLFD40-20K-1/4J	M6
			ø3	VPLFD50-5K-1/6J				ø1/8	VPLFD50-5K-1/6J	
		10	ø4	VPLFD50-5K-1/4J			10	ø5/32	VPLFD50-5K-1/32J	
			ø6	VPLFD50-5K-1/6J			15	ø1/4	VPLFD50-5K-1/4J	
		15	ø3	VPLFD50-10K-1/6J			15	ø1/8	VPLFD50-10K-1/6J	
			ø4	VPLFD50-10K-1/4J			20	ø5/32	VPLFD50-10K-1/32J	
		20	ø6	VPLFD50-10K-1/6J			20	ø1/4	VPLFD50-10K-1/4J	
			ø3	VPLFD50-15K-1/6J				ø1/8	VPLFD50-15K-1/6J	
			ø4	VPLFD50-15K-1/4J				ø5/32	VPLFD50-15K-1/32J	
			ø6	VPLFD50-15K-1/6J				ø1/4	VPLFD50-15K-1/4J	
			ø3	VPLFD50-20K-1/6J				ø1/8	VPLFD50-20K-1/6J	
			ø4	VPLFD50-20K-1/4J				ø5/32	VPLFD50-20K-1/32J	
			ø6	VPLFD50-20K-1/6J				ø1/4	VPLFD50-20K-1/4J	

Notes

*Barb fitting type holders are also available.
Contact us for the details.



Packaging specifications
1 pc./bag

Optional items
⇒ P.525

Fall
Prevention
Valve



Swivel
Joint for
vacuum pad



Filter



RoHS2 (2011/65/EU+EU2015/863) compliant

Holder type	Pad dia. (mm)	Stroke (mm)	Male thread size	Model code	Connection config. code
Spring type, Side port, Female thread, Low dust emission VPLFD	ø10	5	M5×0.8	VPLFD10-5K[6]-M5	M4
		10	M5×0.8	VPLFD10-10K[6]-M5	
		15	M5×0.8	VPLFD10-15K[6]-M5	
		20	M5×0.8	VPLFD10-20K[6]-M5	
	ø20	5	M6×1	VPLFD20-5K[6]-M6	
		10	M6×1	VPLFD20-10K[6]-M6	
		15	M6×1	VPLFD20-15K[6]-M6	
		20	M6×1	VPLFD20-20K[6]-M6	
	ø30	5	M6×1	VPLFD30-5K[6]-M6	
		10	M6×1	VPLFD30-10K[6]-M6	
		15	M6×1	VPLFD30-15K[6]-M6	
		20	M6×1	VPLFD30-20K[6]-M6	
ø40	5	M6×1	VPLFD40-5K[6]-M6	M6	
	10	M6×1	VPLFD40-10K[6]-M6		
	15	M6×1	VPLFD40-15K[6]-M6		
	20	M6×1	VPLFD40-20K[6]-M6		
ø50	5	M6×1	VPLFD50-5K[6]-M6		
	10	M6×1	VPLFD50-10K[6]-M6		
	15	M6×1	VPLFD50-15K[6]-M6		
	20	M6×1	VPLFD50-20K[6]-M6		
Holder type					
Fixed type, Direct mount, Standard VPE					
*Pads with the same configuration code as the holder can be connected. (See Pad rubber only (page 377)). Metric male thread: M8, M10, M12, M14 Metric female thread: M5, M8 Taper pipe thread: R1/8, R1/4, R3/8, R1/2 Parallel pipe thread: G1/8, G1/4, G3/8, G1/2 NPT thread: NPT1/8, NPT1/4, NPT3/8, NPT1/2					
Applicable Screws					
Holder type	Pad dia. (mm)	Female thread size	Model code	12 -S3 -S3 spec.	Connection config. code
Spring type, Direct mount VPF	ø10	M14×1	VPF10K[6][8][12]	○	M4
	ø20	M14×1	VPF20K[6][8][12]	○	
	ø30	M14×1	VPF30K[6][8][12]	○	
	ø40	M14×1	VPF40K[6][8][12]	○	
	ø50	M14×1	VPF50K[6][8][12]	○	
Stroke 5.8mm					

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Options

8: -DC ⇒ Holder with dust catcher
12: -S3 ⇒ -S3 spec. (○ in the lists: Available)

*1. For ~S3 spec., the release ring color is dark blue, and the gasket material is FKM+SUS316.

2. For inch size push-in fitting, the release ring color is white even for ~S3 spec.




Optional items (○: -S3 spec. is available)

8 Dust Catcher: -DC

Optional	Connection config. code	-S3 spec.
Dust Catcher (-DC)	M4	○
	M6	○

Holder type
VPC | VPD | VPF



9 Fall Prevention Valve: -ECV


Optional	Connection config. code	Model code
Fall Prevention Valve (-ECV)	M4	ECVM4-FM4
	M6	ECVM6-FM6

Characteristics of Dust Catcher ▶ P.371

Characteristics of Fall Prevention Valve ▶ P.722

10 Swivel Joint: -FH, -FHH, -CFH

Optional	Swivel angle	Connection config. code	Model code
Ball Swivel Joint (-FH)	30° (-FH)	M4	FH10
		M6	FH20
	15° (-FHH)	M4	FH10-15
		M6	FH20-15



Optional	Connection config. code	-S3 spec.	Model code (*)
Flexible Swing Joint (-CFH)	M4	○	CFHM4-FM4
	M6	○	CFHM6-FM6

When ordering a Flexible Swing Joint alone, please enter ~S3 at the end of the model code for ~S3 specification.

Characteristics of Ball Swivel Joint ▶ P.724

Characteristics of Flexible Swing Joint ▶ P.725

Characteristics of Filter ▶ P.726

See the page 508 for the model designation including optional items.

Replacement parts

Pad screw Model code	12 -S3 -S3 spec.	Applicable pad dia. (mm)	Connection config. code
VPM46-6[12]	○	ø10	M4
VPM610-8[12]	○	ø20	
VPM612-10[12]	○	ø30	
VPM610-15[12]	○	ø40, ø50	

Plain washer Model code	Applicable pad dia. (mm)	Connection config. code
HW8.4×15.5×1.6	ø20, ø30	M6
HW8.5×22×1.6	ø40, ø50	

Pad support Model code	Applicable pad dia. (mm)	Connection config. code
VPW40	ø40	M6
VPW50	ø50	

Gasket Model code	Applicable pad dia. (mm)	Connection config. code
VPFG10	ø10~ø50	M4 M6


Rearrangement parts

Model code of Adapter for pad connection type conversion	12 -S3 -S3 spec.	Applicable pad dia. (mm)	Connection config. code Before → After
FVPL-FM4-M6[12]	○	ø10	M4 → M6

*1. This adapter is used to mount pad & screw set with M4 configuration code on a holder with M6 configuration code.
*2. Gasket for adapter is equipped with an Adapter.

Pad screw Model code	12 -S3 -S3 spec.	Applicable pad dia. (mm)
VPM56-7[12]	○	ø10
VPM510-8[12]	○	ø20
VPM512-9[12]	○	ø30
VPM510-13[12]	○	ø40, ø50

1. PISCO's Vacuum pad series consists of the combination of vacuum pads and holders.




2. Vacuum pad and pad holder have a specific connection type depending on the size and shape.

Pad connection type	Insert type (Direct connection)		Mount type (Direct connection)		Screw type (Connection with screw)	
Connection configuration code	H3		T4 T8 T15 T40 (Exclusive to soft type & soft bellows type vacuum pads) PB8 PB15 (Exclusive to Vacuum pad for packaging bag) E10 E20 (Exclusive to Oval type vacuum pad)		M4 M6 M10 M20 G1 G2 G3 G4	

*As shown in above drawings, Vacuum pad and pad holder are connected with a screw or a rim.

3. Any Vacuum pad and pad holder can be connected, as long as their connection configuration codes are same.



If you have purchased a pad and holder set but want to install a different pad or replace the holder with a different one...
→Please check the connection configuration code of your pad or pad holder and select the one that matches the configuration code.

4. Please refer to the below chart for the "Connection Configuration Code". *Configuration codes are also listed on the page of model code list for each product.

Connection configuration code list (Holder)

Common holder

	Fixed type		Mini	Slim	Spring type		No cover	Low dust emission
	Mini	Standard			Standard			
Code	VPMA	VPA	VMC	VPSC	VPC	VPOC	VPLFC	
Type								
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	H3 T8	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPMB	VPB	VPMD	—	VPD	VPOD	VPLFD	
Type				—				
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T4 T8 M4 M6	—	H3 T8 M4 M6 M10 M20 G1 G2 G3 G4	T8 M4 M6	T4 T8 M4 M6	
Code	VPME	VPE	—	—	VPF	*Holders with configuration code: G1 to G4 can be connected to VPE holders.		
Type			—	—		Holder with configuration code: G1, G2, G3 and G4 VPE holder (Male thread: G1, G2, G3, and G4) Vacuum Pad		
Configuration code	T4 T8 M4 M6	H3 T8 M4 M6 M10 M20 T15 T40	—	—	H3 T8 M4 M6			

Common holder (Lightweight/Low profile)

	Top port		Side port	Dual side port
	Code	VPHC		VPHD
Type				
Configuration code	T15 T40 M4 M6	T15 T40 M4 M6	T15 T40 M4 M6	T15 T40 M4 M6
Code	—	VPHE	—	VPHEW
Type	—		—	
Configuration code	—	T15 T40 M4 M6	—	T15 T40 M4 M6

Special holder *Pads of other shapes cannot be installed.

	Top port		Side port
	Code	VPA	VPB
Type			
Configuration code	E10 E20	E10 E20	E10 E20
Code	—	VPA	VPE
Type	—		
Configuration code	—	PB8 PB15	PB8 PB15

Connection configuration code list (Pad) (○: Available)

Pad type or application	Standard														Pad type or application
	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Pat Large suction flow type	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	
Code	R	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	E
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

Some combinations are possible by using a conversion screw adapter.

H3, T4 and T8 can be converted to M4 or M6. M4 to M6 conversion is also available. For details, please see "Rearrangement parts" of each pad type.

Model Designation (Example)



(1) Vacuum Pad

(2) Pad size (3) Pad type (6) Connection configuration code *Required for Pad & screw set only. (○: Available)

Pad type or application	Small	General	Deep	Bellows	Multi-bellows	Metal detectable	Skidproof	Flat (Large suction flow type)	Mark-free	Soft	Soft bellows	Sponge	Ultrathin	For packaging bag	Pad type or application
Code	RM	R	A	B	W	BE, BD	K	F, FH	Q	L	LB	S	P	PB	Code
0.7	○	○	○	○	○	○	○	○	○	○	○	○	○	○	2x4
1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	3.5x7
1.5	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x10
2	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x10
3	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x10
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x20
6	○	○	○	○	○	○	○	○	○	○	○	○	○	○	4x30
8	○	○	○	○	○	○	○	○	○	○	○	○	○	○	5x30
10	○	○	○	○	○	○	○	○	○	○	○	○	○	○	6x30
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x20
20	○	○	○	○	○	○	○	○	○	○	○	○	○	○	8x30
25	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
30	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
35	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
40	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
50	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
60	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
70	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
80	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
100	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
150	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
200	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

(4) Pad material (○: Available)

Code	N	S	U	F	SE	NE	G	HN	EP	FS	NH	YS2	YS4	MSF3	MSF5	MSS3	MSS5
Rubber material	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	Food Sanit. Act compliant NBR	HNBR	EPDM	Fluoro-silicone	Oil proof NBR	Extra soft silicone	Iron powder type	SUS powder type	Metal detectable silicone		
Pad color	Black	Clear white	Dark blue	Gray	Black	Black	Light gray	Black	Black	Red-orange	Black	Pink	Blue	Reddish-brown	Dark-green	Brown	Green
Material code marking ¹⁾	None	None	None	None	SE	NE	None	HN	EP	None	None	None	None	SF	SF	SS	SS
Standard	General	Deep	Small	Soft	Soft bellows	Skidproof	Bellows	Multi-bellows	For packaging bag	Metal Detectable	Ribs (Bellows with bumps)	Ultrathin	Flat	Flat large suction flow	Oval		
Code	R	A	RM	L	LB	K	B	W	PB	BE	BD	P	F	FH	E		

● Mark-free type (Pad type code: Q)

Code	K	M	KE
Resin material	PEEK	POM	Conductive PEEK
Pad color	Beige	White	Black

● Sponge type (Pad type code: S)

Code	S	C
Rubber material	Silicone	Chloroprene
Pad color	Dark-orange	Black

*1. For vacuum pads in black color (SE: Conductive silicone, NE: Conductive NBR (low resistance), HN: HNBR and EP: EPDM) and Vacuum pad Metal Detectable type, the pad material code is marked on the top or the side of the vacuum pad for material identification. (The marking on black vacuum pads has started since Oct. 2023 gradually.)



*2. Some materials are not available depending on pad size. Please see the catalog for details.

*3. Pad color of pads for Packaging bag. Lip hardness 20° (Pink) Lip hardness 40° (Blue)

*4. The Conductive Silicone rubber (SE) is a silicon rubber capable of releasing static electricity. (Volume resistance: More than 200 Ω·cm and 10⁵ Ω·cm or less)

*5. Nitrile rubber (N), Conductive NBR (Low resistance, Volume resistance: 200Ω·cm or less) (NE), Food Sanitation Act-compliant NBR (G), Oil proof NBR (NH) are not suitable for use with ozone environment.

*6. Extra soft silicone (YS2/YS4), Metal detectable silicone and Silicone for Packaging bag are compliant with Food Sanitation Act and FDA.

*7. Volume resistance of Conductive PEEK (KE) is 10⁵ to 10⁶ Ω·cm.

(5) Surface treatment (Optional) (○: Available)

Code			No code	-NF	-SF	-DL	-ER	-FG	
Surface treatment			None	Fiber surface		DLC. coating	Reformed surface	Fluoro-coating	
				Nylon fiber	Silk fiber				
			—						
Applicable pad material			—	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F)	Silicone (S) Fluoro (F) Conductive silicone (SE)	Nitrile (N) Conductive NBR (NE)	Silicone (S) Conductive silicone (SE) Extra soft silicone (YS2, YS4)	
Pad type	Standard	General	R	—	○	○	○	○	
		Deep	A	—	○	○	○	○	
		Small	RM	—	—	—	○	○	
	Soft	L	—	○	○	○	○	○	
		Soft bellows	LB	—	○	○	○	○	○
		Skidproof	K	—	—	—	—	—	—
	Bellows	B	—	○	○	○	○	○	
		Multi-bellows	W	—	—	—	○	○	○
	For packaging bag	PB	—	—	—	—	—	○	
	Metal Detectable	BE,BD	—	—	—	—	—	—	
	Ultrathin	P	—	—	—	○	○	○	
	Flat	F	—	—	—	○	○	○	
	Flat large suction flow	FH	—	—	—	○	○	○	
	Mark-free	Q	—	—	—	—	—	—	
Sponge	S	—	—	—	—	—	—		
Oval	E	—	—	—	○	○	○		

*Some surface treatments are not available depending on pad size.

Please refer to page 370 for the details of each pad surface type and treatment for Suction Mark-free.


(6) Connection configuration code (Required for Pad & screw set only.) Please refer to the Pad size and type list on the 374 page.

Code	No code	-M4	-M6	-M10	-M20	-M5 ^(*)
Connection config. code	—	M4	M6	M10	M20	—
Thread size	Pad rubber only	M4×0.7	M6×1	M10×1.5	M20×2	M5×0.8

*M5 thread is used for mounting on non-PISCO holders. Contact us for the price of screw set.

(7) Mark-free resin attachment material (Bellows type only) (Optional)

Code	No code	-QK	-QM	-QKE
Resin material	—	PEEK	POM	Conductive PEEK (Volume resistance: 10 ⁵ to 10 ⁶ Ω·cm)
	—			



*1. Selectable for Bellows type pad dia. 10 to 30 mm.

*2. Resin attachment cannot be installed when selecting surface treatment.

*3. Resin attachment cannot be installed when selecting Extra soft silicone for pad material.

(8) -S3 spec. (Required for Pad & screw set only) (Optional)

Code	No code	-S3
Metal material	Standard	No copper-based metallic materials used in flow paths

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code (M4 , M6 etc.)" can be connected. For connectable holders, please see the page of Pad holder only (page 384-).



Bellows series,

Pad rubber alone



P526

Model code	○: Available as standard item										Connection config. code
	④ Pad rubber material										
	N	S	YS2	YS4	U	F	SE	NE	HN	EP	
	Nitrile	Silicone	Extra soft silicone ⁽²⁾ Hardness 20 [*]	Hardness 40 [*]	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM	
VP2B④	○	○	—	—	—	—	—	—	—	—	H3
VP4B④	○	○	—	—	—	—	○	—	—	—	
VP6B④⑤	○	○	—	—	○	○	○	○	○	○	T8
VP8B④⑤	○	○	—	—	○	○	○	○	○	○	
VP10B④⑤	○	○	(*)	(*)	○	○	○	○	○	○	M4③
VP15B④⑤	○	○	(*)	○	○	○	○	○	○	○	
VP20B④⑤	○	○	○	○	○	○	○	○	○	○	M6③
VP25B④⑤	○	○	○	○	○	○	○	○	○	○	
VP30B④⑤	○	○	○	○	○	○	○	○	○	○	
VP40B④⑤	○	○	○	○	○	○	○	○	○	○	
VP50B④⑤	○	○	○	○	○	○	○	○	○	○	
VP60B④⑤	○	○	—	—	○	○	○	○	○	○	M10③
VP80B④⑤	○	○	—	—	○	○	○	○	○	○	
VP100B④⑤	○	○	—	—	○	○	○	○	○	○	



Bellows series,
Pad & screw set

P526

Model code	○: Available as standard item										Connection config. code	
	④ Pad rubber material											⑧
	N	S	YS2	YS4	U	F	SE	NE	HN	EP		-S3
	Nitrile	Silicone	Extra soft silicone ⁽²⁾ Hardness 20*	Hardness 40*	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM		-S3 spec.
VP10B④⑤-M4⑧	○	○	(*)	(*)	○	○	○	○	○	○	○	M4
VP15B④⑤-M4⑧	○	○	(*)	○	○	○	○	○	○	○	○	
VP20B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP25B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP30B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	M6
VP40B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP50B④⑤-M6⑧	○	○	○	○	○	○	○	○	○	○	○	
VP60B④⑤-M10	○	○	—	—	○	○	○	○	○	○	(*)	M10
VP80B④⑤-M10⑧	○	○	—	—	○	○	○	○	○	○	○	
VP100B④⑤-M10⑧	○	○	—	—	○	○	○	○	○	○	○	

■ Available pad size and material for surface treatment (Bellows series)

Pad dia. (mm)	⑤ Surface treatment code					Model code	YS2	YS4	⑧	-S3	-S3 spec.	Connection config. code
	-NF	-SF	-DL	-ER	-FG							
	Fiber surface Nylon	Silk coating	DLC coating	Reformed surface	Fluoro-coating (S, SE) (YS2, YS4)							
φ6	—	—	○	○	○	—	—	—	—	—	—	M4③
φ8	—	—	○	○	○	—	—	—	—	—	—	
φ10	—	—	○	○	○	—	—	—	—	—	—	
φ15	○	○	○	○	○	○	○	○	○	○	○	
φ20	○	○	○	○	○	○	○	○	○	○	○	
φ25	○	○	○	○	○	○	○	○	○	○	○	
φ30	○	○	○	○	○	○	○	○	○	○	○	
φ40	○	○	○	○	○	○	○	○	○	○	○	
φ50	○	○	○	○	○	○	○	○	○	○	○	
φ60	○	○	—	○	○	—	—	—	—	—	—	
φ80	○	○	—	—	○	—	—	—	—	—	—	M4
φ100	—	—	—	—	○	—	—	—	—	—	—	
Material	S, F	S, F, SE	N, NE	S, SE, YS2, YS4								

- Notes
- *1. For Pad & screw set of Bellows series 60 mm pad dia., the standard spec. is equivalent to "-S3" spec.
- *2. Extra soft silicone is compliant with Food Sanitation Act and FDA.
- *3. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.

CAD data is available at PISCO website.

Packaging specifications 1 pc./bag

Options

⑤ : Surface treatment

⑧ : -S3 ⇒ -S3 spec.

Holders with the same "connection configuration code (M4 , M6 etc.)" can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Bellows series, with Resin attachment

P526

Picture of mark-free resin attachment with pad

By attaching a resin attachment, bellows pad (pad dia.: 10 to 30 mm) can be used as Mark-free pad.

Model code	○: Available as standard item								Connection config. code	
	④ Pad rubber material									
	N	S	U	F	SE	NE	HN	EP		
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM		
VP10B④-QK	○	○	○	○	○	○	○	○	M4③	
VP10B④-QM	○	○	○	○	○	○	○	○		
VP10B④-QKE	○	○	○	○	○	○	○	○		
VP15B④-QK	○	○	○	○	○	○	○	○		
VP15B④-QM	○	○	○	○	○	○	○	○		
VP15B④-QKE	○	○	○	○	○	○	○	○	M6③	
VP20B④-QK	○	○	○	○	○	○	○	○		
VP20B④-QM	○	○	○	○	○	○	○	○		
VP20B④-QKE	○	○	○	○	○	○	○	○		
VP25B④-QK	○	○	○	○	○	○	○	○		
VP25B④-QM	○	○	○	○	○	○	○	○		
VP25B④-QKE	○	○	○	○	○	○	○	○	M10③	
VP30B④-QK	○	○	○	○	○	○	○	○		
VP30B④-QM	○	○	○	○	○	○	○	○		
VP30B④-QKE	○	○	○	○	○	○	○	○		

Pad holder

● How to attach

- (1) Fix a bellows pad and a pad holder with a pad screw.
- (2) Attach a resin attachment to the bellows pad.


Bellows
pad

Pad screw

Resin
attachment

Picture of mark-free resin attachment with pad

By attaching a resin attachment, bellows pad (pad dia.: 10 to 30 mm) can be used as Mark-free pad.





Bellows series,

Pad & screw set + Resin attachment



P526

Model code	○: Available as standard item									Connection config. code
	④ Pad rubber material									
	N	S	U	F	SE	NE	HN	EP	-S3	
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)	HNBR	EPDM	-S3 spec.	
VP10B④-M4-QK⑧	○	○	○	○	○	○	○	○	○	M4
VP10B④-M4-QM⑧	○	○	○	○	○	○	○	○	○	
VP10B④-M4-QKE⑧	○	○	○	○	○	○	○	○	○	
VP15B④-M4-QK⑧	○	○	○	○	○	○	○	○	○	
VP15B④-M4-QM⑧	○	○	○	○	○	○	○	○	○	
VP15B④-M4-QKE⑧	○	○	○	○	○	○	○	○	○	M6
VP20B④-M6-QK⑧	○	○	○	○	○	○	○	○	○	
VP20B④-M6-QM⑧	○	○	○	○	○	○	○	○	○	
VP20B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○	
VP25B④-M6-QK⑧	○	○	○	○	○	○	○	○	○	
VP25B④-M6-QM⑧	○	○	○	○	○	○	○	○	○	
VP25B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○	M10
VP30B④-M6-QK⑧	○	○	○	○	○	○	○	○	○	
VP30B④-M6-QM⑧	○	○	○	○	○	○	○	○	○	
VP30B④-M6-QKE⑧	○	○	○	○	○	○	○	○	○	



Mark-free resin attachment for

Bellows series



P526

Model code	○: Available as standard item		
	④ Resin attachment material		
	K	M	KE
	PEEK	POM	Conductive PEEK
VP10BQ④-AT	○	○	○
VP15BQ④-AT	○	○	○
VP20BQ④-AT	○	○	○
VP25BQ④-AT	○	○	○
VP30BQ④-AT	○	○	○

Mark-free resin attachment for Bellows series

Model code	○: Available as standard item		
	④ Resin attachment material		
	K	M	KE
	PEEK	POM	Conductive PEEK
VP10BQ④-AT	○	○	○
VP15BQ④-AT	○	○	○
VP20BQ④-AT	○	○	○
VP25BQ④-AT	○	○	○
VP30BQ④-AT	○	○	○

- Notes
- *1. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- *2. Resin attachment must be used with a vacuum pad for work conveyance.

CAD data is available at PISCO website.

Packaging specifications 1 pc./bag

Options

⑧ : -S3 ⇒ -S3 spec.

Vacuum pad / Pad & screw set

Holders with the same "connection configuration code" (M4, M6 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Flat series, Pad rubber alone										Flat series, Pad & screw set									
○: Available as standard item										○: Available as standard item									
Model code	④ Pad rubber material						Connection config. code	Model code	④ Pad rubber material						Connection config. code				
	N	S	U	F	SE	NE			N	S	U	F	SE	NE		-S3			
	Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Urethane	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.			
VP10F④⑤	○	○	○	○	○	○	M4⑧⑨	VP10F④⑤-M4⑧	○	○	○	○	○	○	○	M4			
VP15F④⑤	○	○	○	○	○	○		VP15F④⑤-M4⑧	○	○	○	○	○	○	○				
VP20F④⑤	○	○	○	○	○	○	M6⑧⑨	VP20F④⑤-M6⑧	○	○	○	○	○	○	○	M6			
VP25F④⑤	○	○	○	○	○	○		VP25F④⑤-M6⑧	○	○	○	○	○	○	○				
VP30F④⑤	○	○	○	○	○	○		VP30F④⑤-M6⑧	○	○	○	○	○	○	○				

 Flat large suction flow series, Pad rubber alone							 Flat large suction flow series, Pad & screw set							
○: Available as standard item							○: Available as standard item							
Model code	④ Pad rubber material					Connection config. code	Model code	④ Pad rubber material					Connection config. code	
	N	S	F	SE	NE			N	S	F	SE	NE		⑤
	Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)			Nitrile	Silicone	Fluoro	Conductive silicone	Conductive NBR (Low resistance)		-S3 spec.
VP10FH④⑤	○	○	○	○	○	M4⑧	VP10FH④⑤-M4⑧	○	○	○	○	○	○	M4
VP15FH④⑤	○	○	○	○	○		VP15FH④⑤-M4⑧	○	○	○	○	○	○	
VP20FH④⑤	○	○	○	○	○	M6⑧	VP20FH④⑤-M6⑧	○	○	○	○	○	○	M6
VP25FH④⑤	○	○	○	○	○		VP25FH④⑤-M6⑧	○	○	○	○	○	○	
VP30FH④⑤	○	○	○	○	○		VP30FH④⑤-M6⑧	○	○	○	○	○	○	

									
Mark-free series, Resin pad alone				Mark-free series, with Flexible Swing Joint					
Model code	○: Available as standard item			Connection config. code	Model code	○: Available as standard item			Connection config. code
	④ Pad rubber material					④ Pad rubber material			
	K	M	KE			K	M	KE	
	PEEK	POM	Conductive PEEK			PEEK	POM	Conductive PEEK	-S3 spec.
VP10Q④	○	○	○	M4①①	VP10Q④-M4⑧	○	○	○	M4
VP20Q④	○	○	○	M6①①	VP20Q④-M6⑧	○	○	○	M6
VP30Q④	○	○	○		VP30Q④-M6⑧	○	○	○	



Sponge series, Pad rubber alone

P.656



Sponge series, Pad & screw set

P.656

○: Available as standard item ④ Pad rubber material C S Chloroprene Silicone				Connection config. code	○: Available as standard item ④ Pad rubber material ⑧ C S -S3 Chloroprene Silicone -S3 spec.				Connection config. code
Model code					Model code				
VP10S④	○	○		M8④	VP10S④-M6⑧	○	○		M8
VP15S④	○	○			VP15S④-M6⑧	○	○		
VP20S④	○	○			VP20S④-M6⑧	○	○		
VP25S④	○	○			VP25S④-M6⑧	○	○		
VP30S④	○	○			VP30S④-M6⑧	○	○		
VP35S④	○	○		M10④	VP35S④-M6⑧	○	○		M10
VP50S④	○	○			VP50S④-M6⑧	○	○		
VP70S④	○	○			VP70S④-M10	○	○	(*)	
VP100S④	○	○			VP100S④-M10	○	○	(*)	

- Notes**
- *1. A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- *2. A Flexible Swing Joint is required to mount on the holder. If you do not have a Flexible Swing Joint, please select from the Mark-free series, with Flexible Swing Joint set.
- *3. For Pad & screw set of Sponge series 70 mm and 100 mm pad dia., the standard spec. is equivalent to "-S3" spec.

CAD data is available
at PISCO website.

Packaging specifications
1 pc./bag

Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Holders with the same "connection configuration code" (E10, E20 etc.) can be connected. For connectable holders, please see the page of Pad holder only (page 384-).

Oval series, Pad rubber alone												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP				
VP2×4E④⑤	○	○	○	○	○	○	○	○				
VP3.5×7E④⑤	○	○	○	○	○	○	○	○				
VP4×10E④⑤	○	○	○	○	○	○	○	○				
VP4×20E④⑤	○	○	○	○	○	○	○	○				
VP4×30E④⑤	○	○	○	○	○	○	○	○				
VP5×10E④⑤	○	○	○	○	○	○	○	○				
VP5×20E④⑤	○	○	○	○	○	○	○	○				
VP5×30E④⑤	○	○	○	○	○	○	○	○				
VP6×10E④⑤	○	○	○	○	○	○	○	○				
VP6×20E④⑤	○	○	○	○	○	○	○	○				
VP6×30E④⑤	○	○	○	○	○	○	○	○				
VP8×20E④⑤	○	○	○	○	○	○	○	○				
VP8×30E④⑤	○	○	○	○	○	○	○	○				

Oval series, Pad & screw set												
Model code	○: Available as standard item											
	④ Pad rubber material											
	N	S	U	F	SE	NE	HN	EP	-S3			
VP2×4E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP3.5×7E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP4×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP5×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×10E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP6×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×20E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			
VP8×30E④⑤-M6⑧	○	○	○	○	○	○	○	○	○			


- Notes**
- *A pad screw is required to mount on the holder. If you do not have a pad screw, please select from the Pad & screw set.
- CAD data is available
at PISCO website.
- Packaging specifications
1 pc./bag
- Options
⑤ : Surface treatment
⑧ : -S3 ⇒ -S3 spec.

Available pad size and material
for surface treatment
(Oval series)


Pad dia. (mm)	⑤ Surface treatment code		
	-DL DLC coating	-ER Reformed surface	-FG Fluoro- coating
2×4	○	○	○
3.5×7	○	○	○
4×10	○	○	○
4×20	○	○	○
4×30	○	○	○
5×10	○	○	○
5×20	○	○	○
5×30	○	○	○
6×10	○	○	○
6×20	○	○	○
6×30	○	○	○
8×20	○	○	○
8×30	○	○	○
Material	S, F, SE	N, NE	S, SE

Vacuum Pad Configuration


Pad dia. : $\phi 0.7, \phi 1, \phi 1.5, \phi 2, \phi 3, \phi 4$ mm





Pad dia. : $\phi 1, \phi 2, \phi 3, \phi 4$ mm



Pad dia. : $\phi 6, \phi 8, \phi 10, \phi 15, \phi 20$ mm






Pad dia. : $\phi 4, \phi 6, \phi 8, \phi 10, \phi 15$ mm






Vacuum Pad Configuration




Pad dia. : $\varnothing 10$, $\varnothing 15$, $\varnothing 20$, $\varnothing 25$, $\varnothing 30$, $\varnothing 35$, $\varnothing 40$, $\varnothing 50$ mm



Pad dia. : $\varnothing 60$, $\varnothing 70$, $\varnothing 80$, $\varnothing 100$ mm




Pad dia. : $\varnothing 150$, $\varnothing 200$ mm




Vacuum Pad Configuration


● Pad dia. : $\varnothing 4, \varnothing 6, \varnothing 8, \varnothing 10, \varnothing 15$ mm (Exclusive to Soft and Soft Bellows type)




● Pad dia. : $\varnothing 20, \varnothing 30, \varnothing 40$ mm (Exclusive to Soft and Soft Bellows type)




● Pad dia. : $\varnothing 20, \varnothing 25$ mm (Exclusive to Vacuum pad for packaging bag)



● Pad dia. : $\varnothing 30, \varnothing 40, \varnothing 50$ mm (Exclusive to Vacuum pad for packaging bag)



● Pad size : 2×4, 3.5×7, 4 to 6×10 mm (Exclusive to Oval type)



● Pad size : 4 to 8×20 mm, 4 to 8×30 mm (Exclusive to Oval type)

